

Design and commissioning experience with state of the art MPS for LEReC accelerator

S. Seletskiy (on behalf of LEReC team)

ERL 2019

BROOKHAVEN
NATIONAL LABORATORY



MPS subsystems experts


- Zeynep Altinbas – MPS engineer (MPS controller, MPS interaction with various subsystems etc.)
- Rob Hulsart – BPMs
- Toby Miller – diagnostics in general, insertable devices and BLMs in particular
- Matt Paniccia – FCTs
- Kevin Mernick – RF system and overall timing system
- Don Bruno – gun
- Patrick Inacker – laser
- Loralie Smart – vacuum system
- Sergei Seletskiy – conceptual design, coordination & administration

What is LEReC?


- Low Energy RHIC electron Cooler (LEReC) is the world's first RF-based (“bunched”) electron cooler
- LEReC is the first electron cooler which is applied directly to the ions in the collider at top energy
- LEReC is the first electron cooler that utilizes the same electron beam for cooling ions in two consecutive cooling sections in two rings of the collider
- LEReC is an important part of low energy RHIC run dedicated to search of the QCD critical point in the nuclear matter phase diagram
- Since LEReC uses RF acceleration of the bunched beam it can be easily scaled for high energy applications

Accelerator layout

180° bend



i-bunch
e-macrobunch (30 704 MHz e-bunches)



- 704 MHz e-bunches (chopped into 9 MHz macrobunches) are produced from photocathode and accelerated in gun to 400 keV
- Electrons are accelerated to design energy (1.6 MeV, 2 MeV, 2.6 MeV) in 704 MHz SRF Booster
- e-bunches are brought to Yellow and then Blue RHIC cooling sections (20 m long) where they co-travel with ion bunches with the same average velocity

- Operational beam current is 35-55 mA (baseline with trains); CW 85 mA (1.6 MeV), 67 mA (2 MeV)
- Operational beam power is <140 kW
- The smallest transverse RMS beam size in the LEReC (Merger beamline) is 0.25 mm

Time structure of LEReC beam


- Continuous sequence of 9 MHz macro-bunches or
- Trains (of length Δt) of 9 MHz macro-bunches repeated with frequency (f)

Q_b – charge per bunch (operational 130 pC)

N_b – number of bunches per macro-bunch (operational 30)

Δt – length of train of macro-bunches

N_{mb} – number of macro-bunches per train



Beam modes

Timing Pattern	Beam modes	Goals	Power
$N_b = 30$ $N_b * N_{mb} * Q_b \leq 40 \text{ nC}$ $f = 1 \text{ Hz}$	Low Current Mode (LCM); $Q_b = 30 - 200 \text{ pC}$	Set beam optics & RF for nominal Q_b . Measure and fine-tune bunch parameters.	$P \leq 16 \text{ mW}$ $I \leq 40 \text{ nA}$
$N_b = 10, 15, 20, 25, 30$ $\Delta t \leq 250 \text{ us}$ $T = 1 \text{ s} - 5 \text{ s}$	RF Studies Mode (RFSM); $Q_b \leq 200 \text{ pC}$	RF fine-tuning. Study beam loading.	$P \leq 7 \text{ W}$ $I \leq 3 \text{ uA}$
$N_b = 30$ $N_{mb} = 1-6$ $f = 76 \text{ kHz}$	76 kHz Mode (76M) $Q_b \leq 200 \text{ pC}$	Obtain and optimize cooling of several ion bunches	$P \leq 7 \text{ kW}$ $I \leq 2.7 \text{ mA}$
$N_b = 30$ $f = 9 \text{ MHz}$	High current Mode (HCM); $Q_b = 30 - 200 \text{ pC}$	Getting cooling of all ion bunches.	$P = 142 \text{ kW}$ $I \leq 55 \text{ mA}$
704 MHz CW	CW Mode (CWM); $Q_b = 95 - 120 \text{ pC}$	Alternative to HCM.	$P = 136 \text{ kW}$ $I = 68 - 85 \text{ mA}$

RFSM – has not been needed yet

CWM – is almost certainly obsolete

2.6 MeV – is obsolete. Hence, expected average power is reduced

MPS parameters

- We considered various failure scenarios resulting in the wrong power beam hitting various in-vacuum components: YAG screens, Vacuum Valves, Emittance Slits, Dumps, RF cavities and Vacuum Chamber
- As a result we identified the critical MPS parameters:

MPS Parameters	Value
Current threshold for ultimately safe operation mode (USOM)	40 nA
Reaction time (focused acute loss)	40 us
Tolerable routine distributed losses (halo scraping)	100 uA
Reaction time for small (up to 0.5 mA) distributed losses	1 s

The MPS reaction time was derived under assumption that beam optics studies are performed in LCM only and that in HCM the beam trajectory is kept in some reasonable range and that several critical magnet power supply currents are kept at operational values.


List of MPS devices

- Fast diagnostic (overall reaction time from fault detection to machine interlock <20 us):
 - Beam loss monitors (BLMs) – for fast loss detection
 - Fast current transformer (FCTs) – for measuring beam current. FCT processing scheme involves integrating charge accumulated in the 1 s moving window.
 - BPMs – to control beam trajectory
- Slow diagnostic:
 - Vacuum gauges
 - Dumps water flow and temperature
 - Beamline and dumps temperature
 - RF cavities “health” and compliance
 - Gun “health” and HVPS compliance
 - Insertable devices in/out status
 - Cryogenics temperature
- Monitoring bends to control beam trajectory and several critical solenoids to control focusing
- MPS interlocks the machine by blocking the photocathode laser beam

Requesting ½ of safe reaction time

MPS Logic (I)

- MPS works with Machine Modes (MM)
- MM is defined by where the beam is supposed to land (determined from dipoles settings)
- Each MM has the safe current (SC) associated with it
- Actual beam current (ABC) is measured by the FCT
- If $ABC > SC$ then the beam is interlocked



MPS Logic (II)

Beam modes	MPS operation
Low Current Mode (LCM); $I \leq 40 \text{ nA}$	Allowed: everything Monitored: HVPS, BLMs, Vacuum, RF health & compliance
RF Studies Mode (RFSM); $I \leq 3 \text{ uA}$	Allowed: RF YAG exposure to beam Monitored: HVPS, BLMs, Vacuum, IDs, BPMs, Gun-Booster mags, RF YAG wheel, RF health & compliance
HCM or CWM ($P \leq 10 \text{ kW}$); 76 kHz mode	Prohibited: going to RF line Monitored: HVPS, BLMs, Vacuum, IDs, BPMs, Gun-Booster mags, RF health & compliance
High current Mode (HCM); CW Mode (CWM); $P > 10 \text{ kW}$	Prohibited: going to RF line, going to 10 kW line Monitored: HVPS, BLMs, Vacuum, IDs, BPMs, Gun-Booster mags, RF health & compliance

MPS Logic (III)

It's HCM but
beam P<10kW

Level 0 \ Level 1 \ Level 2 \ Level 3 \ Level 4

Level 3 - 10kW Mode OFF Fri 07/12 20:59:59 2019

Pockels Cell Interlock Fault Fri 07/12 20:59:59 2019

Slow Shutter Interlock Fault Fri 07/12 20:59:59 2019

AOM Interlock Fault Fri 07/12 20:59:59 2019

Beam Destination: Level3-HiPwr_Dump


10 kW Dump \ 140 kW Dump \ No Destination

	Status	Enable	Relative Fault Time		Status	Enable	Relative Fault Time
Inject Dipole at Zero	OK			Merger Dipole in Range	OK		0
DC Gun HVPS Fault Stat	OK		0	RF 2.1 GHz Status	OK		
DC Gun HVPS in Range	OK		0	RF 2.1 GHz Compliance	OK		
FCT/Laser Differential	OK		0	RF 9 MHz Status	OK		
SRF Cavity Health	OK		0	RF 9 MHz Compliance	OK		
SRF Cavity Compliance	OK		0	Dechirp Cavity Status	OK		0
BLM Card A	OK		0	Dechirp Cavity Comply	OK		0
BLM Card B	OK		0	RF/Laser Locked	Disabled		0
BPM (Gun/Booster)	OK		0	Cryo	OK		0
BPM (Transport)	OK		0	InsertDev: Gun/Booster	OK		0
BPM (Cooling Section)	Fault		1	InsertDev: Transport	OK		0
Gun Corrs in Range	OK		0	InsertDev: Cool Section	OK		0
Gun Solenoids in Range	OK		0	Water: 140kW Dump	OK		0
CS Dipole in Range	OK		0	Temp: Beam Line	OK		0
180 Dipole in Range	OK		0	Temp: Extraction Line	OK		0
Extract Dipole in Range	OK		0	Valve Summary	OK		0
Dump Dipole in Range	OK		0	Vacuum Summary	OK		0
Quad Q7 in Range	OK		0	Temp: 140 Ceramic	OK		0
Quad SP Sol in Range	OK		0	Temp: 140 Copper	OK		0
FCT Diff 140kW	OK		0	Water Flow 140 Flange	OK		0
DCCT FC Diff 140kW	OK		0	Water Temp 140 Flange	OK		0


MPS tripped on beam
position in cooling
section

Beam goes
to HP dump

MPS Logic (IV)





MPS – Laser interface



- The MPS is interlocking the machine by switching off the (train shaping) Pockels cell and the intensity feedback AOM and by closing the mechanical shutters
- The measured closing time of AOM is 130 ns

Current measurements



- Fast current transformer (FCT) is always engaged and providing the current measurements to the MPS.
- First laser-produced e-beam was obtained on May 5th 2017, FCT signal was observed right away.
- Beam-based calibration of the FCT involved comparing its response to the beam charge measured with FCs and later with DCCT.
- The FCT reliably determines and sets MPS current levels as long as charge/bunch ≥ 0.7 pC.



- For the sake of superfluity, when CW settings are detected (half-wave plate is inserted and laser shutter is open) we automatically assume that we are in HCM
- We do the same for 76M – whenever MPS detects that timing system is set to 76 kHz and that the shutter is open the HCM is assumed.


BPMs

- BPMs have been reliably interlocking the MPS whenever the beam trajectory was moved out of the allowed range both in the pulsed and in the CW modes.
- For instance, BPMs were interlocking the MPS because of trajectory change along the train of macrobunches due to the beam loading or due to instability of the gun PS.



BLMs


- Beam loss monitors (BLMs) are PMTs retrofitted with few feet long scintillating fiber
- BLMs cover the whole accelerator
- BLMs detect losses in all directions



- We set BLMs to trigger the MPS trip at the radiation levels equivalent to the loss of 40 nQ pulsed beam on the insertable devices. Although this setting might be too conservative, it did allow us to operate 30 mA beam.
- The only nuisance was that during the RHIC injections (when injection lattice is not optimized) BLMs were triggered by ion losses causing LEReC MPS trips.

BLMs operation and upgrade

- Up to this point we used 1 mm diameter scintillating plastic optical fibre (POF) and it worked fine.
- Yet it was noticed that increased power of testing in CW mode has caused ~17% darkening in some of the fibers.
- An undoped quartz fiber was tested and found to have a response of 85% of that of the POF; which can be compensated for with increased bias voltage. Thus, a 1.5 mm quartz fiber in armoured sheath with SMA terminations is ordered in 16 lengths of 3 – 13 m to replace the POF covering the entire 100 m of the LEReC beam line.
- A test of the Libera BLM board was made with one of the BLMs. Libera was locked to the RHIC revolution frequency clock. This allowed the capture of the LEReC macrobunch structure in the beam loss data.
- Libera BLM can be used to sample the beam only in the RHIC abort gap (effectively sampling ~1us out of every RHIC turn) so as to be insensitive to the RHIC beam losses and only sensitive to the LEReC beam losses. This method may be used in the future to mitigate MPS trips during RHIC injection losses.



Stainless Steel Tubing




Response time of fast diagnostics

An example of measurement for BPMs:


The fault condition was created at the BPM and the reaction time was measured from the delay between the BPM-registered fault and the disappearance of the signal on the MPS PD.

MPS controller response time is 500 ns (blue trace to purple trace). The time from an interlock to 'no-beam' condition, is within 2 μ s. Adding 3 μ s of processing and cable delay time we get 5 μ s for the overall MPS reaction time.




Slow diagnostics

- The vacuum gauges, readback of the magnets PS currents, readback of position of various insertion devices, Gun HVPS readback and beamline and dump temperatures worked reliably through 2017-2019 gun, accelerator and cooling commissioning.



MPS development and administration



- MPS prototype (having all main features of the present system) was developed for 2017 gun commissioning. It included gun and 7 m beamline to the diagnostic dump.
- MPS for the full LEReC was developed and commissioned in 2018 as a part of accelerator commissioning.
- In 2019 MPS was operated with some minor modifications (as compared to 2018) during commissioning of electron cooling.
- Evolution of the MPS had the following features:
 - The system became less “configurable” (all vacuum gauges and all BLMs are always monitored no matter the beam destination)
 - Duplicating levels of protection were added for some critical features (current measurement, SRF Booster protection etc.)
- MPS is checked first without and then with the beam before each run.

A few lessons we learned

- Of course, the MPS is designed to be fail-safe. It is important to double-check that every part of every subsystem interacting with the MPS is fail-safe too.
- Commissioning of such an accelerator as LEReC (actual R&D, both from engineering and physics point of view, which must be turned into an operational machine in a record time) requires frequent adjustments to various machine parameters affecting the MPS. No matter how inconvenient it is, never allow access to the MPS and MPS-related settings to anyone but people who have detailed understanding of the system intricacies.
- Having redundancy in the system is important.

Conclusion

- LEReC is an unconventional and a sophisticated accelerator that requires a sophisticated MPS for safe operations.
- LEReC MPS was designed, developed and deployed during 2017-2018 commissioning of accelerator and was fully operational during 2019 electron cooling commissioning.
- Each and every part of the LEReC MPS has been battle-tested. It is ready for LEReC transition to operations.