

START-TO-END SIMULATIONS OF THE CLARA FEL TEST FACILITY

D. J. Dunning^{*1,4}, D. Angal-Kalinin^{1,4}, A. D. Brynes^{1,4}, L. T. Campbell^{2,4},
 H. M. Castaneda Cortes^{1,4}, J. K. Jones^{1,4}, B. S. Kyle^{3,4}, J. W. McKenzie^{1,4}, B. W. J. McNeil^{2,4},
 J. D. A. Smith⁵, N. R. Thompson^{1,4}, P. Traczykowski^{2,4}, P. H. Williams^{1,4},

¹STFC Daresbury Laboratory, Daresbury, ²University of Strathclyde, Glasgow, UK

³University of Manchester, Manchester, UK, ⁴The Cockcroft Institute, Daresbury, UK

⁵Tech-X UK Ltd, Sci-Tech Daresbury, Daresbury, UK

Abstract

CLARA is a new FEL test facility being developed at STFC Daresbury Laboratory in the UK, aiming to deliver advanced FEL capabilities including few-cycle pulse generation and Fourier transform limited output. Commissioning is underway on the front-end (photo-injector and first linac) while the later stages are being procured and assembled. Start-to-end (S2E) simulations of the full facility are presented, including optimisation of the accelerator setup to deliver the required properties of one of the electron beam modes specified for FEL operation. FEL simulations are performed using the Genesis 1.3 and Puffin codes and the results are compared.

INTRODUCTION

The UK is constructing a new FEL test facility called CLARA [1], which will be a dedicated accelerator R&D facility focused around demonstrating FEL schemes that can be applied to enhance the capabilities of X-ray FEL facilities - including a potential UK XFEL [2]. It will operate with 250-MeV maximum energy and $\lambda_r = 100\text{--}400$ nm fundamental FEL wavelength. The front end (up to 50 MeV) is being commissioned [3,4] and the second phase (full energy accelerator) is being assembled while technical design and procurement of the later stages continues - aiming for FEL lasing in 2022.

The conceptual design of the FEL section was finalised in September 2017 and is summarised in [5]. Briefly, the aim is to demonstrate novel FEL capabilities that can be applied at X-ray FEL facilities including high-brightness SASE [6], mode-locking [7], mode-locked afterburner [8], optically slicing an isolated pulse [9] and others. It is a flexible design to accommodate new ideas and future changes.

As shown in Table 1, a number of electron beam operating modes have been defined [10], with short-bunch and long-bunch modes both specified as 250-pC Gaussian bunches with target 0.5 mm-mrad normalised emittance and 25 keV energy spread but with different compression (peak currents of 400 A and 125 A respectively). ‘Ultra-short’ and ‘flat’ modes are also specified, with the latter (not shown in Table 1) being similar to the short mode with the additional constraint of a 250-fs region with flat current and emittance. The design of the accelerator layout to deliver the required beams is now finalised [11] and is shown in Fig. 1.

* david.dunning@stfc.ac.uk

Table 1: CLARA FEL Electron Beam Modes

Parameter	Beam Mode		
	Long	Short	Ultra-short
Energy [MeV]	150-240	150-240	240
Δt_{FWHM} [fs]	1875	585	50/40/35
Charge [pC]	250	250	25/40/50
I_{peak} [A]	125	400	~500/1000/1500
$\epsilon_{\text{norm.}}$ [mm-mrad]	0.5-0.8	0.5-1.0	1.0-1.5
σ_E [keV]	25-75	25-120	100-150
Chirp [MeV/ps]	<1	<1	-

S2E simulations of the finalised layout are underway for different electron beam modes and different FEL schemes. In this paper we report the results of S2E modelling for the FEL mode of self-amplified spontaneous emission (SASE), using the short-bunch electron beam mode at 240 MeV (‘short-240’ mode). SASE is the default operating mode for an amplifier FEL so this case serves as the baseline from which more advanced schemes can be compared. Details of the modelling and optimisation procedures are described.

ACCELERATOR OPTIMISATION

Simulations of the CLARA accelerator (up to the FEL) have been performed using a Python-based framework [12] for interacting with standard tracking codes, performing non-linear multi-variate optimisation and data analysis and plotting. The CLARA standard code is ASTRA [13] due to the strong longitudinal and transverse space-charge effects in a low-energy machine. ASTRA, however, does not include the effects of coherent synchrotron radiation in the variable bunch compressor, so CSRTrack [14] is used for this section. For benchmarking purposes the framework also tracks in Elegant [15]. The lattice is defined using a bespoke format and encoded in YAML [16], which is both well integrated into Python and is human-readable. Tracking I/O is interfaced through HDF5 [17] intermediary files, allowing an arbitrary choice of simulation code for each section of the lattice. Further benchmarking is performed in the GPT [18] code, which is currently being integrated into the framework. For optimisation we use the DEAP [19] package.

Results from the optimisation of the short-240 mode of CLARA (see Fig. 2) show acceptable bunch properties matching all of the desired FEL parameters with the exception of a residual longitudinal energy chirp of $\sim 4\text{--}6$ MeV/ps.




Figure 1: Schematic layout of CLARA. The total length is ~ 90 m.

Slice properties of the bunch show normalised-emittance below 0.5 mm-mrad and acceptable slice energy spreads at peak-currents close to 400 A. This improvement in beam properties over previous studies is primarily driven by a standardisation of the RF gun peak field to 120 MV/m and photoinjector laser pulse profile to a 3-ps flat-top [20].

Attempts to reduce the residual energy chirp have so far resulted in significant reduction in the bunch quality. The implementation of improved wakefield models is expected to help to some extent. Separate studies on dielectric wakefield de-chirping [21] are on-going. Integration of the de-chirper dynamics into the simulation framework is a current high-priority topic. The effect of energy chirp on FEL performance is discussed in the following section.




Figure 2: Slice parameters and longitudinal phase space of the optimised S2E bunch at the entrance to the FEL. The normalised emittance meets the spec. of <0.5 mm-mrad and the energy spread is close to the target of 25 keV. The peak of the slice-averaged current is slightly less than 400 A in order to minimise energy chirp, nevertheless the energy chirp of ~ 4 MeV/ps exceeds the spec. of 1 MeV/ps.

FEL MODELLING

The FEL section was simulated in both Genesis 1.3 [22] (version 2) and Puffin [23–25] using the short-240 mode S2E bunch from the previous section, with additional parameters given in Table 2.

Genesis Method

Simulations in ASTRA and CSRtrack were carried out with a total of 262k particles, which was determined to be optimal in numerical convergence tests. The ASTRA output distribution was pre-processed to include matching of the initial distribution to the undulator FODO lattice and converting the electron distribution into a *dist* file to be read as input by Genesis. The pre-processing stages were carried out using the OCELOT framework [26]. OCELOT integrates Genesis with pre-processing and post-processing methods in order to automate the simulation runs and is implemented in Python. At the end of the simulation, plots of the most relevant FEL properties are obtained from the Genesis output files.

Puffin Method

Before use in Puffin, the ASTRA data was processed using the FXFEL [27] package, which pre-conditions the beam for the FEL simulation. This pre-conditioning involves up-sampling the beam distribution to a number of particles that adequately samples each FEL wavelength, whilst adhering to fundamental shot-noise statistics [28]. The up-sampling

Table 2: FEL Parameters

Parameter	Value
Undulator type	Planar
Field Orientation	Horizontal
Period, λ_u	25 mm
Module Length (total)	0.75 m
Inter-module gap length	0.5 m
Number of full periods	27
Active module length	0.675 m
Undulator parameter, a_u	0.8667
Resonant wavelength, λ_r	~ 100 nm
Electron beam transverse size, $\bar{\sigma}_{x,y}$	50 μm

is performed by utilising cumulative distribution functions of the initial particle density. The FXFEL package handles conversion from CSRTrack/ASTRA format to Puffin format via the intermediary Standard Units (SU) format [27, 29], where sliced analysis using the Xie parameterisation [30] is used to check the beam's suitability for FEL amplification. The package matches the beam to the undulator FODO lattice, if desired. The entire pre-and-post processing chain in Puffin is implemented using these custom Python modules.

Results Comparison

Figure 3 shows FEL simulation results for the S2E bunch, simulated in Genesis and Puffin. The pulse energy vs distance through the undulator is shown together with the temporal and spectral profiles at saturation. For Genesis, multiple shot-noise realisations are shown. In general there is reasonable agreement between the two codes. The pulse energy grows slightly faster in Puffin (outside the range of the Genesis shot-noise realisations) and shows a clearer saturation point. The drops in pulse energy in break sections are expected to be due to radiation being absorbed by the transverse boundaries of the field mesh due to high diffraction in the system, though imperfect phase-matching between modules could also contribute - further study is underway. Due to the random shot-to-shot fluctuations inherent in SASE there is not close agreement between the temporal and spectral profiles but there is reasonable qualitative agreement.

Energy Chirp

The impact of energy chirp on SASE pulse energy and bandwidth has been assessed in Genesis simulations. It was found that the pulse energy decreased by $\sim 10\%$ and the bandwidth increased by $\sim 5\%$ per 1 MeV/ps of chirp (for chirps with lower energy at the head: chirps in the opposite sense increased pulse energy analogous to undulator tapering). While the pulse energy reduction can be compensated by undulator tapering, the bandwidth increase cannot. The S2E bunch was artificially dechirped and simulated in Genesis and the performance was found to meet that of an ideal Gaussian beam with the specified parameters. The maximum energy chirp for the short-bunch mode has been specified as 1 MeV/ps. Tolerance studies of more advanced FEL schemes could yet impose more stringent limits.

CONCLUSION AND OUTLOOK

CLARA SASE FEL S2E simulations have been carried out. The accelerator has been optimised such that the electron beam meets all specifications except energy chirp. Reasonable agreement has been found between Genesis and Puffin for FEL modelling, though further investigation of discrepancies is required. The next steps are to include dechirper modelling in the accelerator simulation, and to study advanced FEL schemes where the difference between FEL codes is expected to be more significant. S2E is one component of a larger framework for CLARA including a virtual accelerator [31] and accelerator control systems [3].




Figure 3: FEL simulation results. Top and second from top: FEL pulse energy with distance through the undulator on linear and log scales. Below: temporal profiles and spectra at saturation (15 m). For each plot there are multiple shot noise realisations shown for the Genesis results (grey), with one typical case highlighted (red) and the average also shown (black). One shot noise realisation is shown for Puffin (blue).

REFERENCES

- [1] J. A. Clarke *et al.*, “CLARA conceptual design report,” *Journal of Instrumentation*, vol. 9, no. 05, p. T05001, 2014, <https://doi.org/10.1088/1748-0221/9/05/T05001>.
- [2] Science & Technology Facilities Council (UK), “Free-Electron Laser (FEL) Strategic Review,” 2016. [Online]. Available: <https://www.stfc.ac.uk/files/fel-report-2016/>
- [3] D. Angal-Kalinin *et al.*, “Commissioning of Front End of CLARA Facility at Daresbury Laboratory,” 2018, presented at IPAC2018, Vancouver, Canada, paper THPMK059, this conference.
- [4] L. Cowie *et al.*, “High Power RF Conditioning on CLARA,” 2018, presented at IPAC2018, Vancouver, Canada, paper THPAL085, this conference.
- [5] D. J. Dunning *et al.*, “CLARA facility layout and FEL schemes,” 2017, presented at FEL2017, Sante Fe, NM, USA, paper MOP054.
- [6] B. W. J. McNeil, N. R. Thompson, and D. J. Dunning, “Transform-Limited X-Ray Pulse Generation from a High-Brightness Self-Amplified Spontaneous-Emission Free-Electron Laser,” *Phys. Rev. Lett.*, vol. 110, p. 134802, Mar 2013, <https://doi.org/10.1103/PhysRevLett.110.134802>.
- [7] N. R. Thompson and B. W. J. McNeil, “Mode locking in a free-electron laser amplifier,” *Phys. Rev. Lett.*, vol. 100, p. 203901, May 2008, <https://doi.org/10.1103/PhysRevLett.100.203901>.
- [8] D. J. Dunning, B. W. J. McNeil, and N. R. Thompson, “Few-cycle pulse generation in an x-ray free-electron laser,” *Phys. Rev. Lett.*, vol. 110, p. 104801, Mar 2013. [Online]. Available: <https://doi.org/10.1103/PhysRevLett.110.104801>
- [9] E. L. Saldin, E. A. Schneidmiller, and M. V. Yurkov, “Self-amplified spontaneous emission FEL with energy-chirped electron beam and its application for generation of attosecond X-ray pulses,” *Phys. Rev. Spec. Top. Accel. Beams*, vol. 9, no. 5, pp. 1–6, May 2006. [Online]. Available: <https://doi.org/10.1103/PhysRevSTAB.9.050702>
- [10] P. H. Williams *et al.*, “Developments in the CLARA FEL Test Facility Accelerator Design and Simulations,” in *Proc. of IPAC2016*, 2016, pp. 797–800.
- [11] P. H. Williams, D. J. Dunning, and N. R. Thompson, “Developments in the CLARA FEL Test Facility Accelerator Design and Simulations,” in *Proc. of IPAC2017*, 2017, pp. 2787–2789.
- [12] ASTeC. [Online]. Available: <https://github.com/VELA-CLARA-software/OnlineModel/tree/master/SimulationFramework>
- [13] K. Flöttmann, “ASTRA - A Space Charge Tracking Algorithm,” 2000, <http://www.desy.de/~mpyflo>.
- [14] M. Dohlus, “CSRtrack code.” [Online]. Available: <http://www.desy.de/fel-beam/csrtrack/>
- [15] M. Borland, “User’s Manual for elegant,” APS-ANL, Chicago, IL, 2017.
- [16] K. Simonov. [Online]. Available: <https://github.com/yaml/pyyaml>
- [17] The HDF Group, “Hierarchical Data Format, version 5,” 1997-2018.
- [18] Pulsar Physics, “General Particle Tracer.” [Online]. Available: <http://www.pulsar.nl/gpt/>
- [19] F.-A. Fortin, F.-M. D. Rainville, M.-A. Gardner, M. Parizeau, and C. Gagné, “DEAP – Evolutionary Algorithms Made Easy,” *Journal of Machine Learning Research*, vol. 13, pp. 2171–2175, 2012.
- [20] J. W. McKenzie, A. D. Brynes, and B. L. Milityn, “Front End Simulations and Design for the CLARA FEL Test Facility,” 2015, presented at FEL2015, Daejeon, Korea, paper MOP057.
- [21] T. H. Pacey, G. Xia, Y. Saveliev, and D. J. Dunning, “Phase space manipulation of sub-picosecond electron bunches using dielectric wakefield structures,” in *Proc. of IPAC2017*, 2017, pp. 3302–3304.
- [22] S. Reiche, “GENESIS 1.3: a fully 3D time-dependent FEL simulation code,” *Nucl. Instr. Meth. Phys. Res. Sect. A*, vol. 429, p. 243, 1999. [Online]. Available: [https://doi.org/10.1016/S0168-9002\(99\)00114-X](https://doi.org/10.1016/S0168-9002(99)00114-X)
- [23] L. T. Campbell and B. W. J. McNeil, “PUFFIN: a three-dimensional, unaveraged free-electron laser simulation code,” *Phys. Plasmas*, vol. 19, p. 093119, 2012. [Online]. Available: <https://doi.org/10.1063/1.4752743>
- [24] L. Campbell, J. Smith, P. Traczykowski, and B. McNeil, “An Updated Description of the FEL Simulation Code Puffin,” 2018, presented at IPAC2018, Vancouver, Canada, paper THPMK112, this conference.
- [25] [Online]. Available: <https://github.com/UKFELs/Puffin>
- [26] I. Agapov, G. Geloni, S. Tomin, and I. Zagorodnov, “Ocelot: A software framework for synchrotron light source and fel studies,” *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, vol. 768, pp. 151 – 156, 2014, <http://dx.doi.org/10.1016/j.nima.2014.09.057>.
- [27] [Online]. Available: <https://github.com/UKFELs/FXFEL>
- [28] B. W. J. McNeil, M. W. Poole, and G. R. M. Robb, “Unified model of electron beam shot noise and coherent spontaneous emission in the helical wiggler free-electron laser,” *Phys. Rev. Spec. Top. Accel. Beams*, vol. 6, p. 070701, 2003, see also reference [14] within.
- [29] R. J. Allan *et al.*, “Simulation Suite for Future FELs,” in *Proc. of FEL 2015*, 2015, p. 384, presented at FEL2015, Daejeon, Korea, paper TUP017.
- [30] M. Xie, “Design optimization for an x-ray free electron laser driven by SLAC linac,” *Proceedings of the 1995 IEEE Particle Accelerator Conference*, pp. 183–185, 1995, <https://doi.org/10.1109/PAC.1995.504603>.
- [31] T. J. Price *et al.*, “Virtual VELA-CLARA: The Development of a Virtual Accelerator,” 2018, presented at IPAC2018, Vancouver, Canada, paper THPML060, this conference.