

CYCLOTRONS'13

September 16. – 20., Vancouver, Canada

**Tuning of the PSI 590 MeV Ringcyclotron for Accepting and
Accelerating a Rebunched 72 MeV Proton beam**

M. Humbel, Ch. Baumgarten, J. Grillenberger, W. Joho, H. Müller, H. Zhang

PSI Villigen, Switzerland

The PSI 590 MeV Ring cyclotron 1973 - 2013

RF-Flattop System:


Flattop Cavity

500 kV 150MHz, 1.9m
Half Wave Resonator


Main Cavity

850 kV 50MHz, 5.2m
Quarter Wave Resonator

Proton intensity: 2400 μA





Success Factors for PSI Ringcyclotron



W.Joho 2013

Last turns in the Ring cyclotron




MXZ7 Bunch Shape Monitor Scan at 2.3 mA

$$E_{\text{kin}} = 72 \text{ MeV} \Rightarrow \beta = 0.371, \quad v = 111.1 \text{ mm/ns}$$

$$\text{Frq.} = 50 \text{ MHz} \Rightarrow T = 20 \text{ ns}, \quad v = 6.2 \text{ mm/Deg.}$$


MXZ7: $I_{\text{max}} = 54.8 \text{ mm}$, $x_{\text{max}} = 7.6 \text{ mm}$, $r_{15} = +0.54$




QXA1 = 3.7kG
QXA2 = -3.6kG
QXA3 = 1.7kG

SM2E measured @ 20110707_1740 current: MXC1 5 99.5 i_d


Zmin= 0.00 m Zmax= 75.00 mm Xmax= 20.0 mm Ymax= 20.0 mm Ap * 0.20 7-Jul-11 18:22:21



Centre of Gravity Scans of Beam Optic DN01




monitors **in** the dispersion free section



monitors **off** the dispersion free section

Dispersion-Fit and RRI2 Current Probe




Matched Ring Injektion (Setting DN05b)


IW2 vom Injektor 2 zum Ring 1.Umlauf SM2E measured @ 20120521_1354 current: MXC1 1 292.9

(M)

Zmin= 0.00 m Zmax= 75.00 m Xmax= 20.0 mm Ymax= 20.0 mm Ap * 0.20 21-May-12 13:58:29




Dispersion-Fit and RRI2 Current Probe




Bunch Shape Monitor Scans at $I_p = 200 \mu\text{A}$

Buncher off


before injection
into the
Ring cyclotron



3-wire probe RRI1




after extraction
from Ring




Buncher 200 kVp


before injection
into the
Ring cyclotron



3-wire probe RRI1



after extraction
from Ring



The 72 MeV transfer line is sufficiently equipped for the buncher based beam injection into the Ringcyclotron, the appropriate device settings are successfully tested.

In order to accelerate properly a bunched high intensity beam, more insight by means of additional equipment, as well as by a substantial effort in precision simulation is needed.

Conclusions

The 72 MeV transfer line is sufficiently equipped for the buncher based beam injection into the Ringcyclotron, the appropriate device settings are successfully tested.

In order to accelerate properly a bunched high intensity beam, more insight by means of additional equipment, as well as by a substantial effort in precision simulation is needed.





Thank You for Your Attention!