

Dario Pellegrini
on behalf of Alessandra Valloni

CERN SC RF AND ERL TEST FACILITY PLANS

ERL 2015
Workshop on Energy Recovery Linacs



ERL2015

June 7-12, 2015

Stony Brook University, Stony Brook, New York, USA

The 56th ICFA Advanced
Beam Dynamics Workshop
on Energy Recovery Linacs




Electron-Hadron collisions at CERN

The **LHeC** is an accelerator study for a possible upgrade of the existing LHC

By adding a new electron accelerator, the LHeC would enable the investigation of electron-proton collisions at unprecedented high energies and rate.

The baseline design consists of a 3-pass ERL to provide a 60 GeV, high-current e^- beam



In parallel a design study for an **ERL test platform** is being pursued at CERN to test machine and operation issues before designing a large scale facility

LHeC ERL Facility & SC RF

FUNDAMENTAL MOTIVATION:

- **Proof validity of fundamental **design** choices:**
 - Three-turns acceleration + three-turns deceleration
(other existing ERLs have only two passages)
 - Implications of high current operation ($6 * 10\text{mA} > 60\text{mA}$ in the linacs!)
- **Build up **expertise** for a facility with a fundamentally new operation mode:**
 - ERLs are circular machines with tolerances and timing requirements similar to linear accelerators (no 'automatic' longitudinal phase stability, etc.)
- **Verify and test components and operation **tolerances** before building a large scale facility:**
 - Tolerances in terms of field quality of the arc magnets
 - Required RF phase stability (RF power) and LLRF requirements

Goals of the ERL Facility

Dedicated Accelerator physics studies and R&D:


- Injector studies
- Beam diagnostics developments and testing with beam
- Could it be foreseen as the injector to LHeC ERL and to FCC?

Scientific and technical applications:

- Possible use for detector development
- Controlled quench and damage test for SC magnets
- Generation of gamma-ray beams via Compton backscattering

TARGET PARAMETER*	VALUE
Injection Energy [MeV]	5
Final Beam Energy [MeV]	900
Normalized emittance $\gamma\epsilon_{x,y}$ [μm]	5
Delivered Beam Current [mA]	10
Bunch Spacing [ns]	25 (50)
Passes	3

*in few stages



Outline

1. DESIGN STAGES AND PARAMETERS

2. MACHINE DESIGN

3. SC RF

4. PLANNING AND TIMELINE

Planning for each stage

STEP 1


SC RF cavities, modules and e⁻ source tests

- Injection at 5 MeV
- 1 turn
- 75 MeV/linac
- Final energy 150 MeV

ARC	ENERGY
ARC 1	80 MeV
ARC 2	155 MeV

Two cryomodules with 4 SRF 5-cell cavities at 801.58 MHz.

Clear path already established in collaboration with JLab to obtain a prototype.




Planning for each stage

STEP 2

Test the machine in Energy Recovery Mode

- Injection at 5 MeV
- 3 turns
- 75 MeV/linac
- Final energy 450 MeV

ARC	ENERGY
ARC 1	80 MeV
ARC 2	155 MeV
ARC 3	230 MeV
ARC 4	305 MeV
ARC 5	380 MeV
ARC 6	455 MeV



Recirculation realized with vertically stacked recirculation passes

Planning for each stage


STEP 3

Additional SC RF modules test

Full energy test in Energy Recovery Mode

- Injection at 5 MeV
- 3 turns
- 150 MeV/linac
- Final energy 900 MeV

ARC	ENERGY
ARC 1	150 MeV
ARC 2	300 MeV
ARC 3	450 MeV
ARC 4	600 MeV
ARC 5	750 MeV
ARC 6	900 MeV



Outline


1. DESIGN STAGES AND PARAMETERS

**2. MACHINE DESIGN: LAYOUT AND OPTICS
MAGNET INVENTORY
TRACKING SIMULATIONS**


3. SC RF

4. PLANNING AND TIMELINE


Layout




Linac 1 Multi-Pass Optics



Linac 2 Multi-Pass Optics



Arc 1 optics




Arc dipoles :

$L_{dip} = 71.8 \text{ cm}$


$B = 5.67 \text{ kGauss}$

$\rho = 91.45 \text{ cm}$

Arc 3 optics



Arc 5 optics




Arc dipoles :

Ldip = 90.58 cm


B = 10.92 kGauss

$\rho = 230.66$ cm


Magnets inventory




155 MeV




455 MeV




755 MeV



305 MeV



605 MeV



905 MeV

Summary of magnets inventory


A preliminary inventory of the magnets of the ERL Facility lists:

- 40 bending magnets (vertical field)
- 36 bending magnets (horizontal field) in the spreaders / combiners
- 114 quadrupole magnets
- a few magnets in the injection / extraction parts

Conventional iron-dominated resistive magnets can be used

ARC	ENERGY	LENGTH	# QUADS	# DIPOLES
ARC 1	150 MeV	35.98 m	21	12
ARC 2	300 MeV	35.74 m	21	12
ARC 3	450 MeV	35.61 m	21	14
ARC 4	600 MeV	35.74 m	21	14
ARC 5	750 MeV	35.98 m	15	12
ARC 6	900 MeV	34.43 m	15	12
TOTAL		297.9 m	114	76

Footprint



ARCS

Total length for Pass 1

99.86 m

$$267 \times \lambda_{rf} = 20 \cdot n \cdot \lambda_{rf} + 7 \cdot \lambda_{rf}$$

Total length for Pass 2

99.48 m


$$266 \times \lambda_{rf} = 20 \cdot n \cdot \lambda_{rf} + 6 \cdot \lambda_{rf}$$

Total length for Pass 3

98.55 m

$$263.5 \times \lambda_{rf} = 20 \cdot n \cdot \lambda_{rf} + 3.5 \cdot \lambda_{rf}$$

LINAC



ONE CRYOMODULE: 8 RF CAVITIES

Linac length ~ 12.6 m

Chicane inj/extr length ~ 1.42 m




F= 801.58 MHz

$\lambda_{rf} = 37.4$ cm


Total length for 3 passes

297.9 m

Arc layout




Start-to-end Optics with PLACET2*




Transverse Phase space at 900 MeV (PLACET2 – only optics)

Horizontal phase space
at 900 MeV





Vertical phase space
at 900 MeV



Very well preserved phase space and transverse emittance at 900 MeV and down to the dump

Small impact of (coherent) synchrotron radiation verified with Elegant
Small impact of short-range wakefields expected (to be further investigated)

Longitudinal Phase Space (PLACET2 – only optics)



Bunch length preservation down to dump (very good isochronicity)
Some energy chirp at dump -> requires fine tuning of the arc lengths

With 6 mm long bunches, the RF curvature can be seen at high energy,
still extremely small energy spread: 5 ‰ at injector -> 0.1 ‰ at 900 MeV

Possibility to introduce energy chirp and tune the arcs R_{56} to manipulate the phase space


Recombination Pattern

Multi-bunch effects are enhanced by the parameter:

$$\int \frac{\beta}{E} ds$$

Almost the same for every passage
in the linacs

Varies substantially



The bucket filling at subsequent turns can be controlled tuning the length of the arcs


Recombination Pattern

Multi-bunch effects are enhanced by the parameter:

$$\int \frac{\beta}{E} ds$$

Almost the same for every passage
in the linacs

Varies substantially




Maximum separation between lowest energy passages minimizes the bunch cross-talk


Long Range Wakefields Threshold Current

Multi-bunch tracking simulations with PLACET2 and optimal recombination pattern
26 dipole modes of the SPL cavity scaled to 802 MHz
100 particles per bunch – BBU triggered by statistical fluctuations of the centroid

10e9 particles per bunch



12e9 particles per bunch




Offending mode builds up in the vertical plane (coupling between a specific mode frequency, time of flight and the vertical betatron tune)

Threshold current >5 times higher than the nominal (2e9 particles per bunch)

Optics for steps 1 and 2

- Complete Step 2 and Step 1 configuration and optics layout



Outline

1. DESIGN STAGES AND PARAMETERS

2. MACHINE DESIGN

3. SC RF

4. PLANNING AND TIMELINE

Superconducting RF

CERN needs to study and develop the technologies to prepare for a possible next energy-frontier machine (European Strategy for Particle Physics)



Superconducting RF is a key area –
this is where this planned facility comes in

CERN management has asked us to conduct a **Conceptual Design Study** for an Energy Recovery Linac Facility (ERLF)

We have started this study and have started to establish collaborations


SC RF Activities at CERN

... in the nineties (LEP)

At LEP II times, CERN had the largest SRF installation



Wart Schirm and Albert Insomby 'operate' on a superconducting radio frequency cavity in a clean room.




CERN AC/LC715/32-4-95

SC RF Activities at CERN

...today (1/2)



Cavity reception & tuning




HIE-Isolde cavity preparation



HIE-Isolde cavity substrate



EP




SM18 Upgraded and extended clean rooms with HP water rinsing and HP water station



HIE-Isolde cavity assembly

SC RF Activities at CERN


...today (2/2)



SPL cryomodule

Frequency = 704 MHz

Novel cavity suspension by FPC cavities in bulk Nb



HL-LHC crab cavities,
Frequency = 400 MHz,
2-cavity prototype CM
cavities in bulk Nb
(fabricated at Niowave)

SC RF Activities at CERN


The CERN SRF R&D has to cover many areas, accelerators, technologies. Where possible, choices were made to exploit synergies!

PROGRAMME	FREQUENCY	TECHNOLOGY
LHC, spare and more	400 MHz	Nb on Cu
LHC upgrade	800 MHz	Nb on Cu? Bulk?
HIE-ISOLDE	101 MHz	Nb on Cu
CRAB	400 MHz	Bulk Nb
SPL (ESS)	704 MHz	Bulk Nb
ERL-Facility, FCC-he	800 MHz	Bulk Nb
FCC-ee, FCC-hh	400 & 800 MHz	Nb on Cu & bulk

SCRF @ the ERL FACILITY

PARAMETER	VALUE
RF frequency	801.58 MHz
Acc. Voltage/cavity	18.7
# Cells/cavity	5
Cavity length	~ 1.2 m
# Cavities/cryomodule	4
RF power/cryomodule	< 50 MW
# Cryomodules	4
Acceleration/pass	300 MeV
Bunch repetition	40 MHz
Duty factor	CW

Initial Cavity Design (SPL, JLAB and BNL experience)




Possibility to install and test cavities at other European frequencies (ESS, SPL,...), (LHC harmonic, SPS, LHeC, FCC,...) (XFEL, ILC) if:

- Photocathode pulsing at a sub-harmonic (12.16 MHz)
- Tunable arc length (10 cm) to match the phase

Cryomodule Design

JLAB had designed an 805 MHz cryomodule for SNS (concept for the 801.58 MHz baseline design)



Established collaboration with JLab taking advantage of their experience with CEBAF and the FEL in ERL mode:

- crucial contributions already obtained for the machine layout and lattice
- design and construct the 801.58 MHz cavities and cryomodules.

Outline

1. DESIGN STAGES AND PARAMETERS

2. MACHINE DESIGN

3. SC RF

4. PLANNING AND TIMELINE

ERL Facility at CERN for Applications

- Facility for testing quench and damage levels of SC wires and SC magnets
 - Intensities and repetition rates
 - Space, powering and other requirements
- Generation of high-energy monochromatic polarized photons via Compton backscattering of laser light from relativistic electrons for nuclear physics research
 - Investigate the maximum energy and flux of the gamma-beam generated
 - Define the laser requirements according to the electron beam parameters

ERL facility at CERN for applications, *Erk Jensen*
WG5 Session 1: ERL Applications
Wednesday June 10, 9:50 am

Possible Site options

- Many site possibilities presented @ January 2014 LHeC Workshop



Three main options:

- **Point 2 @ ALICE** – apparently hosting power converters (tbc)
- **SM18** – existing cryogenic and powering infrastructure, but no available space
- **Preveessin site** – still under investigation

**Site specific studies are foreseen
for the ERL TF and auxiliary applications
in preparation for the ERL TF CDR**

Planning for the CDR

- Draft a preliminary version by the end of June 2015:

To be presented at the next **LHeC Workshop***

CERN (24 June) and Chavannes-de-Bogis (25-26 June)

Organization committee:

S. Bertolucci, F. Bordry, O. Bruning, L. Hemery, M. Klein

- Complete CDR by the end of 2015

LHeC Workshop

International Advisory Committee:

Guido Altarelli (Rome)
Sergio Bertolucci (CERN)
Nicola Bianchi (INFN Frascati)
Frederick Bordry (CERN)
Stan Brodsky (SLAC)
Hesheng Chen (IHEP Beijing)
Andrew Hutton (Jefferson Lab)
Young-Kee Kim (Chicago and Fermilab)
Victor A. Matveev (JINR Dubna)
Shin-Ichi Kurokawa (Tsukuba)
Leandro Nisati (Rome)
Leonid Rivkin (EPF Lausanne)
Herwig Schopper (CERN) - Chair
Jürgen Schukraft (CERN)
Achille Stocchi (LAL Orsay)


Working Group Convenors

Physics and Detector

Voica Radescu (Heidelberg)
Peter Kostka (Liverpool)

Accelerator and ERL Facility

Gianluigi Arduini (CERN)
Erk Jensen (CERN)



The poster for the 'Workshop on the LHeC' features a blue and green color scheme. At the top, it includes the website 'http://cern.ch/lhec' and email 'lhec.ws@cern.ch'. The main title 'Workshop on the LHeC' is in large black font, with the subtitle 'Electron-proton and electron-ion collisions at the LHC' below it. The dates '24 June 2015 CERN' and '25-26 June 2015 Chavannes-de-Bogis, Switzerland' are prominently displayed. A central graphic shows a circular particle accelerator ring composed of blue, green, and red blocks, with a dashed yellow line representing the path. The bottom section lists the 'International Advisory Committee' and 'Coordination Group' members, followed by the 'Organizing Committee' members. Logos for CERN, EUCARD², XBEAM, and LHeC are at the bottom.

<http://cern.ch/lhec> lhec.ws@cern.ch

Workshop on the LHeC

Electron-proton and electron-ion collisions at the LHC

24 June 2015 CERN
25-26 June 2015 Chavannes-de-Bogis, Switzerland

International Advisory Committee

Guido Altarelli (Rome)
Sergio Bertolucci (CERN)
Nicola Bianchi (INFN)
Frederick Bordry (CERN)
Stan Brodsky (SLAC)
Hesheng Chen (IHEP Beijing)
Andrew Hutton (Jefferson Lab)
Young-Kee Kim (Chicago and Fermilab)
Victor A. Matveev (JINR Dubna)
Shin-Ichi Kurokawa (Tsukuba)
Leandro Nisati (Rome)
Leonid Rivkin (EPF Lausanne)
Herwig Schopper (CERN) - Chair
Jürgen Schukraft (CERN)
Achille Stocchi (LAL Orsay)
John Womersley (STFC)

Coordination Group

Gianluigi Arduini (CERN)
Nestor Armesto (Santiago de Compostela)
Oliver Brüning (CERN)
Stefano Forte (Milano)
Andrea Gaddi (CERN)
Erk Jensen (CERN)
Max Klein (Liverpool)
Peter Kostka (Liverpool)
Bruce Mellado (Wits)
Paul Newman (Birmingham)
Voica Radescu (Heidelberg)
Daniel Schulte (CERN)
Alessandra Valloni (CERN)
Frank Zimmermann (CERN)

Organizing Committee

Sergio Bertolucci (CERN)
Frederick Bordry (CERN)
Oliver Brüning (CERN)
Laurie Hemery (CERN)
Max Klein (Liverpool)

CERN EUCARD² XBEAM LHeC

Summary

- An **ERL platform** is being pursued at CERN to validate the LHeC key design choices along with dedicated physical and technical applications
- The concept of the ERL Facility is designed to allow for a **staged** construction with verifiable and useful stages for an ultimate beam energy in the order of 900 MeV
- An **optics** design study of the ERLF has been completed and start-to-end analysis are on going
- Design **complementary to & synergetic** with other proposals worldwide
- **Collaborations** with other institutes have been started
- Completion of **Conceptual design study** of an ERLF at CERN by 2015

Thank you for your attention

...and thanks to the LHeC collaboration, in particular to

A. Bogacz, O. Bruning, V. Chetvertkova, E. Jensen, M. Klein, D. Wollmann, F. Zomer

<http://lhec.web.cern.ch>






www.cern.ch

LHeC as an Higgs Factory: ultimate IP parameters

$10^{34} \text{ cm}^{-2} \text{ s}^{-1}$ Luminosity reach	PROTONS	ELECTRONS
Beam Energy [GeV]	7000	60
Luminosity [$10^{33} \text{ cm}^{-2} \text{ s}^{-1}$]	16	16
Normalized emittance $\gamma \epsilon_{x,y}$ [μm]	2.5	20
Beta Function $\beta^*_{x,y}$ [m]	0.05	0.10
rms Beam size $\sigma^*_{x,y}$ [μm]	4	4
rms Beam divergence $\sigma'_{x,y}$ [μrad]	80	40
Average Beam Current [mA]	1112	25 delivered 150 in linacs
Bunch Spacing [ns]	25	25
Bunch Population	$2.2 \cdot 10^{11}$	$4 \cdot 10^9$
Bunch charge [nC]	35	0.64

Review of some ERL-based machines worldwide (planned/existing/operating)



Beam Energy	88-165 MeV
-------------	------------

Beam Current	10 mA
--------------	-------

Bunch charge	135 pC
--------------	--------

RF frequency	1500 MHz
--------------	----------

Passes	1
--------	---

Beam Energy	12-26 MeV
-------------	-----------

Bunch charge	40-60-200 pC
--------------	--------------

RF frequency	1300 MHz
--------------	----------

Passes	1
--------	---

Beam Energy	35-125-250 MeV
-------------	----------------


Beam Current	10mA (100mA)
--------------	--------------

Bunch charge	7.7pC- 77pC
--------------	-------------


RF frequency	1300 MHz
--------------	----------

Passes	1- 2
--------	------


Review of some ERL-based machines worldwide (planned/existing/operating)



Beam Energy	88-165 MeV
Beam Current	10 mA
Bunch charge	135 pC
RF frequency	1500 MHz
Passes	1




Beam Energy	5 GeV
Bunch charge	77 pC
Beam Current	100 mA
RF frequency	1300 MHz



Beam Energy	20 MeV
Bunch charge	0.5-5 nC
Bunch current	300 mA
RF frequency	704 MHz
Passes	1



Review of some ERL-based machines worldwide (planned/existing/operating)



Beam Energy	35 MeV
Beam Current	10 mA
Bunch charge	77 pC
RF frequency	1300 MHz
Passes	1

Beam Energy	50 MeV
Beam Current	100 mA
Bunch charge	77 pC
RF frequency	1300 MHz
Passes	1

Beam Energy	105 MeV
Bunch charge	0.77 pC
RF frequency	802/1300 MHz
Passes	2



Possible Site option: SM18

- Superconducting magnets and RF test facility.
 - Horizontal benches for SC magnets
 - Vertical cryostats for prototypes
 - RF powering and bunkers for RF SC cavities
- Cryogenics water power and other services already available.



- No space inside existing buildings.
- Adjacent positioning may interfere with SM18 activities.
- Parking space over the hill is not in use.
- South area less convenient as requires excavation
- All this possibilities are being discussed with the area managers

Prevessin Site Investigation



On the limit of the Prevezsin site.

Constructed from shielding blocks, **smaller than required but may be easily extended or rebuilt.**

Some cryogenic infrastructure already available

60x 22



Controlled quench and damage tests

MOTIVATION

FACILITY FOR TESTING QUENCH AND DAMAGE LEVELS OF SC WIRES AND SC MAGNETS

Question:


Are the intensities at extraction and repetition rates sufficient for the tests?

Requirements in terms of:

- Beam energy, intensity and pulse length (**energy deposition**)
- **Space for the magnets installation** (possible tests of cable samples and full cryo magnets)
- **Cryo** requirements
- **Vacuum** requirements
- **Powering** needs

Beam parameters to generate a given amount of energy deposition


CALCULATIONS AND FLUKA SIMULATIONS



Beam parameters


Energy, MeV	Emittance, m	Sigma, cm	FWHM, cm
150	1.70E-07	0.092	0.22
300	8.52E-08	0.065	0.15
450	5.68E-08	0.053	0.13
600	4.26E-08	0.046	0.11
750	3.41E-08	0.041	0.10
900	2.84E-08	0.038	0.09
1000	2.55E-08	0.036	0.08

Results are given for half of bulky target because of symmetry
Binning: 1 mm³ bins



Beam parameters to generate a given amount of energy deposition

CALCULATIONS AND FLUKA SIMULATIONS





Beam parameters

Energy, MeV	Emittance, m	Sigma, cm	FWHM, cm
150	1.70E-07	0.092	0.22
300	8.52E-08	0.065	0.15
450	5.68E-08	0.053	0.13
600	4.26E-08	0.046	0.11
750	3.41E-08	0.041	0.10
900	2.84E-08	0.038	0.09
1000	2.55E-08	0.036	0.08

Results are given for half of bulky target because of symmetry

Binning: 1 mm³ bins


Energy deposition, GeV/cm³/e⁻



Quench & Damage

For **quenching** an LHC MB (main dipole magnet) a certain amount of energy should be deposited in 1mm^3


electrons needed to quench the magnet \approx $\frac{\text{Quench threshold}}{\text{Maximum value for the energy deposition}}$



Can easily quench with a single bunch at 150MeV
Bunch charge $2e9 >$ quench threshold $1e9$

Damage limit in present studies is defined as a number of electrons needed for melting 1mm^3 of Cu


Number of electrons for melting Cu should be delivered to the target within several hundreds ms in order to avoid heat transfer




$2e11$ electrons required over 0.1 s to melt 1mm^3
 $8e15$ electrons accelerated over 0.1 s
(can extract few bunches with a fast kicker)

Gamma beams at the ERL Facility

GOAL: Generation of high-energy monochromatic polarized photons via Compton backscattering of laser light from relativistic electrons for nuclear physics research



Gamma beams at the ERL Facility: input parameters





ELECTRON BEAM PARAMETERS

Energy	900 MeV
Charge	320 pC
Bunch Spacing	25 ns
Spot size	30 μm
Norm. Trans. Emittance	5 μm
Energy Spread	0.1 %

LASER BEAM PARAMETERS

Wavelength	515 nm - 1030 nm
Average Power	300kW - 600 kW
Pulse length	3 ps
Pulse energy	7.5mJ - 15 mJ
Spot size	30 μm
Bandwidth	0.02 %
Repetition Rate	40 MHz

Gamma beam properties at the ERL facility




GAMMA BEAM PARAMETERS

Energy	30 MeV
Spectral density	$9 \cdot 10^4$ ph/s/eV
Bandwidth	< 5%
Flux within FWHM bdw	$7 \cdot 10^{10}$ ph/s
ph/e ⁻ within FWHM bdw	10^{-6}
Peak Brilliance	$3 \cdot 10^{21}$ ph/s*mm ² *mrad ² 0.1%bdw


Input laser beam

Mode locked laser beam : electric field





FT

“frequency comb”




Four mirror cavity resonator :
Each tooth of the comb locked to a cavity mode



State of the art (average power/ ~10 ps pulses) :
 $P_{circ} \sim 670 \text{ kW}$ for $P_{in} = 315 \text{ W}$ (250 MHz; table top ; Garching, OL39(2014)2595)
 $P_{circ} \sim 50 \text{ kW}$ for $P_{in} < 10 \text{ W}$ (178.5 MHz;
 gamma-ray exp. at ATF/KEK, CELIA/KEK/Hiroshima/LAL/LMA)

Configuration for LHeC ERL gamma source :
~same as ThomX project (CELIA, LAL)
R&D going on at LAL and CELIA Labs.



Configuration 2 for LHeC ERL gamma source

