



# $C\beta$ : Cornell-BNL ERL-FFAG Test Accelerator

## Optics considerations






# C $\beta$ : Cornell-BNL ERL-FFAG Test Accelerator



# eRHIC



[arxiv.org/abs/1409.1633](https://arxiv.org/abs/1409.1633)

# C $\beta$ White Paper

## The Cornell-BNL FFAG-ERL Test Accelerator


White Paper

Ivan Bazarov, John Dobbins, Bruce Dunham, Georg Hoffstaetter,  
Christopher Mayes, Ritchie Patterson, David Sagan

*Cornell University, Ithaca NY*

Ilan Ben-Zvi, Scott Berg, Michael Blaskiewicz, Stephen Brooks,  
Kevin Brown, Wolfram Fischer, Yue Hao, Wuzheng Meng,  
François Méot, Michiko Minty, Stephen Peggs, Vadim Ptitsin,  
Thomas Roser, Peter Thieberger, Dejan Trbojevic, Nick Tsoupas.

*Brookhaven National Laboratory, Upton NY*



December 16, 2014


1

arXiv:1504.00588v1 [physics.acc-ph] 2 Apr 2015

[arxiv.org/abs/1504.00588](https://arxiv.org/abs/1504.00588)

Christopher Mayes – June 10, 2015


# Layout





# FFAG Optics

## Cell



3.6 deg

8 cm

11 cm


42.5 T/m

-27.5 T/m


-0.104 T

0.5044 T



## Merge (10 cells)



22 deg




# FFAG Arc, Merge, Straight






# Splitter S1-4

- Accept large beams from Linac
- Steer onto FFAG closed orbits
- Match to FFAG optics
- $\mathcal{R}_{56}$  adjustment
- Path length adjustment via vertical chicanes
- Total path lengths close to ideal for ERL operation





# Splitter S1



Linac


Vertical  
chicane

FFAG

# Pass 1 optics

76 MeV


to 146 MeV



# Pass 2 optics

146 MeV


to 216 MeV



# Pass 3 optics

216 MeV

to 286 MeV







# Pass 4 optics

Decelerate  
to 216 MeV

286 MeV











# Full ERL bunch tracking















# Longitudinal Phase Space

end of the Linac for pass (full scale 8%)



# Longitudinal Phase Space

end of the Linac for pass (full scale 8%)




$r_{56}$  adjusted on pass 4




# Simulation Software

## Bmad & Tao (Cornell)



[www.lns.cornell.edu/~dcs/bmad](http://www.lns.cornell.edu/~dcs/bmad)

# Next steps





- Real fieldmaps (FFAG magnets, cavities, ...)
- Wakefields (CSR, resistive wall, ...)
- Injector + Linac space charge optimization
- Touschek scattering
- Dark current tracking & collimation
- BBU
- Ion trapping
- Orbit and optics correction
- Tolerance & stability analysis

# FFAG orbit correction simulation

500 um rms x offset errors


SVD correction given BPM readings for separate beams and correction coils on every other dipole




FFAG Arc

# Example errors, correction, and bunch tracking

## Variety of errors



SVD correction given BPM readings for separate beams and correction coils on every other FFAG dipole and all quadrupoles




1-pass ERL-FFAG (early design)

Christopher Mayes – June 10, 2015



# C $\beta$ : Cornell-BNL ERL-FFAG Test Accelerator



End