

FEL 2015

23rd – 28th August, 2015
Daejeon Convention Center, DAEJEON, KOREA

37th International Free Electron Laser Conference

Commissioning of the Delta Polarizing Undulator at LCLS

Heinz-Dieter Nuhn for the Delta Project Team

Wednesday, August 26, 2015



WED01

SLAC NATIONAL
ACCELERATOR
LABORATORY

Authors



**H.-D. Nuhn[#], S.D. Anderson, R.N. Coffee, Y. Ding, Z. Huang, M. Ilchen,
Y. Levashov, A.A. Lutman, J. MacArthur, A. Marinelli, S.P. Moeller,
F. Peters, Z. Wolf**, SLAC National Accelerator Laboratory (SLAC)

A.B. Temnykh, Cornell University (CLASSE)

G. Hartmann, J. Viefhaus, Deutsches Elektronen-Synchrotron (DESY)


J. Buck, European XFEL GmbH (XFEL.EU)

A.O. Lindahl, University of Gothenburg Department of Physics

We appreciate the opportunity to present our results at this conference!

Circular Polarized FEL X-Rays at LCLS

SLAC




X-ray beam polarization controllable from circulator through elliptical to linear

Delta Development


SLAC

Cornell University
Proof-of-Principle
0.3 m



A. Temnykh,
Phys. Rev. ST Accel. Beams
11, 120702 (2008).


SLAC
Prototype
1.0 m



Delta Development




Cornell University
Proof-of-Principle
0.3 m




A. Temnykh,
Phys. Rev. ST Accel. Beams
11, 120702 (2008).

SLAC
Prototype
1.0 m




SLAC
LCLS Delta
3.2 m




Variable Phase Undulator for Polarization Control

SLAC



Four independent quadrants of permanent magnets move longitudinally at fixed gap.

By sliding the quadrants it is possible to control the K from full to zero
and to have full control the polarization




Delta Benefit Expectations (2012)

Short Term:

- Add circular polarization capability to the current LCLS (in afterburner configuration).

Primary Photon Energy Range 0.28 – 2.0 keV




Yuantao Ding

Long Term:


- Provide polarization control for the LCLS-II SXR line.
- Build future Delta x-ray FELs with full polarization control and full tunability under LCLS type alignment control.

Delta 1.0-m Prototype (during assembly)

SLAC




1.0-m Prototype – Row Movement



For measurements plastic filler gauge was used. Measurement accuracy ~ 25 µm.
Nominal A-B dimension ~ 635 µm.

Mode: Planer / vertical field A,B,C,D = 0		Dimensions are µm			
		A-B	B-D	C-D	A-C
Reference		1,397	597	1,334	635
Mode: Helical right A,D = 0 B,C = +8mm					
		A-B	B-D	C-D	A-C
		1,359	699	1,270	762
Change from reference		38	-102	64	-127
Mode: Helical left A,D = 0 B,C = -8mm					
		A-B	B-D	C-D	A-C
		1,334	762	1,207	762
Change from reference		-64	165	-127	127
Mode: Planer / horizontal field A,B = 0 B,C = -16mm					
		A-B	B-D	C-D	A-C
		1,143	940	1,080	914
Change from reference		-254	343	-254	279
A	B				
C	D				

1.0-m Prototype – Row Movement




For measurements plastic filler gauge was used. Measurement accuracy $\sim 25 \mu\text{m}$. Nominal A-B dimension $\sim 635 \mu\text{m}$

		Dimensions are μm			
Mode: Planer / vertical field A,B,C,D = 0		A-B	B-D	C-D	A-C
Reference		1,397	597	1,334	635
Mode: Helical right A,D = 0 B,C = +8mm					
		A-B	B-D	C-D	A-C
		1,359	699	1,270	762
Change from reference		38	-102	64	-127
Mode: Helical left A,D = 0 B,C = -8mm					
		A-B	B-D	C-D	A-C
		1,334	762	1,207	762
Change from reference		-64	165	-127	127
Mode: Planer / horizontal field A,B = 0 B,C = -16mm					
		A-B	B-D	C-D	A-C
		1,143	940	1,080	914
Change from reference		-254	343	-254	279
		A	B		

Much more rigid design required for 3.2-m Delta

3.20- Delta Undulator Components (new design)

SLAC




Glossary:

- 1 Permanent Magnet
- 2 Magnet Holder
- 3 Carrier
- 4 M Shape Rail
- 5 V Shape Rail
- 6 Needle Bearings
- 7 Right Strongback ("E")
- 8 Left Strongback ("E")
- 9 Drive Unit Nut and Spindle

Requires rigid structure

0.75mm

2.2 t magnetic forces
due to very small gaps




Structural Stiffness Controls Strong Magnetic Forces

SLAC

Displacement
[μm]

Small Residual Displacements at Peak Linear Fields



Vertical Linear Field

Horizontal Linear Field

Will provide required micron-level reproducibility


Franz Peters 7/24/2013

Structural Stiffness Controls Strong Magnetic Forces

SLAC

Displacement
[μm]

Small Residual Displacements at Peak Linear Fields



Vertical Linear Field

Horizontal Linear Field

Will provide required micron-level reproducibility

Franz Peters 7/24/2013

13


Quadrant Tuning

SLAC




Delta Assembly Complete

SLAC





Delta Field Mapping

SLAC




Delta Field Mapping Result: Examples




Delta with Vacuum Chamber

SLAC




Phase Shifter

SLAC



Delta Undulator and Phase Shifter installed on U33

SLAC




October 2014

First Light Through Delta Undulator

SLAC



- Commissioning with beam started on 10/14/2014
- Images show spontaneous radiation of linear and circularly polarized configuration at 9.2 keV.
- The observed patterns and intensities agree with calculations by J. MacArthur.



Delta in Regular Afterburner Configuration at 930 eV

SLAC

LCLS Undulator Taper Configuration




Peak Current around 1.5 kA

- 42 μJ with Delta off
- 88 μJ with Delta on

First Phase Shifter Scan

LCLS Phase Shifter Scan

28-Oct-2014 18:24:34



$$\varphi(g, K) = \frac{2\pi}{0.030 \text{ m}} \left(\frac{e}{mc} \right)^2 PI(g)$$

Fit: $GDET = A \sin(\varphi(g, K) + B) + C g + D$
rms = 14.3 μJ


Parameter	Value	Unit
K	3.4710	
A	0.06054	mJ
B	-1.24898	rad
C	-0.00606	mJ/mm
D	0.30799	mJ

Delta in Enhanced Afterburner Configuration at 710 eV




Reverse Taper

E.A. Schneidmiller, M.V. Yurkov, "Obtaining high degree of circular polarization at X-ray FELs via a reverse undulator taper", arXiv:1308.3342 [physics.acc-ph]



- X-ray growth suppressed during reverse taper



- 30 μ J with Delta off
- 510 μ J with Delta on


Peak Current increased above 4 kA



Reverse Taper Simulation

SLAC


Regular Taper



Reverse Taper Simulation

SLAC


Reverse Taper



Reverse Taper Simulation

SLAC



Reverse Taper + Afterburner



TOF Polarimeter – DESY / EXFEL







SLAC

- 16 channels (max.) \Rightarrow Angular resolution
- Analysis of dipole photoemission
 \Rightarrow Linear polarization




TOF Polarimeter Displays

SLAC



Online Polarization Information

SLAC



$$P(\theta) = 1 + \frac{\beta}{4} \cdot [1 + 3 \cdot P_{lin} \cdot \cos(2 \cdot (\theta - \psi))]$$

Courtesy of Anton Lindahl

Online Polarization Information



$$P_{lin} \propto \sqrt{\frac{s_1^2 + s_2^2}{s_0^2}}$$

$$\begin{aligned} s_0 &= I_x + I_y \\ s_1 &= I_x - I_y \\ s_2 &= I_{45^\circ} - I_{-45^\circ} \\ s_3 &= I_{RCP} - I_{LCP} \end{aligned}$$

with

$$s_0^2 \geq s_1^2 + s_2^2 + s_3^2.$$

The degree of linear polarization as measured by the TOF polarimeter can be expressed in terms of the Stokes parameters

Scheme	E_{circ}/E_{lin}	P_{lin}	P_{circ}	$E_{xray} (\mu J)$
Crossed Polarization			low	50 ^a
Regular Afterburner	up to ~4	0.5	0.87	50 ^a
Reverse Taper	up to ~15	0.3	0.96	480 ^b
Split Beams	≥100		~1	220 ^b

The equal sign applies if the light is fully polarized. Only in this case can the degree of circular polarization be deduced from the absence of linear polarization


$$P_{circ} = \frac{|s_3|}{s_0} = \sqrt{1 - \frac{s_1^2 + s_2^2}{s_0^2}} = \sqrt{1 - P_{lin}^2}$$

The actual degree of circular polarization has since been confirmed using x-ray magnetic circular dichroism (XMCD)

^aPeak Current about 1500 A; ^b Peak Current above 4000 A

Operational Polarization Record


SLAC





LCLS-II SXR and HXR Component Layouts

Space for 3 Delta Undulators

SLAC



- Increased period length (39 mm) to match SXU segments
- Larger transverse block dimensions to reach $SXU\ K_{max} = 5.48$
- Improved carrier structure for increased stability and improved tuning.
- Water-cooled vacuum chamber.



Summary



- Adding the polarization control Delta undulator to the LCLS provides for the first time circularly polarized ultrafast x-ray pulses for experimental use.
- The final performance characteristics: nearly 100% degree of circular polarization and pulse intensities in excess of 0.2 mJ exceed expectations.
- Advanced modes of two colors with two polarizations with control of time and energy separations have already been demonstrated.
- A Delta undulator tailored for the new LCLS-II SXR line is being developed.

Acknowledgements



We thank **Leif Glaser, Frank Scholz, Jörn Seltmann, Ivan Shevchuk (DESY, Hamburg, Germany)** and **Jan Grünert (European XFEL)** for providing the polarimeter and excellent support with running the device during Delta machine development shifts.

Work was supported by U.S. Department of Energy, Office of Basic Energy Sciences, under Contract DE-AC02-76SF00515. A.B. Temnykh is supported U.S. National Science Foundation awards DMR-0807731 and DMR-DMR-0936384.

