




HIE-ISOLDE Project Status Report

Yacine KADI
CERN
HIE-ISOLDE Project

13th International Conference on Heavy Ion Accelerator Technology
Yokohama, Japan
7-11 September 2015




OUTLINE

- ISOLDE Facility
- Scope of HIE-ISOLDE Project
- Results from the Machine Commissioning
- Status of the Beam Commissioning
- Experiments for 2015
- Conclusions



ISOLDE Facility : a few facts

- ISOLDE is the CERN radioactive beam facility (approved 50 y ago!)
- Provides low energy or post-accelerated beams
- Run by an **international collaboration since 1965. Presently 13 members** (B, CERN, Dk, E, F, Ge, Gr, I, India, N, R, S, UK)
- **> 500 Users from 100 Institutions, 50 experiments / year**






Physics program @ REX

REX-ISOLDE started in 2001



108 different beams already used at REX of 1300 available!

Coulomb excitation with Miniball:

- collectivity versus individual nucleon behaviour



beam




HIE-ISOLDE aims at increasing the energy of the RIB up to 10AMeV and their intensity by a factor 10

Energy Upgrade:

The HIE-ISOLDE project concentrates on the construction of the SC LINAC and associated infrastructure in order to upgrade the energy of the post-accelerated radioactive ion beams to **5.5 MeV/u in 2016** and **10 MeV/u by 2017**

Beam Quality Upgrade:

RFQ cooler and buncher
Solid state lasers for RILIS
Higher mass resolving power HRS



Intensity Upgrade:

The design study for the intensity upgrade, also part of HIE-ISOLDE, **started in 2012**, it addresses the technical feasibility and cost estimate for operating the facility at **15 kW** once LINAC4 and Upgraded PS Booster are online.


HIE-ISOLDE Opportunities:

Reaction	Physics	Optimum energy
(d,p), ($^3\text{He},\alpha$), ($^3\text{He},\text{d}$), (d,n),... transfer	Single-particle configurations, r- and rp-process for nucleosynthesis	10 MeV/u
	pairing	5-10 MeV/u
	Structure of neutron-rich and proton-rich nuclei	8 MeV/u
	High-lying collective states	6-8 MeV/u
Compound nucleus reactions	Exotic structure at drip line	5 MeV/u
Coulomb excitation, g-factor measurements	Nuclear collectivity and single- particle aspects	3-5 MeV/u
(p,p' γ), (p, α), ...	nucleosynthesis	2-5 MeV/u




Physics @ HIE-ISOLDE

- May 2010: 34 LoI submitted
- 27 experiments already approved
- 600 shifts already allocated for day 1 physics




Instrumentation

- Miniball + T-ReX (upgrade planned) : COULEX + Transfer
- Multipurpose reaction chamber
- CORSET chamber for Fusion-fission reactions
- SPEDE: added to Miniball+T-REX
- Helios type device: transfer @ TSR
- MAYA/ACTAR: resonant scattering + transfer.
- For LS2: TSR storage ring,




Proposed beam line layout



HIAT2015, Y. Kadi, 7 Sep. 2015

HIE-ISOLDE Roadmap



Legend:




Existing REX-structures:

RFQ, IHS: 20-gap IH-structure, 7GX: 7-gap split-ring cavities, 9GP: 9-gap IH-structure


The HIE ISOLDE Cryomodules

Common vacuum concept - Actively cooled thermal shield-
Superconducting active elements: RF cavities and solenoid



The HIE ISOLDE Cryomodules

Common vacuum concept - Actively cooled thermal shield-
Superconducting active elements: RF cavities and solenoid




Choice of cavity technology

Superconducting option

- High Q (low power dissipation)
- Cryogenics
- High CW fields (30 MV/m peak)
- Possible field emission, X rays

Niobium sputtering on copper

- Thermal stability
- Mechanical stability → less sensitive to He pressure fluctuations and to mechanical vibrations → Low RF power
- Less sensitive to magnetic fields → no need of shielding the cryostat
- Potentially cheaper (especially for large series)
- Possible to recycle substrates




Roadmap of developments (2011-2013)


Strong development program focused on bias diode sputtering method. Main steps:

- Increasing baking and coating temperatures
- Increasing sputtering power (global deposition rate)
- Coating in steps
- Sputtering gas, venting gas
- Global film thickness
- Local film thickness







Top gap distance reduced to 22 mm



Performance of the first 4 series cavities



Tuning system evolution (plates and actuators)



Design : Cryomodule



Design : Cryomodule




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




Design : Cryomodule

- 5 QWR cavities (BE/RF)
 - Tuners, couplers, instrumentation
- 1 solenoid (TE/MSC)
 - 116A – 13.5T².m – NbTi
 - Immersed in 4.5K LHe 1.5 bara
 - Vapor-cooled current leads
 - Resistive splice
- Supporting frame assembly
 - Actively cooled at 4.5K
 - 316L structure
 - Live monitoring of positions
- Helium reservoir, circuits and interfaces
 - 150l of LHe, 1.5 bara nominal, 4.5K
 - Instrumentation
- Top plate and services
 - Services : 53 ports
 - Seal interface
- Thermal shield
 - Actively cooled to 55-75K Ghe, 13 bara
 - Nickel plated copper
- Vacuum vessel
 - 15mm thick 316L plates
 - Vacuum interfaces
 - 10-8 mbar.l.s-1




CM1 assembly




HIE-Isolde CM#1


Machine Commissioning




Cryogenic Plant




Cryogenic Plant



Cryogenic Plant



Cryo System: fully commissioned. Liquid He made.




Cryo Cold Line & Jumper Boxes instrumentation: installation finished
Pressure tests done on Cold Line.

HEBT Lines




HEBT Lines





HEBT commissioning: all circuits done

Site name:	Magnet name	Power consumption	PC connection	PC test	DC cable connection	Water connection	BLO connection	WIC-request interface test	WIC-PC connection	PC-direct connection	PS setup connection	Performance test	min op	max op	Released	For OP
KTOM-A0010	221378A	10100000	221382A										0	4.13		
KTOM-A0020	221378A	AT0100000	221380A										2	1.03		
KTOM-A0030	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	0	4.13		
KTOM-A0040	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	2	1.03		
KTOM-A0050	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	2	1.03		
KTOM-A0060	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	2	1.03		
KTOM-A0070	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	2	1.03		
KTOM-A0080	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	2	1.03		
KTOM-A0090	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	0	■		
KTOM-A0100	221378A	AT0100000	221384A	■	■	■	■	■	■	■	■	■	0	■		


HEBT commissioning: all circuits done








Cryo-Module 1 installed on Saturday 2nd May.
Cool-down: mid-June to mid-July




HIE ISOLDE roadmap 2015






HIE ISOLDE roadmap 2015



All HEBT hardware commissioned on schedule
CM1 cooled down and hardware tests complete
Issue with power coupler → looking for an operational point
Cryogenics Incident on 12th August

HIE ISOLDE roadmap 2015



All HEBT hardware commissioned on schedule
 CM1 cooled down and hardware tests complete
Issue with power coupler → looking for an operational point
 Cryogenics Incident on 12th August




CM1 HW commissioning: main results


- ✓ Cryogenics: ~100% availability over 2 months, then problems (4 CB stops + incident)
- ✓ Vacuum: in range of 10^{-11} mbar
- ✓ Cold alignment: ~1.2 mm vertical offset corrected
- ✓ Cavity conditioning OK, only CAV2 has FE
- ✓ Cavity tuning OK: all cavities at 101.28 MHz, mid range
- ✓ Cavity performance: 6 MV/m/CAV with less than 50 W
- ✓ Serious issue with power coupler identified
- ✓ Solenoid performance: OK, “feature” under control
- ✓ Combined powering cavities and solenoid OK
- ✓ Static heat load measured within specs (~ 10 W)
- ✓ LLRF loops working well beyond specs at 2 MV/m

HIE-ISOLDE LLRF status (as of 27.8.2018)

- Loops at nominal gain on a cavity with 5 Hz bandwidth, 1.5 MV/m
- Amplitude noise ~0.1%_{pk-pk}, phase noise ~0.2°_{pk-pk}



D. Valuch



REX Commissioning

- $2.5 < A/Q < 4.5$ acceptance
- Beam from 5 keV/u to ~ 2.85 MeV/u
- RF frequency: 101.28 MHz (9gap: 202.56 MHz)

RF Systems:

RF Structure	Final Energy [MeV/u]
4-rod RFQ	0.3
Buncher	0.3
IHS	1.2
7gap 1	1.55
7gap 2	1.88
7gap 3	2.2
9gap	2.85

Magnets:

Triplets	6
Doublets	1
Steerers	1H, 1V


Diagnostics:

REX	HIE-ISOLDE
FC	FC
MCP	Si detector
Collimator apertures	Scanning Slits
Beam attenuators	Collimator apertures


Vacuum (incl. low energy):

Sectors	10
Turbopumps	~ 20
Cryopumps	3
Gauges	~ 25


Beam to HIE-ISOLDE
2.85 MeV/u



REX commissioning highlights




- All vacuum, magnets, power converters and diagnostics systems ready
- All RF systems ready for commissioning with beam
- Beam commissioning well advanced. Achieved beam up to 2.2 MeV/u
- Phasing of 9-gap completed this week (to reach 2.85 MeV/u)



REX Beam Commissioning



- ✓ Commissioning with beam started on wk. 25 (June 16th)
- ✓ Beam with an A/Q=4.0 was accelerated to 0.3 MeV/u (RFQ output energy)
- ✓ We reached the first diagnostic box and commissioned the FC, MCP and collimator wheel on wk. 25
- ✓ Beam transmission through RFQ for different power levels on wk. 26






REX Beam Commissioning

- ✓ First diagnostics box of HIE-ISOLDE installed at the end of wk. 27
- ✓ First beam in FC and to the Si detector (used for relative beam energy measurements) with 0.3 MeV/u energy on wk. 28



Diagnostic box:
FC, Si detector,
Scanning slit
Collimator slit





Experiments for 2015 (wk.42)

- [IS557](#): Coulomb excitation $^{74}\text{Zn} - ^{80}\text{Zn}$ ($N=50$): probing the validity of the shell-model descriptions around ^{78}Ni on experimental station XT01 using MINIBALL Ge detector array
- [IS561](#): Transfer reactions at the neutron dripline with triton target on experimental station XT02 using Scattering chamber
- [IS563](#): Coulomb excitation of 182-184Hg: Shape coexistence in the neutron-deficient lead region on experimental station XT01 using MINIBALL Ge detector array + SPEDE spectrometer



Overall Summary

- Plenty of challenging physics waiting for the starting of HIE-ISOLDE!
- Many new groups and devices have been attracted by the increase of energy of the post-accelerated beams.
- The physics cases approved expand over the wide range of post-accelerated beams available at ISOLDE with more than six hundred shifts approved for day one physics.
- Enormous progress since April 2015
 - Infrastructure in place
 - HEBT hardware commissioning completed
 - CM1 installed, cooled and powered. Full test campaign carried out
 - REX beam commissioning well advanced
 - Beam commissioning of SC Linac is possible in September
- **However: the results of hardware tests (problem on RF couplers) highlighted that CM1 is not fully qualified for sustained operation as planned**
- **Agree with Collaboration on a common scope for 2015 Physics run**





Thank you for your attention

