




# Technical Developments in Support of Accelerator-based Science at SLAC

Marc Ross (SLAC LCLS-II)

International Beam Instrumentation Conference

September 15, 2014



# Technical Developments for Accelerator-based Science

---

## Basic Energy Science Advisory Committee (BESAC) and Particle Physics Project Prioritization Panel (P5)

1. *BESAC recommends FEL construction:*

- SLAC proposed LCLS-II, now accepted,
- a new 4 GeV CW superconducting linac
- LCLS-II involves several US partner-labs
- now in full-swing.

2. *P5 strongly supports International Linear Collider (ILC) development,*

- directed toward construction in Japan.

**Both rely on L-band superconducting RF (SRF)  
technology in development for 25 years.**

# SRF Development for particle physics deployment phase:

---

SRF technology was developed for use in high-energy physics accelerators.


Pioneers: e+/e- collider storage rings at DESY (Petra), Cornell (CESR), KEK (Tristan), and Cern (LEP)

Goal: cost-effective, high-gradient, reliable SRF for next generation e+/e- colliders: storage-ring ‘factories’ and linear colliders.

TESLA collaboration: increasing the practical SRF accelerating gradient to propose a multi-kilometer pulsed SRF linac.

1. increase industrial involvement,
2. reduce static cryogenic-loss,
3. improve packing-factor

# SRF Development for particle physics deployment phase:



# SRF for the International Linear Collider (2005 – present)

---

## 2012: International Linear Collider (ILC) Technical Design Report

- ILC Technical Design:
  - standardized, industrialized, production recipe for 1.3 GHz bulk-niobium SRF cavities
  - Performance demonstration, production capability, cost estimate

European XFEL project, (DESY host), with roughly 100 (800 SRF resonator cavities) cryomodules using exactly this technology (2016)

LCLS-II project, (SLAC host), 300 cavities using the CW adaptation of this technology

# Outline

---

1. Industrialization of 1.3 GHz SRF technology
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
2. LCLS-II
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
3. SRF for LCLS-II
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Multi-lab partnership
4. Implications for ILC

# Outline

---

- 1. Industrialization of 1.3 GHz SRF technology**
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
- 2. LCLS-II**
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
- 3. SRF for LCLS-II**
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Multi-lab partnership
- 4. Implications for ILC**

# SRF: ILC ↔ LCLS-II ↔ ILC

---

Before: TESLA Collaboration, XFEL, SRF R&D

2013: ILC TDR International Review (Feb)

Performance Demonstrations, Industrialization, Cost

2013: LCLS-II CW SRF Linac proposed to DoE – SC(BES)

CD-0 (Aug), CD-1 (Aug 2014), CD-2/3 (3QFY15)

2014: High Q0 Process development (Apr – Sep)

Fermilab (lead), JLab, Cornell; (Cavities from FNAL)

2018: *LCLS-II Cryomodule Construction Complete (Aug)*

→ *First light at end of FY2019*

2018: *US Infrastructure Qualified and Demonstrated*

→ *ready for ILC or ?*

*SRF Cost Reduction / Risk Reduction through application*

# LCLS-II SCRF linac basic building block: 9-cell sheet-metal cavity



Figure 1.2-1: A TESLA nine-cell 1.3 GHz superconducting niobium cavity.

~ 70 parts electron-beam welded at high vacuum

- ~  $1.25 \text{ m}^2 \times 3\text{mm}$  thick sheet metal

pure niobium and niobium/titanium alloy

- niobium cost similar to silver

weight ~ 70 lbs


6 flanges

Colder is better – to a point

## SCRF vs temperature

SLAC

### Measurement of the Surface resistance




R<sub>BCS</sub> ~ 8nΩ,  
理論と良く合っている。

Real surface resistance : R<sub>S</sub> = R<sub>BCS</sub>(T) + R<sub>res</sub>

# SRF Specifics and Constraints

What happens when microwave is input a cavity?



*Surface resistance* is very very small.

→ Cavity performance strongly depends on the surface.

Thermal conductivity @ superconducting state is very small.


→ *High thermal conductivity* is very important.

# 1300 MHz SCRF

## Cavity:

1.7 million volts  
acceleration  
between adjacent  
irises.

Electric current in  
the SCRF  
resonator is  
entirely in a thin  
film close to the  
internal surface





# 1300 MHz SCRF

## Cavity:

1.7 million  
acceleration  
between a  
irises.

Electric cur  
the SCRF  
resonator  
entirely in  
film close  
internal su





# 1300 MHz SCRF


## Cavity:

1.7 million  
acceleration  
between a  
irises.

Electric cur  
the SCRF  
resonator  
entirely in  
film close  
internal su



# 1300 MHz SCRF Cavity inside its liquid-filled tank




- 9 cell resonator cavity
- Ports:
  - Beam in /out
  - Bring in power
  - Monitor field
  - Extract unwanted frequencies

better


# Q-E Curves (Performance)

Heating to Cold helium



# SRF Cavity Gradient Progress


## L-Band SRF Niobium Cavity Gradient Envelope and Gradient R&D Impact to SRF Linacs



Steady progress in SRF cavity gradient makes SRF an enabling technology  
SRF based electron linacs (CW & pulsed) have track record of successful operations

# SRF Cavity Gradient Progress

## L-Band SRF Niobium Cavity Gradient Envelope and Gradient R&D Impact to SRF Linacs




Steady progress in SRF cavity gradient makes SRF an enabling technology  
SRF based electron linacs (CW & pulsed) have track record of successful operations

Step hosted	Industry	Industry/Lab- ratory	Hub- laboratory	ILC Host- laboratory
Regional constraint	no	yes or no	yes	yes
Sub-comp/material - Production/Procurement	Nb, Ti, specific comp. ...		Procurement	
9-cell Cavity - Manufacturing	9-cell-cavity, Process, He-Jacketing		Procurement	
9-cell Cavity - Performance Test			Cold, gradient test	
Cryomodule component - Manufacturing	V. vessel, cold-mass ...		Procurement	
Cryomodule/Cavity - Assembly		Cav-string/ CM-assembly		
SCRF Cryomodule - Performance Test			Cold, gradient test	
Accelerator integration, Commissioning				Accelerator sys. Integ.

```


graph TD
    A[Sub-comp/material - Production/Procurement] --> B[9-cell Cavity - Manufacturing]
    B --> C[9-cell Cavity - Performance Test]
    D[Cryomodule component - Manufacturing] --> E[Cryomodule/Cavity - Assembly]
    E --> F[SCRF Cryomodule - Performance Test]
    G[Accelerator integration, Commissioning]
    C --> H[Cold, gradient test]
    D --> I[Cold, gradient test]
    E --> J[Cav-string/CM-assembly]
    J --> K[Accelerator sys. Integ.]
    H --> L[Procurement]
    I --> M[Procurement]
    I --> N[Cold, gradient test]
    M --> O[Procurement]
    N --> P[Cold, gradient test]
    P --> Q[Accelerator sys. Integ.]
    L --> R[Procurement]
    O --> S[Cold, gradient test]
    S --> T[Accelerator sys. Integ.]
    P --> U[Procurement]
    R --> V[Cold, gradient test]
    V --> W[Accelerator sys. Integ.]
    S --> X[Procurement]
    T --> Y[Cold, gradient test]
    W --> Z[Accelerator sys. Integ.]
    U --> AA[Procurement]
    V --> BB[Cold, gradient test]
    BB --> CC[Accelerator sys. Integ.]
    X --> DD[Procurement]
    Y --> EE[Cold, gradient test]
    EE --> FF[Accelerator sys. Integ.]
    Z --> GG[Procurement]
    AA --> HH[Cold, gradient test]
    CC --> II[Accelerator sys. Integ.]
    EE --> JJ[Cold, gradient test]
    FF --> KK[Accelerator sys. Integ.]
    GG --> LL[Procurement]
    HH --> MM[Cold, gradient test]
    KK --> NN[Accelerator sys. Integ.]
    JJ --> OO[Procurement]
    MM --> PP[Cold, gradient test]
    PP --> QQ[Accelerator sys. Integ.]
    LL --> RR[Procurement]
    OO --> SS[Cold, gradient test]
    SS --> TT[Accelerator sys. Integ.]
    PP --> UU[Procurement]
    TT --> VV[Cold, gradient test]
    VV --> WW[Accelerator sys. Integ.]
    RR --> XX[Procurement]
    SS --> YY[Cold, gradient test]
    WW --> ZZ[Accelerator sys. Integ.]
    XX --> AAA[Procurement]
    YY --> BBB[Cold, gradient test]
    BBB --> CCC[Accelerator sys. Integ.]
    XX --> CCC
    AAA --> DDD[Procurement]
    BBB --> EEE[Cold, gradient test]
    EEE --> FFF[Accelerator sys. Integ.]
    CCC --> GGG[Procurement]
    DDD --> HHH[Cold, gradient test]
    FFF --> III[Accelerator sys. Integ.]
    GGG --> JJJ[Procurement]
    HHH --> KKK[Cold, gradient test]
    III --> LLL[Accelerator sys. Integ.]
    JJJ --> MMM[Procurement]
    KKK --> NNN[Cold, gradient test]
    LLL --> OOO[Accelerator sys. Integ.]
    MMM --> PPP[Procurement]
    NNN --> QQQ[Cold, gradient test]
    OOO --> RRR[Accelerator sys. Integ.]
    PPP --> SSS[Procurement]
    QQQ --> TTT[Cold, gradient test]
    RRR --> UUU[Accelerator sys. Integ.]
    SSS --> VVV[Procurement]
    TTT --> WWW[Cold, gradient test]
    UUU --> XXX[Accelerator sys. Integ.]
    VVV --> YYY[Procurement]
    WWW --> ZZZ[Cold, gradient test]
    XXX --> AAAA[Accelerator sys. Integ.]
    YYY --> ZZZZ[Cold, gradient test]
    ZZZZ --> AAAA
  
```

# Vertical Cavity Test Results at DESY: 1995-2006



Vertical Test; 1500 MHz 7 cell;  
10% gradient correction

### Jefferson Lab 12 GeV C100 Cavity Final $E_{max}$





**E.ZANON**  
S.p.A.



research  
instruments

- 2 Europe
- 3 Americas
- 4 Asia

**MITSUBISHI**  
HEAVY INDUSTRIES, LTD.

Our Technologies, Your Tomorrow

**TOSHIBA**

Leading Innovation >>>

**HITACHI**  
Inspire the Next

**Energy Advanced Systems, Inc.**



**NIOWAVE**  
[www.niowaveinc.com](http://www.niowaveinc.com)

**PAVAC**  
INDUSTRIES INC.

Global Industrial Cavity  
Fabrication Partners –  
*qualified\**



宁夏东方钽业股份有限公司  
NINGXIA ORIENT TANTALUM INDUSTRY CO.,LTD.

\* (or soon to be)


# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out

Building lot I about 600 m<sup>2</sup>




Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup> for services)




# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out

Building lot I about 600 m<sup>2</sup>



Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup> for services)




# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out


## Building lot I about 600 m<sup>2</sup>



Chem,  
rinse, and  
clean-  
room



Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup> for services)





# Ovens


# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out

## Building lot I about 600 m<sup>2</sup>




ing lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup> for services)



# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out

## Building lot I about 600 m<sup>2</sup>




# EB- Welder



## Receiving

Chem,  
rinse, and  
clean-  
room

Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup> for services)




## Ovens


# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out

Building lot I about 600 m<sup>2</sup>




Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup> for services)




# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out

Building lot I about 600 m<sup>2</sup>




Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup>)




# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out

Building lot I about 600 m<sup>2</sup>




Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup>)




# Infrastructure for SC cavities production ( D )

## Cavity's production lay-out


Building lot I about 600 m<sup>2</sup>



Building lot IV 1200 m<sup>2</sup> (plus 600 m<sup>2</sup>)




# An Accelerator Complex for 17.5 GeV



## 100 accelerator modules

### Some specifications

- Photon energy 0.3 - 24 keV
- Pulse duration ~ 10 - 100 fs
- Pulse energy few mJ
- Superconducting linac. 17.5 GeV
- 10 Hz (27 000 b/s)




## 800 accelerating cavities


**1.3 GHz / 23.6 MV/m**



**25 RF stations  
5.2 MW each**




**SC Linac (~ 1 km)**




**EXFEL: 1/20 Scale Project on going, Industrialization being verified !!**

0

# SCRF Cavity Production




# SCRF Cavity Production



- **Gradients** in average above specification (almost 300 cavities tested)
  - Average usable gradient after delivery ( $26.8 \pm 7.1$ ) MV/m
  - 2/3 of cavities can be used w/o further treatment
  - 1/3 is getting additional treatm. -> usable grad. increased to ( $29.6 \pm 5.1$ ) MV/m

2014.6: # cavities produced > 300. Usable Gradient:  $\sim < 30 >$  MV/m





Gate valve	CV 1	CV2	CV3	CV4	CV5	CV6	CV7	CV8	BQ
	AC114	AC156	AC146	AC154	AC157	AC158	AC151	AC152	
Eacc (VT)	31,4	31,5	41,5	36,9	29,7	38,8	22,2	28,9	
Fe limit (VT)	31,4	31,5	41	36,9	29,7	38,8	16,8	20	
CMTB	23,2	31,4	40,8	38,5	31,5	38,1	22,7	33	


## XM-3 total gradient compared with VT

229,6 MV  
231,8 MV  
29,0 MV/m


# Will it work ? System Tests - Fermilab



# Will it work ? System Tests - Fermilab



# Will it work ? System Tests - Fermilab



# Outline

---

1. Industrialization of 1.3 GHz SRF technology
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
2. LCLS-II
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
3. SRF for LCLS-II
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Multi-lab partnership
4. Implications for ILC

# Outline

---

1. Industrialization of 1.3 GHz SRF technology
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
2. LCLS-II
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
3. SRF for LCLS-II
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Multi-lab partnership
4. Implications for ILC

# Linac Coherent Light Source Facility

First Light April 2009, CD-4 June 2010

Injector at  
2-km point

Existing Linac (1 km)  
(with modifications)

New  $e^-$  Transfer Line (340 m)

Undulator (130 m)

Near Experiment Hall

X-ray Transport  
Line (200 m)

Far Experiment Hall





NATIONAL ACCELERATOR LABORATORY



UCLA


# Photons for Basic Energy Science (Material, Condensed Matter, Biology, Chemistry...)



- Hard X-Ray Source:
  - 1-5 keV w/ new 4 GeV SC linac
  - Up to 25 keV with LCLS Cu Linac
- Soft X-Ray Source:
  - 250 eV-1.2 keV w/ 4 GeV linac
- **Both linacs feed HXR undulator**


# LCLS-II Concept

Use 1<sup>st</sup> km of SLAC linac for CW SCRF linac



# LCLS Layout in SLAC Linac Tunnel

(only approximately to scale)



## LCLS-II Objectives:

---

- Build 4 GeV (up to 300 micro-Amp) CW superconducting linac based on TESLA / ILC / E-XFEL 1.3 GHz technology
- Develop cavity process for high-Q0 production
- Develop CW cryomodule design and operations scheme for 110 W @ 2K / CM (or better) based on high-Q0 cavity process
- Use industrial capability for 1) dressed-processed-cavity, 2) coupler, and 3) vacuum-vessel/cold-mass production
- Adapt JLab ‘CHL-2’ (12 GeV Upgrade) Cryoplant for SLAC

## LCLS-II Cavity Control

---

10 to 100x lower current than ILC / XFEL

- (LCLS-II 60 micro Amp / EXFEL - ILC 6 mA)
- → Matched LCLS-II loaded  $Q_L \sim 3e8$ ; effective resonance width very narrow; BW few Hz
- Difficult with today's state-of-the-art cavity controls


LCLS-II:  $6e6 < Q_L < 1e8$ ; nominal  $4e7$  BW 50 Hz

ILC / XFEL:  $1e6 < Q_L < 1.4e7$

***Microphonics / cavity resonance control → key R&D topics for low current CW linacs***

- Also useful for ILC

# LCLS-II Linac



Closely based on the European XFEL / ILC / TESLA Design


Under development ~ 20 years with **> 1000 cavities** to be made and tested (inc. 800 for E-XFEL – completed 2016)

- Thirty-five **1.3 GHz 8-cavity cryomodules**
- Two **3.9 GHz 8-cavity cryomodules**
- Four cold segments (L0, L1, L2 and L3) which are separated by warm beamline sections.
- 280 1.3 GHz cavities
- 16 3.9 GHz cavities

# Re-purposing the SLAC Tunnel

SLAC Linac Tunnel: 11 wide x 10 feet high


It will be a tight fit!




# Re-purposing the SLAC Tunnel

SLAC Linac Tunnel: 11 wide x 10 feet high


It will be a tight fit!



# LCLS-II Cryomodule in 3-D




# CM, Feed Cap and Bypass and Vertical Transferline




## Cryomodule from the side:

12.6 m long; 1 m diameter

- (Similar to LHC dipole)
- 8 cavities w / superconducting quad magnet



# Future view along linac – after LCLS-II SCRF linac installation:



# Project Collaboration: SLAC couldn't do this without...



- 50% of cryomodules: 1.3 GHz
- Cryomodules: 3.9 GHz
- Cryomodule engineering/design
- Helium distribution
- Processing for high Q (FNAL-invented gas doping)



- 50% of cryomodules: 1.3 GHz
- Cryoplant selection/design
- Processing for high Q



- Undulators
- e<sup>-</sup> gun & associated injector systems




- Undulator Vacuum Chamber
- Also supports FNAL w/ SCRF cleaning facility
- Undulator R&D: vertical polarization




- R&D planning, prototype support
- processing for high-Q (high Q gas doping)
- e<sup>-</sup> gun option


# Summary Schedule



# Summary Schedule



# Summary Schedule



# Outline

---

- 1. Industrialization of 1.3 GHz SRF technology**
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
- 2. LCLS-II**
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
- 3. SRF for LCLS-II**
  - Historic shift – very high performance resonators with  $Q_0 \sim 1e11$
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Three-lab (Fermilab, JLab and Cornell) development and demonstration
  - Multi-lab partnership
- 4. Implications for ILC**

# Outline



---

1. Industrialization of 1.3 GHz SRF technology
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
2. LCLS-II
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
3. SRF for LCLS-II
  - Historic shift – very high performance resonators with  $Q_0 \sim 1e11$
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Three-lab (Fermilab, JLab and Cornell) development and demonstration
  - Multi-lab partnership
4. Implications for ILC

# Motivation for High $Q_0$ R&D

High  $Q_0$  doping  
developed by Fermilab

- High  $Q_0$  is a surrogate for low rf losses = low dynamic cryo heat load
- New Nb surface doping phenomenon with significantly lowered  $R_{s-BCS}$  and  $R_{s-residual}$  discovered 2012-2013
- Our mission: expedite development for use in LCLS-II



# Fermilab-developed ‘gas-doping’ process →

---

Fermilab has developed a cavity processing recipe that results in high quality factors (>3E10) at operating gradients between 10 and 20 MV/m.

In 2014 Fermilab led a Q0 program in collaboration with Cornell and JLab.


The primary goal is to develop a reliable and industrially compatible processing recipe to achieve an average Q0 of 2.7E10 at 16 MV/m in a practical cryomodule; minimum 1.5E10.

To reach this goal, the collaborating institutions processed and tested single-cell and 9-cell 1.3 GHz cavities in a successive optimization cycle.

The deliverable is industrial capability and cost-effective production yield.

- Supporting the cryoplant design choices


# Motivation for High $Q_0$ R&D




"The best cavities of 2010"

The SRF world is changing

"The best dressed cavity of 2014"  
(so far)  
TB9AES011




# Americas ILC Linac Cost Versus Cavity Gradient and Qo



# $Q_0$ picture still looks good for LCLS-II, but new discipline will be required

Theoretical, Previous Standard, and Recent -  $Q_0$  Limit @ 1.3 GHz, Tesla cell Shape



# FNAL IB4 Vacuum Oven



# LCLS-II High Q0 R&D Program – Preliminary Nine-Cell VT Results


High Q0 testing done at 3 labs: Fermilab (from 2012); JLab and Cornell (2014)

High Q0 Program 9 cell results		
	Q0	E_acc (MV/m)
Average	3.5E+10	19.0
Yield	100% (avg. 2.7e10)	47% (18 MV/m) 88%(16 MV/m)
Number of cavities tested; some multi-pass		
17 (3 Cornell; 5 Jlab; 9 Fermilab)		

***Initial results meet LCLS-II VTS High Q0 criteria: 30% margin***

# Field Emission Onset

## Field Emission Onset Distribution (Ten C100's and R100)



Mike Drury,  
JLab

26% reduction  
from Vertical  
Test to CM  
installation

# Effect of cool-down speed-through-transition


Cool-down speed appears to be very important: **Fast is better**

“Dressed” cavity results under different cooling regimes.


- Thermogradient-generated fields have no impact on Q in VT, slow cooling through  $T_c$  has dramatic effect.

[fast ~1.8K/min; slow ~0.3K/min through 9.2K]



- Precautions will have to be taken in CM to obtain fast cooling through transition.



# LCLSII Cavity Tests in the Cornell one-cavity Horizontal-Test-Cryomodule (HTC)



- Small modifications were needed to host a 9-cell cavity (changes to 2-phase line, cavity support).



Fermilab Horizontal Test Cryostat  
With Three Axis Magnetic Cancellation

# Outline

---

1. Industrialization of 1.3 GHz SRF technology
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
2. LCLS-II
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
3. SRF for LCLS-II
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Multi-lab partnership
4. Implications for ILC

# Outline

---

1. Industrialization of 1.3 GHz SRF technology
  - 1990's to present
  - TESLA, E-XFEL, and ILC (also CEBAF 12 GeV)
2. LCLS-II
  - Free Electron Laser at SLAC – based on ILC / E-XFEL SRF
3. SRF for LCLS-II
  - Low cryogenic-loss cavities: 'N<sub>2</sub> doping' process developed by Fermilab
  - Multi-lab partnership
4. Implications for ILC

# For ILC: Summary

---

## Cavity / Cryomodule:

- Cost Validation : **few percent scale**
- Cost Reduction
  - Applied production v/v continued R&D
  - (tooling, infrastructure, and experience)
  - From C100 to EXFEL: **factor 2 cavity cost reduction**
  - (Hasan's target)
- Technical Risk Mitigation
  - **Demonstrate construction and performance** of ILC-type cryomodules for science in the US

For US, the work on ILC and now on LCLS II has brought together SRF programs in a way that maximizes collaboration, efficient sharing of IP, and facilities giving the most “bang for the buck”.