

First LHC Emittance Measurements at 6.5 TeV



Maria Kuhn^{1,2} – September 16, 2015

*F. Antoniou*², *E. Bravin*², *B. Dehning*², *J. Emery*², *V. Kain*²,
A. Langner^{1,2}, *Y. Papaphilippou*², *E. Piselli*², *G. Trad*²,

¹Hamburg University, Hamburg, Germany,


²CERN, Geneva, Switzerland

- o Injection
- o Ramp
- o Squeeze
- o Collisions



- o Two circulating beams.
 - Beam 1 rotating clockwise, beam 2 counter-clockwise.
- o Collisions in four interaction points in the LHC.
 - ATLAS and CMS are the two large multi purpose detectors.

- o Injection
- o Ramp
- o Squeeze
- o Collisions




Proton beam parameters	LHC Design	2012 LHC	Early 2015 LHC
# bunches/ beam	2808	1374	3 - 458
Bunch spacing [ns]	25	50	25 and 50
Mean bunch length [ns]	1.3	1.2	1.2
Bunch intensity [10^{11} p]	1.15	1.1 - 1.7	1.0 – 1.2
Emittance at injection [μm]	3.5	1.5 – 2.0	1.5 – 3.0
Collision energy/beam [TeV]	7	4	6.5
Emittance at collision [μm]	3.75	2.4	1.5 – 4.0
β^* at ATLAS/CMS [m]	0.55	0.6	0.8

Reminder: 2012 Emittance Blow-up

- o In 2012 LHC was operated with high brightness beams.
 - Transverse emittance could not be preserved during the LHC cycle.
 - $\sim 0.4 - 0.9 \mu\text{m}$ normalized emittance growth from LHC injection to start of collisions.
 - But emittance measurement precision during LHC Run 1 doubtful.

2012 LHC
performance



- o Several types of beam profile measurement systems in the LHC.
 - The wire scanners are the most precise and versatile instruments.
 - Two operational wire scanners per beam.
 - Horizontal and vertical.
- o **Wire scanners cannot be used with high intensity physics fills.**
 - Synchrotron light telescope (BSRT) is used for that purpose.
- o BSRT cross calibrated with wire scanners.
- o Currently, wire scanners are the only instrument to measure beam sizes through the LHC energy ramp.
 - Low intensity test fills (a few bunches) are measured to evaluate emittance preservation during the LHC cycle.

- o Transverse normalized emittance ε :

- (For location with no dispersion)

Lorentz factor γ
(beam energy)

Wire scanner beam size σ accuracy

$$\varepsilon_{x,y} = \gamma \frac{\sigma_{x,y}^2}{\beta_{x,y}}$$

- Wire position measurement precision
 - Estimated position measurement potentiometer precision: 50 μm
- Wire position measurement calibration
 - Verified with beam by orbit bump scans at the wire scanner location


LHC Run 2 optics measured with k-modulation at 450 GeV and turn-by-turn phase advance method at 6.5 TeV.

- β function accuracy better than 3 %.

- o Using local orbit bumps to verify the wire position measurement calibration of the wire scanners.
 - Beam position measured with LHC orbit system and extrapolated to wire scanner.
 - Compared to mean position obtained from Gaussian fit to measured transverse beam profile.
 - Measurements at 450 GeV and 6.5 TeV are consistent.

Example B2V1: slope of linear fit shows + 3.3 % calibration error.

→ Overestimating B2V emittances by 6.6 %.



- o Wire scanner position calibration verification results ($\Delta\epsilon_{\text{calibration}}$):
 - Another set of orbit bumps foreseen for the near future to check reproducibility of obtained results.
 - The results in this talk do not include a correction of the calibration.
- o All wire scanner measurements show large σ spread from scan to scan ($\Delta\epsilon_{450\text{GeV}}$ and $\Delta\epsilon_{6.5\text{TeV}}$).
 - Depending on scanner and energy.

Wire Scanner	$\Delta\epsilon_{\text{calibration}}$ [%]	$\Delta\epsilon_{450\text{GeV}}$ [%]	$\Delta\epsilon_{6.5\text{TeV}}$ [%]
B1H2	+ 7.2	25	20
B1V2	- 5.2	20	10
B2H1	+ 9.0	25	15
B2V1	+ 6.6	15	10


- o Wire scanner shower product amplified by photomultiplier (PM).
 - Amplification settings (gain + filter) can alter obtained beam profile.
- o LHC Run 1: strong dependence of measured σ on PM settings.
- o **Optimum PM working point has to be established!**
 - Scan through all available gain and filter setting combinations.

Bunches with different beam sizes were injected.

To remove natural ε growth, scans with fixed reference settings done after each settings change.

→ Exponential fit

Example: B2V1 at 450 GeV




- Wire scanner shower product amplified by photomultiplier (PM).
 - Amplification settings (gain + filter) can alter obtained beam profile.
- LHC Run 1: strong dependence of PM settings on measured σ .
- Optimum PM working point has to be established!**
 - Scan through all available gain and filter setting combinations.

Measured beam sizes minus the fitted growth.

Measurements with same gain + filter settings are averaged.

→ No sign of PM saturation at 450 GeV could be detected.

→ Same for 6.5 TeV.




First Emittance Measurements (1)

- o Example Fill 4284 (August 28, 2015):
 - 3 bunches with different initial emittances, intensities ($0.6 - 1.1 \times 10^{11}$ ppb) and bunch lengths (1.0 – 1.25 ns).

IBS simulations with MADX IBS module include measured initial beam parameters, and radiation damping.

→ Measurements in the horizontal planes match IBS simulation.



- o Example Fill 4284 (August 28, 2015):
 - 3 bunches with different initial emittances, intensities ($0.6 - 1.1 \times 10^{11}$ ppb) and bunch lengths (1.0 – 1.25 ns).

IBS simulations with MADX IBS module include measured initial beam parameters, dispersion, and radiation damping.

Emittance growth through the cycle of bunch 3

	$\varepsilon_{450\text{GeV}} [\mu\text{m}]$	$\varepsilon_{6.5\text{TeV}} [\mu\text{m}]$	$\Delta\varepsilon [\%]$	$\Delta\varepsilon_{\text{sim}} [\%]$
B1H	1.90	2.08	9	8
B1V	1.71	2.04	19	-2
B2H	1.50	1.65	10	10
B2V	1.58	1.95	23	-2


→ Measurements in the horizontal planes match IBS simulation.

Vertical emittance growth through the cycle could not be reproduced with IBS simulations.

- o Measured β during ramp not yet available.
 - Using linear interpolation of measured β at injection + flattop.
- o Current β knowledge results in unphysically growing/shrinking ε .
 - Run 1 experience: non-monotonically changing β functions during the ramp.

Measurements in the horizontal planes consistent with IBS simulations during the ramp.

Beam 2 vertical emittances grow 20 % (~ 0.3 μm).




- o Within measurement accuracy emittances are conserved during the β^* squeeze.
 - Result is reproducible.

Emittances measured with BSRT and averaged over several hundred measurements.

Also need measured β functions during the squeeze.

Emittance Growth Squeeze Fill 3960



- o Comparison of emittance from wire scans and luminosity:
 - Fill 3954 (July 4, 2015), one bunch in collision.
 - According to experts ATLAS luminosity low by ~10 % with uncertainty ± 10 %.
 - 5 % error on crossing angle
 - ± 1 cm error on measured bunch length.
 - β^* measured with k-modulation with 1 % uncertainty.

$$L = \frac{k N^2 f \gamma}{4 \pi \beta^* \varepsilon} \cdot F$$

L Luminosity
 k # bunches
 N # protons / bunch
 f Revolution freq.
 F Luminosity reduction factor

	Injection	Collision	Growth	
WS ε [μm]	2.51 ± 0.10	2.75 ± 0.20	0.24	10 %
ATLAS ε [μm]	n.a.	2.97 ± 0.36	0.46	19 %

- o Preliminary: ATLAS and wire scanner results agree within errors.
 - Better than during Run 1.


Radiation Damping at 6.5 TeV

- o At high energies protons circulating in the LHC emit enough synchrotron radiation to modify the beam parameters
 - First observed during LHC Run 2
 - Counteracts IBS: reduction of vertical emittance

Simulations with MADX IBS module.

→ Simulation predicts slightly faster emittance decrease than measured with BSRT.



→ Additional emittance growth from proton collisions + beam-beam effects not included in the simulation.



- o Emittance in collisions derived from luminosity.
- o Injection emittance of first batch measured with SPS and LHC wire scanners.

Emittance blow-up through the cycle:

- o 50 ns beams show very little blow-up ($\sim 10\%$), much smaller than during Run 1.
- o Large blow-up for 25 ns beams (25 % for most recent fills).
 - Electron cloud effects
 - Beam instabilities



Summary & Conclusion

- o Good progress in understanding wire scanner emittance measurements for LHC Run 2.
 - Wire scanner calibration verified, no PM saturation effects detected.


Emittance growth during the LHC cycle:

- Horizontal emittance growth matches IBS simulations.
 - Small growth in the vertical planes not yet understood.
 - Caveat: single bunch fills.
 - Synchrotron radiation damping observed for the first time at 6.5 TeV.
 - With still not fully calibrated luminosity data: emittances from wire scans and ATLAS luminosity agree within errors.
- o Smaller emittance blow-up ($\sim 10\%$) through the cycle than during Run 1 for 50 ns beams.
 - o 25 ns physics beams show much larger growth.
 - Electron cloud effects and beam instabilities.

APPENDIX


- o LHC cycle and beam parameters
 - LHC Run 1 transverse normalized emittance blow-up
- o LHC wire scanner intensity limitations
- o Run 2 LHC wire scanner accuracy
 - Wire position measurement calibration
 - Photomultiplier working point investigations
- o First transverse normalized emittance measurements
 - Emittance growth during the LHC ramp
 - Emittance preservation during the squeeze
 - Emittance at start of collisions
 - Radiation damping at 6.5 TeV
- o Current performance of the LHC

CERN Accelerator Complex




- Photomultiplier (PM) gain and filter can have a strong influence on measured beam size
 - See measurements of 2012

Observed strong gain dependence at 450 GeV and 4 TeV during Run 1!




PM saturation studies at 450 GeV in 2012.



PM saturation studies at 4 TeV in 2012.

- o Measurements at 6.5 TeV more difficult.
 - Smaller range of possible PM settings before ADC saturation.
- o No evident sign of PM saturation at 6.5 TeV could be seen.




- o Run 1 investigations showed significant dependency of measured beam size on PM settings.
- ➔ LHC wire scanner upgrade during Long Shutdown 1:
 - One broken wire scanner replaced (beam 2).
 - Power supply schematics upgraded.
 - PM gain dependency on light intensity reduced.

- o Can use results from optics measurements with the turn-by-turn phase advance method and k-modulation for:

	IR4				IP1/2/5/8
	Injection	Ramp	Flattop	After Squeeze	β^*
K-modulation	X				X
Turn-by-turn			X	X	

- o Outstanding measurements:
 - K-modulation at 6.5 TeV and after the squeeze
 - Turn-by-turn phase advance measurements at 450 GeV (repeated) and **during the ramp!**
- o For emittance plots: using measured β where possible
 - **β function measurement error < 3 %**
 - Maximum measured beta beat is 5 % at the wire scanners
 - Linear interpolation during the ramp and squeeze

o Sinusoidal k-modulation in IP1/5 on August 8, 2015




Measurement error on tune oscillation amplitude in sub-percent level

→ β^* meas. uncertainty $\leq 1 \%$

→ Beta beat $\leq 1 \%$

→ Compatible with turn-by-turn measurements

Preliminary!	IP1 [m]		IP5 [m]	
	B1	B2	B1	B2
$\beta^* \text{ H}$	0.81	0.79	0.80	0.80
$\Delta\beta \text{ H}$	0.01	0.004	0.001	0.01
$\beta^* \text{ V}$	0.81	0.79	0.79	0.79
$\Delta\beta \text{ V}$	0.01	0.01	0.01	0.002



Bunch Length Measurement

- o Longitudinal bunch shape not Gaussian at 6.5 TeV
 - Due to controlled longitudinal RF blow-up at flattop energy
 - o But LHC bunch length monitor publishes 4σ bunch length values based on FWHM algorithm assuming Gaussian profiles
- ➔ **Bunch length error ± 1 cm!**
- ➔ “True” emittance from luminosity should be larger by $0.1 \mu\text{m}$

