



Next-Generation MADOCa for The SPring-8 Control Framework

T. Matsumoto, Y. Furukawa, M. Ishii
JASRI/SPring-8

Outline

- Introduction to MADOCA
- MADOCA II Messaging
- MADOCA II Applications
- Summary

Introduction to MADOCA

- Control Framework originally developed at SPring-8, Japan
- Adopted in several facilities for various control applications
 - SPring-8, SACLA, NewSUBARU, HiSOR
 - Accelerator, beamline and experimental station controls
- Successfully utilized since 1997



*Photos courtesy of RIKEN/JASRI

Introduction to MADOCA

- Control Framework originally developed at SPring-8, Japan
 - **Message And Database Oriented Control Architecture**
- Adopted in several facilities for various control applications
 - SPring-8, SACLA, NewSUBARU, HiSOR
 - Accelerator, beamline and experimental station controls
- Successfully utilized since 1997



*Photos courtesy of RIKEN/JASRI

MADOC A Messaging

- Based on a text command with S/V/O/C syntax
 - Subject, Verb, Object, Complement
 - Examples:
 - <S>/put/sr_mag_ps_b/on
 - <S>/get/sr_vac_ivg_19_ab3/pressure
 - Unique for object name to identify control equipment
 - <S> = 123_matumot_oprgui_opcon01 (example)
 - from PID, user name, application name and host name
 - Replies are returned from the equipment

MADOC A Messaging

- Based on a text command with S/V/O/C syntax
 - Subject, Verb, Object, Complement
 - Examples:
 - <S>/put/sr_mag_ps_b/on
 - <S>/get/sr_vac_ivg_19_ab3/pressure
 - Unique for object name to identify control equipment
 - <S> = 123_matumot_oprgui_opcon01 (example)
 - from PID, user name, application name and host name
 - Replies are returned from the equipment
 - sr_mag_ps_b/put/<S>/ok
 - sr_vac_ivg_19_abs/get/<S>/1.23E-09Pa


MADOCa Messaging

- Based on a text command with S/V/O/C syntax
 - Subject, Verb, Object, Complement
 - Examples:
 - <S>/put/sr_mag_ps_b/on
 - <S>/get/sr_vac_ivg_19_ab3/pressure
 - Unique for object name to identify control equipment
 - <S> = 123_matumot_oprgui_opcon01 (example)
 - from PID, user name, application name and host name
 - Replies are returned from the equipment
 - sr_mag_ps_b/put/<S>/ok
 - sr_vac_ivg_19_abs/get/<S>/1.23E-09Pa
- Human-readable messages (abstracted)
 - Do not include specific controls on each device

MADOC A Messaging


- Based on a text command with S/V/O/C syntax
 - Subject, Verb, Object, Complement
 - Examples:
 - <S>/put/sr_mag_ps_b/on
 - <S>/get/sr_vac_ivg_19_ab3/pressure
 - Unique for object name to identify control equipment
 - <S> = 123_matumot_oprgui_opcon01 (example)
 - from PID, user name, application name and host name
 - Replies are returned from the equipment
 - sr_mag_ps_b/put/<S>/ok
 - sr_vac_ivg_19_abs/get/<S>/1.23E-09Pa
 - Human-readable messages (abstracted)
 - Do not include specific controls on each device
- These features are essential in our control system

MADOCa Control Framework




MADOCa Control Framework

Shortcomings




MADOCa Control Framework



Shortcomings

- SVOC length \leq 255 characters
 - Not suitable to transmit variable length-data
 - Waveform, Image data


MADOCa Control Framework



Shortcomings

- SVOC length \leq 255 characters
 - Not suitable to transmit variable length-data
 - Waveform, Image data
- Lack of controls on Windows
 - Used only for Linux, Solaris
 - Due to System V IPC, ONC/RPC

MADOCa Control Framework



Shortcomings

- SVOC length \leq 255 characters
 - Not suitable to transmit variable length-data
 - Waveform, Image data
- Lack of controls on Windows
 - Used only for Linux, Solaris
 - Due to System V IPC, ONC/RPC
- Synchronous communication in ONC/RPC
 - Need to wait to finish processing of each message


Next-Generation MADOCA, MADOCA II

- Keep messaging format of MADOCA
- Fix shortcomings in MADOCA

Next-Generation MADOCA, MADOCA II


- Keep messaging format of MADOCA
 - Fix shortcomings in MADOCA
- ✓ Messaging with ZeroMQ/MessagePack
- ✓ Data logging with NoSQL (Cassandra, Redis)
→ Refer M.Kago et al. on TUPPC08
– “Development of a Scalable and Flexible Data Logging System Using NoSQL Databases”

MADOCA




MADOCA

MADOCA II




MADOCA




MADOCA II




MADOCA



MADOCA II




MADOCA




MADOCA II




MADOCA



MADOCA II




MADOCA




MADOCA II




MADOCA



MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II




MADOCA




MADOCA II



MADOCA



MADOCA II





ZeroMQ @ MADOCA II (1)

✓ Messaging with Variable-length data

S/V/O/C

✓ Multi-OS

- Can be used for Linux, Solaris

✓ Multi-languages

- MADOCA II has been written in C++



ZeroMQ @ MADOCA II (1)

✓ Messaging with Variable-length data



✓ Multi-OS

- Can be used for Linux, Solaris

✓ Multi-languages

- MADOCA II has been written in C++



ZeroMQ @ MADOCA II (1)

✓ Messaging with Variable-length data

S/V/O/C



Waveform, Image data etc.
(if required)

✓ Multi-OS

- Can be used for Linux, Solaris

✓ Multi-languages

- MADOCA II has been written in C++



ZeroMQ @ MADOCA II (1)

✓ Messaging with Variable-length data

S/V/O/C



Waveform, Image data etc.
(if required)

✓ Multi-OS

- Can be used for Linux, Solaris

✓ Multi-languages

- MADOCA II has been written in C++



ZeroMQ @ MADOCA II (1)

✓ Messaging with Variable-length data

S/V/O/C



Waveform, Image data etc.
(if required)

✓ Multi-OS

- Can be used for Linux, Solaris and Windows

✓ Multi-languages

- MADOCA II has been written in C++



ZeroMQ @ MADOCA II (1)

✓ Messaging with Variable-length data

S/V/O/C



Waveform, Image data etc.
(if required)

✓ Multi-OS


- Can be used for Linux, Solaris and Windows

✓ Multi-languages

- MADOCA II has been written in C++

Also applied to Python and LabVIEW so far


ZeroMQ @ MADOCA II (2)



✓ Asynchronous communications

- No need to wait to finish processing of each message


ZeroMQ @ MADOCA II (2)



✓ Asynchronous communications

- No need to wait to finish processing of each message
 - Message ID is assigned to each message to handle the relation between sending and reception

ZeroMQ @ MADOCA II (2)



✓ Asynchronous communications

- No need to wait to finish processing of each message
 - Message ID is assigned to each message to handle the relation between sending and reception
- Distributed processing of control messages
 - Multiple Equipment Managers can help

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

✓ Flexible data formats

- Applied to variable-length data, No size limit

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

✓ Flexible data formats

- Applied to variable-length data, No size limit

Array

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

✓ Flexible data formats

- Applied to variable-length data, No size limit

Array [1.23, 4.56, 7.89, ⋯]

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

✓ Flexible data formats

- Applied to variable-length data, No size limit

Array [1.23, 4.56, 7.89, …]

Map

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

✓ Flexible data formats

- Applied to variable-length data, No size limit

Array [1.23, 4.56, 7.89, …]

Map { "image_data_type": "MONO",
"image_data": [1,3,5,…] }

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

✓ Flexible data formats

- Applied to variable-length data, No size limit

Array [1.23, 4.56, 7.89, ⋯]

→ Waveform

Map { "image_data_type": "MONO",
"image_data": [1,3,5,⋯] }

MessagePack @MADOCA II (1)

Used for Serialization of Messaging data

✓ Message exchange among different computing environments

- byte-order procedures are managed

✓ Flexible data formats

- Applied to variable-length data, No size limit

Array [1.23, 4.56, 7.89, ...]

→ Waveform

Map { "image_data_type": "MONO",
"image_data": [1,3,5,...] }

→ Image

MessagePack @MADOCA II (2)

Case for Image:

Key	Data format	Value
image_data_type	string	"MONO", "RGB", "RGBA"
image_width	int32_t	
image_height	int32_t	
image_depth	int32_t	
image_num_type	string	"int32_t", "uint16_t", "uint32_t", "uint64_t", "int16_t", "int32_t", "int64_t", "float", "double"
image_data	defined by [image_num_type]	→Array
image_pixel_order	string	"lefttop", "leftbottom"


MessagePack @MADOCA II (2)

Case for Image:

Key	Data format	Value
image_data_type	string	"MONO", "RGB", "RGBA"
image_width	int32_t	
image_height	int32_t	
image_depth	int32_t	
image_num_type	string	"int32_t", "uint16_t", "uint32_t", "uint64_t", "int16_t", "int32_t", "int64_t", "float", "double"
image_data	defined by [image_num_type]	→Array
image_pixel_order	string	"lefttop", "leftbottom"


Key's can be flexibly added by users

MADOC II Performance (1)




MADOCa II Performance (2)

Solaris
Multi-core
CPU




- “Real-time Process control on Multi-core Processors”
 - MOPPC128 M. Ishii et al.



- RTT < 2ms
 - With binding processes into real-time class
 - Real-time control


MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012



MADOCa II @ BL36XU beamline


Since Sep. 2012



VME for
Insertion
Device

MADOCa II @ BL36XU beamline

Since Sep. 2012




VME for
Insertion
Device


MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS




VME for
Insertion
Device



MADOCa II

BL36XU
Operator
WS

ZeroMQ



MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS

Message
Server

VME for
Insertion
Device

Equipment
Manager



Devices

MADOCa II

GUI
Message
Server 2

BL36XU
Operator
WS

ZeroMQ

Equipment
Manager 2
Equipment
Manager 2


Devices

Devices

Beamline
Front-end
computer

MADOCa II @ BL36XU beamline

Since Sep. 2012



MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS




VME for
Insertion
Device

MADOCa II

BL36XU
Operator
WS


ZeroMQ
↔



MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS




VME for
Insertion
Device

MADOCa II

BL36XU
Operator
WS


ZeroMQ



MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS



VME for
Insertion
Device


Equipment
Manager

Devices

MADOCa II

BL36XU
Operator
WS


ZeroMQ




MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS





VME for
Insertion
Device



MADOCa II

BL36XU
Operator
WS


ZeroMQ
↔




MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS





VME for
Insertion
Device



MADOCa II

BL36XU
Operator
WS


ZeroMQ
↔



MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS



VME for
Insertion
Device


Equipment
Manager

Devices

MADOCa II

BL36XU
Operator
WS

ZeroMQ



Beamline
Front-end
computer


Devices

Devices

MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS




VME for
Insertion
Device



MADOCa II

BL36XU
Operator
WS

ZeroMQ
↔




Beamline
Front-end
computer

MADOCa II @ BL36XU beamline

Since Sep. 2012

Control Room
Operator WS




VME for
Insertion
Device



MADOCa II

BL36XU
Operator
WS


ZeroMQ
↔



Beamline
Front-end
computer


MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II @ BL36XU beamline

Since Sep. 2012



MADOCa II @ BL36XU beamline

Since Sep. 2012




MADOCa II Applications

- “MADOCa II Interface with LabVIEW”
 - MOPPC129 Y. Furukawa et al.
 - Applied to Beam Position Monitor (BPM)
 - Waveform, 20k points/sec
 - Running on Windows
 - LabVIEW protocol for MADOCa II



Applied since Sep. 2013




MADOCA II Applications

- “MADOCA II Interface with LabVIEW”
 - MOPPC129 Y. Furukawa et al.
 - Applied to Beam Position Monitor (BPM)
 - Waveform, 20k points/sec
 - Running on Windows
 - LabVIEW protocol for MADOCA II



Applied since Sep. 2013



MADOCa II Applications


- “MADOCa II Interface with LabVIEW”
 - MOPPC129 Y. Furukawa et al.
 - Applied to Beam Position Monitor (BPM)
 - Waveform, 20k points/sec
 - Running on Windows
 - LabVIEW protocol for MADOCa II



- “Development of MicroTCA-based Image Processing System at SPring-8”
 - TUPPC088 A. Kiyomichi et al.



Applied since Sep. 2013



MADOCa II Applications



- “MADOCa II Interface with LabVIEW”
 - MOPPC129 Y. Furukawa et al.
 - Applied to Beam Position Monitor (BPM)
 - Waveform, 20k points/sec
 - Running on Windows
 - LabVIEW protocol for MADOCa II



- “Development of MicroTCA-based Image Processing System at SPring-8”
 - TUPPC088 A. Kiyomichi et al.



Applied since Sep. 2013



MADOCa II Applications

- “MADOCa II Interface with LabVIEW”
 - MOPPC129 Y. Furukawa et al.
 - Applied to Beam Position Monitor (BPM)
 - Waveform, 20k points/sec
 - Running on Windows
 - LabVIEW protocol for MADOCa II





- “Development of MicroTCA-based Image Processing System at SPring-8”

- TUPPC088 A. Kiyomichi et al.
 - Applied to two-dimensional synchrotron interferometer
 - Image data (VGA), up to 10 Hz



Applied since Sep. 2013



Summary

- New control framework, MADOCA II has been developed
 - Shortcomings in MADOCA are fixed
 - Flexibilities in the Messaging using ZeroMQ/MessagePack
 - Messaging with variable-length data
 - Asynchronous communications
 - Controls on Linux, Solaris and Windows
- Control systems with MADOCA II are implemented
 - Stabilities → confirmed in BL36XU beamline since Sep. 2012
 - BPM and two-dimensional interferometers
 - SACL A experimental station controls  Since Sep. 2013
- Next step: utilize MADOCA II for various applications
 - Upgrade & Replacement of SPring-8 control systems
 - Apply MADOCA II into other facilities