

COMPARISON BETWEEN MEASURED AND COMPUTED TEMPERATURES OF THE INTERNAL HIGH ENERGY BEAM DUMP IN THE CERN SPS



G. Steele, F. Pasdeloup.

R. Folch, V. Kain, I.V.Leitao, C. Maglioni, R. Losito, A. Perillo-Marccone, F. Velotti.

Contents


- Introduction and background
- Motivation for studies
- Energy deposition simulations
- Thermo-mechanical simulations
- Results
- Data-simulation comparison
- Conclusions and outlook

Introduction and background

Introduction to the SPS

- CERN's 2nd largest accelerator
- Switched on in 1976
- Serves as final link in injector chain for the LHC
- Simultaneously provides beams for other fixed target experiments

CERN's Accelerator Complex



LHC Large Hadron Collider SPS Super Proton Synchrotron PS Proton Synchrotron

AD Antiproton Decelerator CTF3 Clic Test Facility AWAKE Advanced WAKEfield Experiment ISOLDE Isotope Separator OnLine DEvice


LEIR Low Energy Ion Ring LINAC LINear ACcelerator n-ToF Neutrons Time Of Flight HiRadMat High-Radiation to Materials

Introduction to the TIDVG

- Target Internal Dump Vertical Graphite (TIDVG)
- High energy dump for the SPS (102.2 to 450 GeV beams)
- Located in LSS1 of the SPS
- Must withstand all beams produced by the SPS e.g. LHC injection beams and fixed target experiment beams
- Combination of the waveforms from 2 vertical kickers and 3 horizontal sweepers spreads a dumped beam over a relatively large area on front face of dump
- 3 devices all based on same design:
 - TIDVG1: installed from 2000 until 2004
 - TIDVG2: installed from 2006 until 2013
 - TIDVG3: installed in 2014

TIDVG composition

- Absorbing core (TIDVG3 in brackets):
 - 2.5 (2.7)m graphite
 - 1.0 (0.8)m aluminium
 - 0.5m copper
 - 0.3m tungsten
- Copper jacket containing water-filled cooling pipes.
- Water cooled iron yoke.



Motivation for studies


Damage sustained

- An endoscopy performed on TIDVG2 showed significant damage to the aluminium section



Response to damage


- Replacement of damaged device with TIDVG3 core (reuse of iron yoke)
- Installation of new temperature sensors
- Develop an improved thermo-mechanical model.
- Post-mortem analysis of when and how damage occurred (see “*Origin of the Damage to the Internal High Energy Beam Dump in the CERN SPS*” V. Kain et al.)
- Set limits on future operation to prevent damage to TIDVG3



Energy deposition studies





Energy deposition simulations

- FLUKA software used to produce energy density maps for different beam impacts.
- Detailed 3D model of TIDVG3 created
- 4 different beams considered - taken as being representative for immediate future running
- Beam particle density maps from tracking simulations used as input.




Input for simulations

Name	Energy [GeV]	Bunch intensity	Number of bunches	Total intensity
LHC 25ns	450.0	1.2e11	288	3.456e13
LHC 50ns	450.0	1.2e11	144	1.728e13
Doublet	450.0	1.6e11	144	2.304e13
Fixed target	400.0	9.52e9	4200	3.9984e13



Peak energy deposition

- Difference between LHC 25 and 50 ns beams due solely to different total intensity.
- Higher proton density of doublet beam on front face means it is most severe initially.
- Further along the device doublet beam also scales w.r.t. total intensity.
- Even though fixed target has the greatest total intensity, the significantly larger sweep is the dominating variable along entire length.




Thermo-mechanical simulations

Initial setup

- FLUKA results used as input for ANSYS simulations
- Focus predominantly on absorbing core and copper jacket
- Affect of thermal radiation discounted after investigation
- Since absorbing blocks do not have any direct cooling the Thermal Contact Conductance (TCC) is a key parameter for simulations and difficult to define precisely.
- Ideally a strongly coupled model (thermal-structural) would be used - not feasible.

TCC

- Calculated using the Mikic or Marotta model depending on materials at boundary
- Only the lower faces of the absorbing blocks are in contact with the copper jacket.
- TIDVG design includes two springs to exert a downward force on the absorbing blocks increasing contact pressure and thus TCC
- Observation of removed Al section showed spring imprints in material.
- This led to a revised estimate of the load now ~50% of the design value.



Heat exchange surface

- Investigations of TCC and heat exchange surface showed that an increased TCC did not compensate for a reduced heat exchange surface.
- Further investigations studied pressure profiles due to beam induced heating to ensure the smallest area was taken for simulations

Material properties

- All devices undergo a bakeout procedure (250°C for 350 hours)
- Leads to the 'aging' of the aluminium which corresponds to a reduction in strength
- Max temp during operation set to be 250°C to prevent further degradation

Simulations performed


- Repeated dumping of all 4 beam types with timings as shown in table
- 5th scenario intended to reflect an SPS supercycle:
 - 1 pulse of LHC 25ns
 - 15 seconds of cooling time
 - 1 pulse of 5% of fixed target
 - 20 seconds of cooling time
 - repeat to achieve steady state
 - after LHC 25ns pulse 6 seconds of cooling
 - 1 pulse of 100% of fixed target

Name	Bunch spacing [s]	Pulse duration [s]	Pulse period [s]
LHC 25 ns	25.0e-9	7.2e-6	21.6
LHC 50 ns	50.0e-9	7.2e-6	43.2
Doublet	25.0e-9	3.6e-6	43.2
Fixed target	5.0e-9	21.0e-6	14.4

Results


LHC type beams

- LHC 25ns beam reaches AI temperature limit after 25 shots.
- Requires 30 minutes of cooling to return to start temperature
- Addition of 15 seconds of cooling between shots gives steady state below temperature limit
- LHC 50 ns and doublet beams achieve steady state (at 121 and 164°C respectively) without any additional cooling time.




Fixed target beams

- Worst case 3 series of 3 pulses rather than continuous dumping separated by 40 seconds cooling time
- Steady state not achieved but peak temp is 205°C
- Time taken to return to initial temperature around 24 minutes



5th scenario

- Steady state achieved at just under 250°C
- Since peak temp is just for short time - still acceptable.
- After full shot of fixed target beam need to return to 179°C to recommence steady state running.
- Return to acceptable level takes 70 seconds





Data-simulation comparisons

Data collected

- Restart of the SPS allowed for the collection of new temperature data.
- Data set for the time being restricted to low intensity beams
- Can still be compared to simulations performed using all latest assumptions for the equivalent scenario.

Temperature comparisons

- Good agreement for total power transfer as shown by water pipe measurements.
- Also good agreement in iron yoke
- Observable difference for temperature in copper jacket around Al section.
- This indicates a lower TCC than anticipated, implying the possibility of higher temperatures in the Al section
- Possible explanation due to non flatness of copper jacket surfaces
- To be verified with higher intensity beams and if necessary re-set limits



Conclusions and outlook

Thermo-mechanical model

- Simulation model has been carefully re-considered
- As far as possible assumptions have been investigated to ensure they are conservative
- Further data analysis will reveal if the assumptions have to be reconsidered

TIDVG device and operation

- Aim of the study was to provide safe operation limits for TIDVG3
- Limits need to be verified, monitored and, if necessary, adjusted with further data taking
- Long term, the current internal dump design becomes increasingly unsuitable.
- HL-LHC will require a new device

Questions?