


HEAVY ION LINAC BOOSTER AT IUAC, NEW DELHI


Amit Roy

Inter University Accelerator Centre,
New Delhi - 110 067, India



2 Oct 2008


Schematic of 15UD Pelletron and Linac Booster




The Accelerator system of IUAC

- Equipped with a Electrostatic Accelerator (Pelletron)
 - Deliver dc (continuous) beam or bunched beam
 - Beam species cover almost the whole periodic table
 - Energy from few tens to few hundred of MeV
 - Beam is utilized to do research in Nucl. Phys, Material science, Biophysics, Atomic Physics etc.

➤ But there is always a demand for more energy



2 Oct 2008



Cryostat dimension:

Length = 2.3 m

Height = 1.3 m

Width = 1.1 m

Eight resonators and solenoid in Linac cryostat # 1

2 Oct 2008



Indigenously built niobium quarter wave resonator with slow tuner bellows at IUAC.



Central conductor
and niobium housing

Resonant Frequency	97MHz
Synchronous velocity	0.08c
Drift tube Voltage	85kV
Energy Content	110 mJ
Peak Magnetic field	106 G
Peak Electric field	3.9MV/m
Geometric factor	17.3
Active length	15.9 cm


2 Oct 2008





**Parts of Nb QWR for
modules 2 & 3**




2 Oct 2008





2 Oct 2008




Modified Slow Tuner with ss bellows

2 Oct 2008





New drive




Old drive

2 Oct 2008



2 Oct 2008




Edge welded bellows



Formed bellows



2 Oct 2008



Rebuncher cryostat with two QWRs

2 Oct 2008

Ion Acceleration through Linac


- Typically, a pulsed beam of ~ 1.5 ns is injected into superbuncher (SB)
- SB typically compresses it to a couple of hundred pico second at the entrance of Linac
- In a recent experiment, 130 MeV $^{28}\text{Si}^{+10}$ beam was injected into Linac having 7 QWR installed at that time
- A final energy of ~ 159 MeV was obtained at the exit of Linac and resonator at rebuncher cryostat compresses the blown up beam to ~ 400 ps at the user's scattering chamber
- 159 MeV $^{28}\text{Si}^{+10}$ beam with a time width of 400 ps was delivered for conducting experiment




2 Oct 2008





Field Gradient @ 6 Watt



2 Oct 2008



2 Oct 2008



2 Oct 2008



Fabrication of Superconducting resonator



- 60 kV, 15 kW,
CNC controlled EBW Machine
- Commissioned in 2001



- Max Temp. 1200 C
@ 5.0×10^{-7} torr
- Hot Zone – $\phi 600\text{mm} \times 1000\text{mm}$
- Commissioned in 2002

2 Oct 2008



Acid Fume Hood



High pressure rinsing



Test Cryostat and top plate with QWR mounted

2 Oct 2008

New Projects


**Niobium Single Spoke Resonator, $\beta=0.22$, $f=325$ MHz
Fermilab – IUAC collaboration**

Design of a low beta cavity ($\beta = 0.05$) for high current injector.




2 Oct 2008





Schematic of the proposed high current injector

2 Oct 2008




PKDELIS ECR source and low energy beam transport


2 Oct 2008



**General Assembly of the 1.17m
modulated RFQ,**

**$A/q = 7$, $E_{in} = 8\text{keV/u}$,
 $E_{out} = 180\text{ keV/u}$**






2 Oct 2008



DTL Prototype Stems



2 Oct 2008

Present Status

- **Linac requires $(1+24+2 =) 27$ QWR**
- **13 QWRs were built in collaboration with Argonne National Lab.**
- **Remaining resonators are being fabricated in-house**
- **The first module of Linac (with 8 QWR) is functioning with Superbuncher (1 QWR) and Rebuncher (2 QWRs)**
- **Linac cryostat # 2 and 3 will be operational in mid- 2009**
- **HTc ECR source operational.**
- **RFQ prototype fabricated. DTL being designed.**

2 Oct 2008

