

SUPERCONDUCTING QUARTER-WAVE RESONATOR CAVITY AND CRYOMODULE DEVELOPMENT FOR A HEAVY ION RE-ACCELERATOR



W. Hartung, J. Bierwagen, S. Bricker, C. Compton,
J. DeLauter, P. Glennon, M. Hodek, M. Johnson, F. Marti,
P. Miller, D. Norton, J. Popielarski, L. Popielarski,
D. Sanderson, J. Wlodarczak, R. York;
A. Facco (INFN-Legnaro); E. Zaplatin (FZ Jülich)

National Superconducting Cyclotron Laboratory
Michigan State University



Poster THP033

XXIV Linear Accelerator Conference


29 September to 3 October 2008, Victoria, BC



$\beta = 0.041$ QWR



$\beta = 0.041$ QWR



$\beta = 0.085$ QWR



Prototype $\beta = 0.041$ QWR



Parts



Tuning Plate



Inside




Etching



Rinsing




Insert



Dewar Test of $\beta = 0.041$ QWR

Stiffening of $\beta = 0.041$ QWR



ANSYS



IC plate



welded plate



top ring




buttress




welded buttress

ANSYS model: predicted deformation for stiffened QWR with He vessel.



Prototype low- β cryomodule



(a) cold mass



(c) inner MLI



(e) outer MLI



(b) top plate




(d) 77 K shield




(f) vacuum vessel

Construction of low- β cryomodule

RF Testing of $\beta = 0.085$ QWR



Test in Dewar vs test in cryomodule (after magnet operation, temperature cycle, and He processing; preliminary analysis)



$\beta = 0.085$ cryomodule for the reaccelerator

Conclusion

- ▶ Prototype cavities for the NSCL reaccelerator have been fabricated and tested.
- ▶ The design goals for the RF performance have been achieved in Dewar tests (both cavity types) and cryomodule test (one cavity type so far).
- ▶ In progress: production cavities and cryomodules for the NSCL reaccelerator.