



Cornell University

First Results for the Cornell ERL Injector

Bruce Dunham, for the ERL Team

Cornell University

Laboratory for Elementary-Particle Physics

Ithaca, NY USA



Cornell University

ERL Team

- Ivan Bazarov
- S. Belomestnykh
- M. Billing
- E. Chojnacki
- Z. Conway
- J. Dobbins
- R. Ehrlich
- M. Forster
- S. Gruner
- G. Hoffstaetter
- V. Kostroun
- M. Liepe
- Y. Li
- X. Liu
- D. Ouzounov
- H. Padamsee
- D. Rice
- V. Shemelin
- C. Sinclair
- E. Smith
- K. Smolenski
- S. Temnykh
- M. Tigner
- V. Veshcherevich
- T. Wilksen

Oct 1, 2008


B. Dunham



- **An ERL at Cornell**
- **The ERL Injector Prototype Project**
 - Overview
 - DC Photoemission Gun/Laser
 - Superconducting RF
 - Beam Diagnostics
- **Results and Prospects**



2110907-001c





- 1. Injector
- 2. Linac 1
- 3. 2.5 GeV turnaround
- 4. Linac 2
- 5. X-ray beam-lines
- 6. 5 GeV turnaround
- 7. X-ray beam-lines
- 8. Beam dump

Oct 1, 2008

B. Dunham



- **Phase I:** Build, test injector, LINAC modules; resolve machine issues. Engineering studies for Phase II (in process; \$30M NSF & NY State)
- **Phase II:** Build a high energy (5 GeV) ERL x-ray facility at Cornell as an upgrade to CESR. (5 year construction, no funding yet)



Parameters:

- 100 mA avg current (5 MeV)
- 33 mA avg current (15 MeV)
- 77 pC / bunch at 1.3 GHz
- < 2 μm emittance
- < 2-3 ps bunch length

Demonstrate:

- Cathode longevity
- Low emittance
- RF controls
- Parameter sensitivity
- reliability





Cornell University

The Photoemission DC Electron Gun

Oct 1, 2008


B. Dunham



Basic design has been used in GaAs polarized electron sources for decades (@ 100 kV).

Oct 1, 2008

B. Dunham




GaAs is still our cathode of choice . . .

- good quantum efficiency (QE)
- low thermal emittance (cold)
- fast time response (@520 nm)

But . . .


- need extreme UHV ($< 1 \times 10^{-11}$ Torr)
- limited lifetime
- minimum thermal emittance near bandgap (where the QE is lowest)
- thermal emittance degrades at higher QE

. . . We are willing to try other cathodes



Manufactured by CPI, Beverly, MA

- Large size to keep field gradients low
- Field emitted electrons can build up on the insulator and punch thru
- External SF₆
- High mechanical stresses due to SF₆ pressure and bakeouts
- Difficult to find suppliers
- Braze difficulties due to large size



Maximum voltage so far 440kV. Operating at 250-300 kV now until a spare is obtained



Cornell University

750 kV HV power supply




750 kV, 100 mA supply
Kaiser Systems, Beverly, MA

Oct 1, 2008




Custom floating ammeter to measure
field emission current during processing




Gun and HVPS inside a high
pressure SF₆ vessel

B. Dunham



For a 10% QE cathode, one needs ~2 Watts to reach 100 mA





We use an 'optical pulse-stretcher' to get 20-40 ps flat-top pulses from a 2 ps laser (DPA – divided pulse amplifier)



Gauss to flat top transformation using a commercial aspheric lens (Newport Corp)


Measured longitudinal laser profile



Measured longitudinal electron beam profile



Beamline for characterizing the phase space from the gun



Oct 1, 2008

B. Dunham



Cornell University


Emittance data at 250kV, 80 pC

$\epsilon = 1.8 \mu\text{m}$


data

5mm


10mrad



Parmela3D



GPT



3.4A

→ SOL1 →

3.8A





Cornell University

The RF and Superconducting RF Systems

Oct 1, 2008


B. Dunham



- **High RF power transfer to beam for acceleration of high current beam \Rightarrow input coupler challenge: $1 \text{ MeV per cavity} * 0.1 \text{ A} = 100 \text{ kW}$**
- **High beam loading needs to be compensated very accurately for injectors \Rightarrow RF control challenge.**
- **Emittance preservation \Leftrightarrow reduce beam-cavity interaction effects, small transverse kick fields, high RF field stability.**
- **Strong damping of HOMs (monopole, dipole and quadrupole) is essential for emittance preservation and to reduce monopole HOM power.**
- **CW cavity operation at higher fields \Rightarrow cryogenic power \Rightarrow cryostat design challenge.**




- five 2-cell cavities
- symmetric beam line
- 2 opposing 50 kW input couplers per cavity
- six beam line HOM loads for aggressive HOM damping



Manufactured by CPI,
Beverly, MA
Oct 1, 2008



HOM absorber
Manufactured by Cornell,
Accel




Vertical test data

cavity frequency	1300 MHz
cells per cavity	2
R/Q per cavity	222 Ω
acc. voltage per cavity	1 to 3 MV
acc. gradient	4.6 to 13.8 MV/m
Q₀	> 1·10¹⁰
Q_{ext}	> 4.6·10⁴ to 4.1·10⁵
active cavity length	0.218 m
total cavity length	0.536 m



Cornell University

SRF and RF installation



Cryomodule installed at the ERL injector



Cavity string before installation into cryomodule



Klystron gallery

Oct 1, 2008

B. Dunham



Cavity	CW	Limit	Pulsed	Limit
1	2.8 MV	Cryogenics	4.35 MV	IC
2	2.9 MV	IC	3.75 MV	IC
3	3.5 MV	Cryogenics	3.66 MV	IC
4	3.4 MV	Cryogenics	4.15 MV	Quench
5	3.5 MV	none	5.20 MV	IC
All 5	2.4 MV/12 MV total	Cryogenics		

IC - input coupler vacuum




Cornell University

Beam Diagnostics and Beam Dump

Oct 1, 2008

B. Dunham



A-line: Full phase space characterization

emittance measurement slits (EMS), bpm's, flying wire, deflection cavity, energy spread, viewers

B-line: Merger studies (low average power)

emittance measurement slits, bpm's, viewers

C-line: phase and energy spread/stability, bunch length

THz interferometer, flying wire, bpm's, viewers




Cornell University

Beam Dump

Beam Dump undergoing e-beam welding, manufactured by Metalex, Inc. Due to ship this week



Up to 500 kW average power in the beam for the Phase 1 injector, probably need 1.5 MW for the final ERL design



Before reaching the dump, the 1 mm dia, 500 kW beam is expanded and rastered to reduce the instantaneous power load. Aluminum is used to minimize neutron production

Oct 1, 2008

B. Dunham



- All construction (except for dump and final shielding) is complete
- RF and SRF commissioning nearly complete
- Diagnostics commissioning is underway
- Beam through all beamlines, 5 MeV, 50 uA max
- All components ready for 100 mA
- Phase space measurements to begin soon



Cornell University

Acknowledgements

This work is supported by NSF PHY-0131508



Industrial Partners:

Communication and Power Industries (CPI) - DC Gun and RF couplers

e2V - 100 kW klystrons

Accel - HOM loads

Kaiser Systems - 750 kV power supply

Metalex - 500 kW beam dump

Myer Tool - Cryomodule

Pritel - Laser oscillator

Oct 1, 2008

B. Dunham



Cornell University

ERL'09



ENERGY RECOVERY LINAC WORKSHOP

ON THE BEAUTIFUL CORNELL UNIVERSITY CAMPUS, ITHACA, NY USA

JUNE 08-12, 2009



Organizing committee:

Ilan Ben-Zvi, BNL
Bruce Dunham, Cornell
Rodney Gerig, ANL
Ryoichi Hajima, JAEA
Georg Hoffstaetter, Cornell (chair)
Geoffrey Kraftt, TJAF
Mike Poole, ASTEC

Cornell organizing committee:

B.J. Boritz
Devin Bougie
Georg Hoffstaetter (chair)
Karl Smolenski
Monica Wesley

PROMISE FOR A BRIGHTER FUTURE


www.lepp.cornell.edu/Events/ERL09/

The next ERL workshop is in Ithaca, NY



Design features:

- ❑ Design derived from the TTF-III coupler
- ❑ The cold part was completely redesigned using a 62 mm, 60 Ohm coaxial line for stronger coupling, better power handling and avoiding multipacting
- ❑ Antenna tip was enlarged and shaped for stronger coupling
- ❑ “Cold” window was enlarged to the size of “warm” window
- ❑ Outer conductor bellows design was improved for better cooling (added heat intercepts)
- ❑ Air cooling of the warm inner conductor bellows was added





Manufactured by CPI,
Beverly, MA




Total # loads	3 @ 78mm + 3 @ 106mm
Power per load	26 W (200 W max)
HOM frequency range	1.4 – 100 GHz
Operating temperature	80 K
Coolant	He Gas
RF absorbing tiles	TT2, Co2Z, Ceralloy

2 proto-types fabricated at Cornell
6 production loads fab'ed by ACCEL



Oct 1, 2008

B. Dunham





- Beam position resolution: $10\ \mu\text{m}$ (spec)
- Energy spread resolution: 10^{-4}
- Transverse beam profile resolution: $30\ \mu\text{m}$ (viewscreens)
 $10\ \mu\text{m}$ (slits)
 $30\ \mu\text{m}$ (flying wire)
- Angular spread resolution: $10\ \mu\text{rad}$
- Pulse length (deflecting cavity&slits): $100\ \text{fs}$
- RF phase angle: 0.5°

Ability to take phase space snapshots of the beam, both transverse planes, and longitudinal phase space