S1-GLOBAL Collaborative Efforts 8-Cavity-Cryomodule: 2 FNAL, 2 DESY and 4 KEK

N. Ohuchi, M. Akemoto, E. Kako, H. Katagiri, Y. Kondo, S. Fukuda, H. Hayano, N. Higashi, T. Matsumoto, H. Matsushita, S. Michizono, T. Miura, H. Nakai, H. Nakajima, S. Noguchi, M. Satoh, T. Shidara, T. Shishido, T. Takenaka, A. Terashima, N. Toge, K. Tsuchiya, K. Watanabe, S. Yamaguchi, A. Yamamoto, Y. Yamamoto, K. Yokoya, M. Yoshida,

KEK, Tsukuba, Japan

C. Pagani, P. Pierini, A. Bosotti, R. Paparella, INFN, Milano, Italy

T. Arkan, S. Barbanotti, H. Carter, M. Champion, B. Kephart, J. Kerby, D. Mitchell, Y. Orlov, M. Ross, T. J. Peterson, FNAL, Chicago, U.S.A

D. Kostin, L. Lilje, A. Matheisen, W. -D. Moeller, N. Walker, H. Weise, DESY, Hamburg ,Germany C. Adolphsen, SLAC, Stanford, U.S.A

2010 Sept, 13

İİL

Global Design Effort

1



- 1. Introduction
- 2. S1-Global Cryomodule
- 3. Construction of S1-Global Cryomodule
- 4. Cold Test
- 5. Summary


Introduction

Basic design of the ILC cryomodule:

- ILC main linac consists of 1815 cryomdules
 - 9 cavities in the 11830 mm cryomodule
 - 8 cavities and 1 quadrupole package in the module center
- Design accelerating gradient of cavities = 31.5 MV/m

As the R&D of ILC Main Linac in the GDE activities:

- 1. High gradient test of 9-cell cavity \rightarrow S0
- 2. Cryomodule test (cavity-string) \rightarrow S1
- 3. Beam test by an accelerator unit (Cryomodule string) \rightarrow S2



IIL

ilc...


The main target of the S1-Global:

- Operating a cryomodule with an average accelerating gradient of 31.5 MV/m
- Construction of the cryomodule under the international research collaboration

S1-Global International Collaborative Framework


- INFN: Design and construction Module-C and production of the blade tuners for the FNAL cavities.
- FNAL: Two TESLA type cavities, power coupler and integration of the INFN blade tuners in the cavity packages.
- DESY: Two TESLA type cavities, including Saclay-type tuners, and power couplers.
- SLAC: Power distribution system for Module-C, and aging of FNAL couplers.
- KEK: Four TESLA-like cavities, with two types of tuner design, Module-A for KEK cavities, power distribution for Module-A, and infrastructure for tests.

S1-Global Cryomodule Overview



2010 Sept, 13

S1-G Cryomodule Schedule




a SC ML Tech. Mtg. at FNAL

2010 Sept, 13

İİL


Design of S1-G Cryomodule




Features of S1-G cryomodule

- 1. The total length of the S1-G modules including end cans was designed to be 14.9 m.
- 2. The mechanical and thermal designs of the 6-m cryomodules were based on the design of the DESY TTF-III cryomodule.
- **3.** S1-G cryomodule consists of two 6-m cryomodules:
 - DESY/FNAL cavities in Module-C
 - KEK cavities in Module-A
- 4. Four different types of cavity package:
 - FNAL: Tesla type cavity, Blade tuner, outer magnetic shield, L=1247.4 mm
 - DESY: Tesla type cavity, Saclay tuner, outer magnetic shield, L=1283.4 mm
 - KEK: Tesla like cavity, Slide jack tuner, inner magnetic shield, L=1247.6 mm

Four types of cavities for S1-G Cryomodule




TESLA cavity / Saclay tuner (DESY) Cavity Length = 1283.4 mm





TESLA cavity / Blade tuner (FNAL) Cavity Length = 1247.4 mm





KEK cavity / Slide Jack tuner Cavity Length =1247.6 mm

Global Design Effort

İİL

Cavity Performance





2010 Sept, 13

116

Construction of S1-Global Cryomodule (1)

Construction of Module-C components by INFN/Italy





2009, July






2010 Sept, 13

Construction of S1-Global Cryomodule (2)

Vacuum vessel and cold components from INFN/Italy



Two cavities from DESY/Germany




Construction of S1-Global Cryomodule (3)

Assembly of DESY/FNAL four cavities







Tuner assembly by INFN/FNAL

2010, January

Global Design Effort


2010 Sept, 13

Construction of S1-Global Cryomodule (4)

Assembly of four KEK cavities









2010 Sept, 13

Construction of S1-Global Cryomodule (5)

Assembly of cold mass









2010, April

2010, March

2010 Sept, 13

Construction of S1-Global Cryomodule (6)

Assembly of DESY/FNAL/KEK warm couplers




DESY/FNAL warm couplers






2010, May

Cold Test of S1-G Cryomodule






2010 Sept, 13

ΪĹ



Single pulse response (Cryo-A) by Piezo tuner



ΪĻ


The second cold test term: 15 weeks from Sept. to Dec.

- Static heat loss measurements at 4K and 2K
- High gradient test (individual cavities)
- Lorentz detuning measurements and compensation
- Dynamic heat load measurements at single cavity, four cavities and eight cavities
- LLRF

• Distributed RF system (DRFS) test

At the end of December, the cold tests of S1-Global cryomodule will be completed.

Ready for High Power Test, Now



Summary

- As the leading project of ILC, the S1-Global cryomodule was successfully constructed on schedule under the international research collaboration of INFN, DESY, FNAL, SLAC and KEK.
- In the 1st cold test, the S1-G cryomodule was cooled down to 2 K, and all functions were confirmed.
- The S1-G cryomodule has started to be cooled down again, and the cold tests will be continued until the end of this year.



Thank you for your attention. Thanks to S1-Global cryomodule team.