

Development of H-Mode Cavities for the FAIR Project

LINAC 2012

Tel Aviv, Israel

10th September 2012



G.Clemente, W. Barth, L. Groening, S. Mickat, B.Schlitt, W.Vinzenz

GSI, Darmstadt

U.Ratzinger, R. Brodhage, H. Podlech, F. Dziuba, R.Tiede, M.Bush

IAP, Goethe University, Frankfurt am Main

Outline


- **H-Mode Cavities**

- TE modes
- Physical Properties
- Beam Dynamics
- Shunt Impedance Charts

- **Linac Upgrade @ GSI for FAIR**

- Proton LINAC
- High Energy LINAC
- Super Heavy Element cw LINAC

From Pillbox to IH-Mode DTL




TE₁₁ Mode in a pillbox

H-Field Parallel to beam Axis

No E-Field component for acceleration

Insertion of stem and drift tube



Perpendicular to the axis



Axial component of E-Field generated !

Acceleration possible!




From Pillbox to CH-Mode DTL



Pillbox excited on TE₂₁ Mode

Suited for higher frequency

Superconducting option possible





H-Mode DTL: RF Properties

The acceleration structure strongly modifies the E field distribution

Very High capacitive load

Capacitive Load: H-Mode vs E-Mode DTL




Capacitive Load and electric field concentrated mainly on the beam axis

H-Mode DTL profits significantly by a slim tube geometry


Beam Dynamics

- Separated function beam dynamics



KONUS




APF



EQUUS



- Periodic Beam Dynamics with Slim Permanent Magnet




Proposed as replacement for the LANSCE Linac

Extremely tight tolerances

T = 200 T/m !

Reduced beam aperture


Shunt Impedance Chart



IH-DTL Established as standard solution for Heavy Ion

CH-DTL Valid alternative to DTL for Proton Linac up to 100 AMeV

THE FAIR P-LINAC



Beam Energy (MeV)	70
Beam Current (mA)	35 - 70
Beam Pulse (μs)	36
Repetition Rate (Hz)	4
Frequency (MHz)	325.224
Norm. Emittance at output (μm)	2.1 / <u>4.2</u>
Momentum Spread	$\leq \pm 10^{-3}$
Beam Loading (peak) (MW)	4.9
RF Power (peak) (MW)	2.2
Klystron (3 MW Peak Power)	7
Solid State Amplifier (50 kW)	3
Total Length (RFQ + CH)	≈ 27 m

DTL Section consists in

- 3 Coupled CH DTL
- 3 Standard CH-DTL

Cavity	Energy (MeV)	Gaps	L (m)
1	3 - 12	22	1.7
2	12 - 24	27	2.7
3	24 - 37	32	4
4	37 - 48	20	2.9
5	48 - 59	21	3.1
6	59 - 70	21	3.4





Related poster: THPB034 L. Groening

The Coupled CH-DTL

At lower β



- KONUS requires shorter focusing period
- Very high Shunt impedance
- Commercial 3 MW Klystron available

Coupled structure at low beta !






FAIR Prototype

Gap	27 (13+14)
Energy Range	11.7-24.3 MeV
β	0.15-0.22
Q_0	15300
Length (m)	2.7
ZT^2	60
RF Losses	1.37
Beam Loading	882 kW (at 70 mA, required 35)
Total Power	1.810 - 2.25 MW (2.7 Available)



FAIR Prototype


- Cavity tuned at : **325.16** against **325.224 MHz** of operation
 - $\epsilon_{\text{air}}=1.005 \propto \epsilon^{1/2}$
 - Beam dynamics verified with measured voltages



FAIR Prototype




Status

- Stainless Steel Stems ready!
- Stainless Steel Drift Tubes in production
- Copper plating performed in late 2012/ early 2013
- 3 MW Klystron delivered. Power Supply is expected for end 2012
- New GSI Test Bench ready for full power RF Test




FAIR PLINAC

Beam Dynamics, Brilliance analysis




UNILAC

Universal Linear Accelerator




UNILAC

Universal Linear Accelerator



UNILAC

Universal Linear Accelerator



4-Rod IH-RFQ

2.2 – 120 keV/u


Built in 1999

$A/q \leq 65$ (U^{4+})

I (mA) = $0.25 A/q$

UNILAC

Universal Linear Accelerator



4-Rod IH-RFQ

2.2 – 120 keV/u


Built in 1999

$A/q \leq 65$ (U^{4+})

I (mA) = $0.25 A/q$

UNILAC

Universal Linear Accelerator



4-Rod IH-RFQ

2.2 – 120 keV/u


Built in 1999

$A/q \leq 65$ (U^{4+})

I (mA) = $0.25 A/q$

UNILAC

Universal Linear Accelerator



IH 1 & IH 2


120–743 keV/u -1.4 MeV/u

Built in 1999

$I \text{ (mA)} = 0.25 A/q$

UNILAC

Universal Linear Accelerator



5 Alvarez Type DTL

1.4 – 11.4 MeV/u

Built in 1975


178 DC Quadrupole

$A/q \leq 8.5$ (U^{28+})

Present Linac Limitations


- 40 years at high duty factor (25 %)

- Massive Sparkovers
- Beam induced surface defects
- Vacuum leaks



- DC Quadrupoles

- Limited flexibility for multi-beam operation
- Ground faults of the coils
- Heat dissipation problematic




- FAIR Requirements (High Intensity, low duty factor)

- Too high for protons
- Challenging for heavy ion
- Not compatible with SHE program

Massive injector upgrade required !

UNILAC Upgrade

Present UNILAC




UNILAC Upgrade

FAIR High Energy LINAC




UNILAC Upgrade

FAIR High Energy LINAC



UNILAC Upgrade

FAIR High Energy LINAC




STEP 1

- New HV Terminal and LEBT to achieve 20 mA for U^{28+} after the stripper

UNILAC Upgrade

FAIR High Energy LINAC



STEP 1


- New HV Terminal and LEBT to achieve 20 mA for U^{28+} after the stripper

STEP 2

- Replacement of the 90 MV DTL with 6 IH-DTL to 11.4 AMeV

UNILAC Upgrade

PAER High Energy LINAC



STEP 1


- New HV Terminal and LEBT to achieve 20 mA for U^{28+} after the stripper

STEP 2

- Replacement of the 90 MV DTL with 6 IH-DTL to 11.4 AMeV

UNILAC Upgrade

FAIR High Energy LINAC



STEP 1

- New HV Terminal and LEBT to achieve 20 mA for U^{28+} after the stripper

STEP 2


- Replacement of the 90 MV DTL with 6 IH-DTL to 11.4 AMeV

Optional

- Enough free space in tunnel for future energy upgrade

UNILAC Upgrade

FAIR High Energy LINAC



STEP 1

- New HV Terminal and LEBT to achieve 20 mA for U^{28+} after the stripper

STEP 2


- Replacement of the 90 MV DTL with 6 IH-DTL to 11.4 AMeV

Optional

- Enough free space in tunnel for future energy upgrade

UNILAC Upgrade

FAIR High Energy LINAC



STEP 1

- New HV Terminal and LEBT to achieve 20 mA for U^{28+} after the stripper

STEP 2

- Replacement of the 90 MV DTL with 6 IH-DTL to 11.4 AMeV

Optional



- Enough free space in tunnel for future energy upgrade

Design machine for Low Duty Factor

A cw LINAC is strongly requested from users in the SHE Program

At low energy, a cw LINAC made of multigap s.c. is the best solution

SUPERCONDUCTING CH-DTL




High estate gradient

Large energy gain/cavity

Less focusing elements



Related Oral Poster
from H.Podlech on
Thursday,
THPB009 D. Maeder



Related Oral Poster

THPB035 P. Gerhard

- **Stage 1: Upgrade of the existing HLI Injector**
 - A new 18GHz ECR ion source
 - A new CW 4-Rod RFQ
 - Status: under commissioning
- **Stage 2: Construction of the first cryogenic module**
 - First CH-DTL, 2 s.c. Solenoids, Cryostat
 - Status: cavity under construction, cryostat ordered




Related Poster:

TUPB074 W. Barth

SUPB071 F.Dziuba

Gap	15
Gradient	5.1 MV/m
Length	0.69 m
Gap length	40.8 mm
Aperture	20 mm
Eff. Gap Voltage	225 kV

SUPERCONDUCTING CH-DTL: General R&D at IAP Frankfurt



325 MHz, s.c. CH-DTL 5MV/m

- 7 equidistant gaps @ 11.4 AMeV
- Inclined stem to tune the end cell
- slow/fast bellow tuner
- Cavity under production!

Related Poster

TUPB071: M.Bush

Pulsed beam test planned behind the UNILAC

Summary

- **H-Mode cavities shows great potential in the low to medium β profile**
 - IH-DTL is established as standard solution for heavy ion
 - Innovative coupling scheme developed for lower betas
 - CH-DTL can become a valid alternative to classical E-Mode DTL
- **FAIR LINAC UPGRADE entirely based on IH-DTL and CH-DTL**
 - A new dedicated 70 MeV CH-DTL is under construction
 - A replacement of the 90 MV UNILAC DTL is under investigation
 - First s.c. 19 gaps CH-DTL built at IAP Frankfurt
 - A cw s.c. prototype LINAC under construction
 - A 325 MHz s.c. CH-DTL under construction.