

HIRFL-CSR

Construction and Commissioning

Jiawen Xia


Presented by Jie Wei

xiajw@impcas.ac.cn


**Institute of Modern Physics (IMP)
Chinese Academy of Science (CAS)**


Lanzhou, China

Major accelerator projects in China



HIRFL-CSR Layout





- Project construction start: 1999
- Total cost: ~US\$30M
 - Including two cooler-synchrotrons, transport lines, experiments, civil engineering (new buildings)

Physics Program of CSR

RIB physics

(With Radioactive Ion Beams)

Researches of hot nuclei

(With high-energy beams)

Atomic physics

(With highly charged heavy ions)


Related applications

	CSRm	CSRe
Circumference (m)	161.0014	128.8011
Average radius (m)	$8R_{SSC}=34R_{SFC}=25.62416$	$4/5R_{CSRm}=20.499328$
Geometry	Race-track	Race-track
Max. energy (MeV/u)	2800 (p) 1100 (C^{6+}) 500 (U^{72+})	2000 (p) 750 (C^{6+}) 500 (U^{92+})
β (Tm)	0.81/12.05	0.50/9.40
γ (T)	0.10/1.60	0.08/1.60
Damping rate (T/s)	0.05 ~ 0.4	-0.1 ~ -0.2
Repeating circle (s)	~17 (~10s for Accumulation)	
Acceptance	Fast-extraction mode	Normal mode
A_h (π mm-mrad)	200 ($\Delta p/p = \pm 0.3\%$)	150 ($\Delta p/p = \pm 0.5\%$)
A_v (π mm-mrad)	40	75
$\Delta p/p$ (%)	1.4 ($\epsilon_h = 50 \pi$ mm-mrad)	2.6 ($\epsilon_h = 10 \pi$ mm-mrad)

CSR major parameters


	CSRm	CSRe
E-cooler		
Electron energy (KeV)	35	300
Eff. cooling length (m)	3.4	3.4
RF system	Accel. Accum.	Deceleration
Harmonic number	1 16, 32, 64	1
f_{min}/f_{max} (MHz)	0.24/1.81 6.0 / 14.0	0.4 / 2.0
Voltages (n $\times$ kV)	1 $\times$ 7.0 1 $\times$ 20.0	2 $\times$ 10.0
Vacuum (mbar)	(3.0×10^{-11})	

CSR Operation Scheme




Fast extraction

CSRe



CSRe



CSRm injection scheme

C, N, O, F, Ne, Ar, Ca, $A \leq 40$, $E = 7\text{--}10$ MeV/u

SFC + CSRm


Stripping injection ($A \leq 20$) + e-cooling $\rightarrow \rightarrow I = 10^9$

MMI + RF stacking ($20 \leq A < 40$) + e-cooling $\rightarrow \rightarrow I = 10^9$


Kr, Xe, Ta, Au, Pu, U, $A \geq 40$, $E = 10\text{--}25$ MeV/u

SFC + SSC + CSRm




MMI + e-cooling ($A \geq 40$) $\rightarrow \rightarrow I = 10^7$



CSRm Lattice Layout




CSRm-dipole Fabrication



-Type, Angle=22.5°, Rbend, Radius=7.6m, Air Gap=80mm, Useful aperture= $140 \times 60 \text{ mm}^2$, Precision= 3×10^{-4}

CSRm-Quadrupole Fabrication



$L=0.5\text{m}, 0.65\text{m}, \Phi=170\text{mm}$, Useful aperture= $160 \times 100\text{mm}^2$, Precision= 1.5×10^{-3}

Special magnets of CSRm





mp

C

S

Sept

Static-electric septum (for multi-turn injection)



$L = 2 \text{ m}$, $V_{\text{max.}} = 160 \text{ kV}$, Septum = **0.1mm**

Kicker for fast extraction



$I_{\max} = 2700\text{A}$


$V_{\max} = 60\text{ kV}$

Rising time: 150ns








e-cooler
for ion cooling



Hollow e-beam



CSRm RF System



RF-station for acceleration

$f = 0.24 \sim 1.81 \text{ MHz}$, $V_m = 7 \text{ kV}$



RF for beam accumulation





$f = 6 \sim 14 \text{ MHz}$, $V_m = 20 \text{ kV}$

UHV System of CSR

Bake-out temperature: 250°C, Pressure: 5×10^{-12} mbar



Electronics Development



SRm hall



SRe hall



SRm Injection Beam line



Line between CSRm & CSR



Power supply system



Ring hall



CSRm 1st-Commissioning in 2006

Scheme

Ion: C⁶⁺

Stripping injection

Electron-cooling


Cooling-Accumulation + Acceleration


Particles: 10^8

Energy: 1 GeV/u

Scheme of the stripping injection in CSRm

05/4/2







Orbits of the stripping injection in CSRm

9 turns beam signal from BPM with zero-bumping

Single-turn injection. All PS were controlled by hand 05/10/22 01:0




4 Bumps layout for the CSRm Injection



Current signals of 4 bump-PS for dynamic bumping orbit

Bump-PS controlled by the new DSP


2006.01



22 turns beam signal from BPM with dynamic bumping orbit

Single-turn injection

2006.01




First stored beam signal from spectrum analyzer

Bumping orbit , RF modulation (1.3Kv), Spe. Ana. in zero-span mode

Multi-turn injection


23Cy2 =7A 21D4 =0.5A

06/1/23 22:47



5 times of RF in 10s 1/e life-time $\approx$ 10s


C^{6+} -beam accumulation test in CSRm



7→1000MeV/u (C^{6+}) Ramping Test

06/10/17 2

Move back the tune before 50MeV/u







Particles: 2x

η ramping
90%

PS & RF Setting

7→1000MeV/u Ramping



Major Parameters of 1GeV/u Acceleration


C⁶⁺-Beam	7→1000MeV/u	0.76Tm→11.3Tm	I _{top} =1mA
Dipole	140x60 mm ² 0.1→1.5T	160A→2500A	450A/s
Quadrupole	160x110 mm ² 0.6T/m → 9T/m	20A →600A	100A/s
RF	f = 0.45→1.63MHz	H = 2→1	V _{max.} = 3.5KV
Machine	T _{ramping} = 7s	Top Power 3MW	Vacuum 5x10 ⁻¹² mbar

First COC for CSRm


06/12/27 21:00

Before correction

After correction




e-cooling for C⁶⁺-beam at 7MeV/u


 $\Delta P/P$
 4×10^{-3}

 2×10^{-4}



Beam Accumulation with e-cooling in CSRm

Beam current: 1.5mA




Cooling-accumulation in CSRm

With 9 times of beam injection



Cooling-Accumulation and Acceleration in CSRm


07/01/03 20:0



7→→1000 MeV/u

Top current: **3 mA**


$\sim 2 \times 10^9$



Cooling-Accumulation and Acceleration in CSRm

7→1000 MeV/u, Top current (final record) : **3.4 mA**, 2.1×10^9

07/01/03 20:3



Schedule of CSR 1st-Commissioning

2006.01	Get the CO beam
2006.03-04	Accumulation: 10^8 Particles (C^{6+})
2006.05-10	1GeV/u-Accelerating
2006.11-12	COC, e-cooling
2007.02-04	SSC+CSRm---MMI (Ar^{18+}), Fast extraction
2007.05-08	Stored beam in CSRe, Experiments

Thank You!