

ENTRY No. C6

NAME OF MACHINE Y-20 DATE
INSTITUTION Institute of Atomic Energy
ADDRESS Box 275, Beijing, PRC
TEL 868221 TELEX
IN CHARGE REPORTED BY

HISTORY AND STATUS

DESIGN, date Model tests
ENG DESIGN, date
CONSTRUCTION, date October 1, 1958
FIRST BEAM, date (or goal)
MAJOR ALTERATIONS

COST, ACCELERATOR 6 million yuan
COST, FACILITY, total 10 million yuan
FUNDED BY

ACCELERATOR STAFF, OPERATION AND DEVELOPMENT
SCIENTISTS ENGINEERS
TECHNICIANS CRAFTS

GRAD STUDENTS involved during year
OPERATED BY Research staff or Operators
OPERATION 120 hr/wk, On target 100 hr/wk
TIME DISTR. in house 100 % , Outside %
BUDGET, op & dev
FUNDED BY

RESEARCH STAFF, not included above
USERS, in house outside
GRAD STUDENTS involved during year
RESEARCH BUDGET, in house
FUNDED BY

MAGNET
POLE FACE, diameter (compact) 120 cm, R extraction 52.5 cm
R injection cm
GAP, min 148 cm, Field 15.95 kG
max 218 cm, Field 13.05 kG } at 286944...
AVERAGE FIELD at R ext 14.50 kG } Ampere turns
B max/ <B>

NUMBER OF SECTORS { compact separated } Spiral, max 45 deg
SECTOR ANGLE (SSC) deg
TRIMMING COILS 7 coils

CONDUCTOR, material and type Cu
STORED ENERGY (cryogenic) MJ
POWER: main coils 130 max, kW ; current stability 2x10-4
trimming coils max, kW ; current stability 1x10-3

WEIGHT: Fe 120 tons ; coils 15 tons
COOLING system water
ION ENERGY (bending limit) E/A = q^2/a^2 MeV/amu
(focusing limit) E/A = q^2/a^2 MeV/amu

ACCELERATION SYSTEM

DEES, number 2 ; angle 180 deg
BEAM APERTURE 35 cm ; DC Bias kV
TUNED by, coarse fine
RF 5.9 to 19.3 MHz, stable +/- 2x10-6
Orb F 6 to 17.2 MHz
HARMONICS, RF/Orb F, used 1st
DEE - Gnd, max 70 kV, min gap 26.5 cm
STABILITY, (pk-pk noise)/(pk RF volt) 1x10-3
ENERGY GAIN, max 200 kV/turn
RF PHASE, stable to +/- 1 deg
RF POWER input, max 120 kW
FREQUENCY MODULATION, rate 300 /s
modulator, type outside modulator
beam pulse, width 2-3 ns

VACUUM SYSTEM

OPERATING PRESSURE 1 x 10-5 Torr or mbar
PUMPS, No, Type, Size

ION SOURCES

PIG. type

INJECTION SYSTEM

EXTRACTION SYSTEM

Electrostatic deflector

FACILITIES FOR RESEARCH

SHIELDED AREA, fixed 150 m^2 ; movable m^2
TARGET STATIONS 3 in 2 rooms
STATIONS served at same time, max 1
MAG SPECTROGRAPH, type
COMPUTER model
OTHER FACILITIES

CHARACTERISTIC BEAMS

Table with columns: PARTICLE, ENERGY (MeV) Goal, Achieved, CURRENT (pA) Internal, External. Rows for P, D, Alpha.

SECONDARY

(part/s)

BEAM PROPERTIES

MEASURED CONDITIONS
PULSE WIDTH 6 RF deg 1 pA of 12 MeV P ions
PHASE EXC, max RF deg pA of MeV ions
EXTRACT eff 0.7 % pA of MeV ions
RESOL delta E/E % pA of MeV ions
EMITTANCE

(pi mm. mrad) { axial rad } pA of MeV ions

OPERATING PROGRAMS, time distribution
BASIC NUCLEAR PHYSICS 90% SOLID STATES PHYSICS
BIOMEDICAL APPLICAT. ISOTOPE PRODUCTIONS

REFERENCES/NOTES

PLAN VIEW OF FACILITY, NOTEWORTHY FEATURES, COMMENTS