

ENTRY NO. CM1 Date July 3, 1992  
 Machine Name CYCLONE 3  
 Manufacturer IBA  
 Address Rue J. E. Lenoir 6, 1348 Louvain-la-Neuve,  
 Tel 32 10 47 58 11 Telex Belgium  
 Fax 32 10 47 58 10 EMAIL  
 In Charge: Yves JONGEN Reported by: Stephane FASSIN.

#### HISTORY AND STATUS

DATES: Design 1989 First Machine 1990  
 SALES: No. Sold/Operational 3 / 2 Currently Available Y  
 COST: Accelerator Facility

#### MAGNET

POLE PARAMETERS:  
 Diameter 50 cm R<sub>extract</sub> 20.5 cm R<sub>inject</sub> 2 cm  
 HILL PARAMETERS: Gap (min) 3.4 cm B<sub>max</sub> 1.95 T  
 (Ø AT) Gap (max) cm B<sub>min</sub> T  
 VALLEY PARAMETERS: Gap (min) 5 cm B<sub>max</sub> 1.70 T  
 (Ø AT) Gap (max) cm B<sub>min</sub> T  
 AVERAGE FIELD: < B ><sub>min</sub> 1.85 T < B ><sub>max</sub> T  
 NUMBER OF SECTORS: compact/separated 4 /  
 sector angle 40° deg. spiral (max) deg.  
 FIELD TRIMMING: Trim Coils  
 Harmonic Coils  
 Other  
 CURRENT: Main Coils 225 Amps Stability 10<sup>-4</sup>  
 Trim Coils +/- 5 Amps Stability 10<sup>-4</sup>  
 Stored Energy (cryogenic) MJ  
 WEIGHT: Iron 5 Tons Conductor 0.5 Tons  
 ION ENERGY: Bending Limit E/A = 7.6 q<sup>2</sup>/A<sup>2</sup> MeV/u  
 Focussing Limit E/A = 7.6 q/A MeV/u

#### ACCELERATION SYSTEM

FUNDAMENTAL ACCELERATION:  
 Description: 2 x 90° Dees  
 No. of Gaps/turn 4 dE/dn(max) 0.08 MeV/q  
 Voltage(max) 0.02 MV Harmonic f<sub>rf</sub>/f<sub>ion</sub> 2  
 Freq 30 MHz Power in(max) 10 kW  
 Stability: Phase +/- 10% Voltage 20 kV (dee)

#### VACUUM SYSTEM

OPERATING PRESSURE: 8 10<sup>-5</sup> mbar  
 PUMPS: No. and type 1 x 300 l/sec ODP

#### ION SOURCE(S)

Type	Intensity (mA)	Ø (π mm mrad)	ε <sub>n</sub> = βγϵ (π mm mrad)	Ion Species
(a) PIG cold cathode	1			deuteron
(b)				

#### INJECTION SYSTEM

Efficiency %

#### EXTRACTION SYSTEM

Deflector Efficiency 70 %

#### CHARACTERISTIC BEAMS

Accelerated Ions	E/A (MeV/u)	Current(part. μA)	Internal	External
(a) deuteron	1.90		100	70
(b)				

#### EXTRACTED BEAM PROPERTIES:

For μA of MeV/u ions  
 ΔE/E % Δφ °f  
 ε<sub>n</sub> = βγϵ x πmm mrad z πmm mrad

#### REFERENCES/NOTES

(a) EPAC 90, Y. Jongen et al., Nice 1990  
 (b)

ENTRY NO. CM2 Date July 3, 1992  
 Machine Name CYCLONE 10/5  
 Manufacturer IBA  
 Address Rue J. E. Lenoir 6, 1348 Louvain-la-Neuve,  
 Tel 32 10 47 58 11 Telex Belgium  
 Fax 32 10 47 58 10 EMAIL  
 In Charge: Yves JONGEN Reported by: Stephane FASSIN.

#### HISTORY AND STATUS

DATES: Design 1988 First Machine 1989  
 SALES: No. Sold/Operational 2 / 2 Currently Available Y  
 COST: Accelerator Facility

#### MAGNET

POLE PARAMETERS:  
 Diameter 76 cm R<sub>extract</sub> ~35 cm R<sub>inject</sub> 2 cm  
 HILL PARAMETERS: Gap (min) 3 cm B<sub>max</sub> 1.9 T  
 (Ø 112,000AT) Gap (max) cm B<sub>min</sub> T  
 VALLEY PARAMETERS: Gap (min) 80 cm B<sub>max</sub> 0.4 T  
 (Ø AT) Gap (max) cm B<sub>min</sub> T  
 AVERAGE FIELD: < B ><sub>min</sub> 1.3 T < B ><sub>max</sub> 1.3 T  
 NUMBER OF SECTORS: compact/separated 4 /  
 sector angle 50° deg. spiral (max) 0° deg.  
 FIELD TRIMMING: Trim Coils None  
 Harmonic Coils None  
 Other  
 CURRENT: Main Coils 200 Amps Stability 5 10<sup>-5</sup>  
 Trim Coils N/A Amps Stability N/A  
 Stored Energy (cryogenic) N/A MJ  
 WEIGHT: Iron 12 Tons Conductor 1,250 Tons  
 ION ENERGY: Bending Limit E/A = 11 q<sup>2</sup>/A<sup>2</sup> MeV/u  
 Focussing Limit E/A = 11 q/A MeV/u

#### ACCELERATION SYSTEM

FUNDAMENTAL ACCELERATION:  
 Description: 2 x 30° Dees on lambda/2 Helical/Vertical Stems  
 No. of Gaps/turn 4 dE/dn(max) 0.104 MeV/q  
 Voltage(max) 0.03 MV Harmonic f<sub>rf</sub>/f<sub>ion</sub> 2 p/4 d  
 Freq 40 MHz Power in(max) 0.010 MW  
 Stability: Phase Voltage 2 10<sup>-3</sup>

#### VACUUM SYSTEM

OPERATING PRESSURE: 3 10<sup>-6</sup>  
 PUMPS: No. and type 2 x 2000 l/sec ODP

#### ION SOURCE(S)

Type	Intensity (mA)	Ø (π mm mrad)	ε <sub>n</sub> = βγϵ (π mm mrad)	Ion Species
(a) PIG 1 DC				H <sup>-</sup>
(b) PIG 1 DC				d <sup>-</sup>

#### INJECTION SYSTEM

2 Internal Sources Efficiency 10 %

#### EXTRACTION SYSTEM

Stripping Efficiency 100 %

#### CHARACTERISTIC BEAMS

Accelerated Ions	E/A (MeV/u)	Current(part. μA)	Internal	External
(a) H <sup>-</sup>	10		100	100
(b) d <sup>-</sup>	2.5		50	50

#### EXTRACTED BEAM PROPERTIES:

For μA of MeV/u ions  
 ΔE/E % Δφ °f  
 ε<sub>n</sub> = βγϵ x πmm mrad z πmm mrad

#### REFERENCES/NOTES

(a) EPAC 90, Y. Jongen et al., Nice 1990  
 (b)