

Present Status of PLS-II and PAL-XFEL

September 13, 2021 Changbum Kim Pohang Accelerator Laboratory





Contents

- Pohang Accelerator Laboratory
- PLS-II Status
- PAL-XFEL Status





Pohang Accelerator Laboratory







History of PAL

I. PLS

| Project started | April | 1988 |
|---------------------------------------|-------|------|
| User service started | Sept. | 1995 |
| II. Major Upgrade of the PLS (PLS-II) | | |
| 3.0 GeV PLS-II upgrade begin | Jan. | 2009 |
| 3.0 GeV PLS-II upgrade completed | Dec. | 2011 |
| User service started | Mar. | 2012 |
| 3.0 GeV 400 mA top-up operation | July | 2015 |
| III. PAL-XFEL | | |
| Project started | April | 2011 |
| Beam commissioning started | April | 2016 |
| Saturation of FEL (0.1 nm) | Nov. | 2016 |
| User service started | June | 2017 |





PLS Upgrade Project: PLS-II

- 1. Period : 3 year (One year break in user service)
- 2. Budget : 100 M \$
- 3. Critical path : All 30 beamlines should be operated in PLS-II after one year shutdown.







Goal of PLS-II

○ Main goals

- Beam energy : 2.5 \rightarrow 3.0 GeV
- Current : 200 \rightarrow 400 mA
- Storage ring emittance : 18.9 \rightarrow 5.8 nmrad
- No. of insertion device : 10 \rightarrow 20
- Top-up operation mode

○ Important improvement

- Introduction of superconducting RF
- In-vacuum undulator development
- New instrumentations: Libera BPM, etc.
- Improved beamline environment
- PAL-DCM development





POHANG ACCELERATOR LABORATORY

PLS-II Linac



- Thermionic electron gun
- 17 pulse modulators (200 MW, 7.5 µs)
- 17 klystrons (80 MW, 4 µs)
- 16 energy doublers (gain = 1.5)
- 46 accelerating sections

- Length = 170 m
- 3.0 GeV, full energy injection
- 2,856 MHz (S-band)
- 10 Hz, 1.5 ns, 1 A pulsed beam
- Norm. Emittance : 150 µmrad







PLS-II Storage Ring





- Beam Energy 3.0 GeV
- Beam Current 400 mA
- Lattice DBA
- Superperiods 12
- Emittance 5.8 nm·rad
- Tune 15.37 / 9.15
- RF Frequency 499.97 MHz
- Circumference 280 m



POHANG ACCELERATOR LABORATORY



PLS-II Top-up Operation

- Beam availability was higher than 97% in 2020.
- Beam current will be back to 400 mA at the end of 2021 with cryomodule #3







Instrumentations for orbit stability





Electron Beam Stability

- Orbit change in 10 Hz slow reading: < 1 μ m for 10 days
- Orbit change in 10 kHz fast reading: < 5 μ m (H), < 3 μ m (V)
- Less than 10% of beam size in both directions





Photon Beam Stability

- Feedback is running in 13 beamlines with PBPMs
- Orbit change in 10 Hz slow reading: < 1 μ m for 10 days
- Number of PBPM is increasing





Inside of PBPM





Hybrid Mode for Time Resolved Experiments

- Harmonic number: 470
- Multi-bunch mode: 400 bunches
- Hybrid mode: 300 bunches + Single bunch
- 4 mA single bunch current is available in user operation







Beamline Map (36 Beamlines)







PLS-II User Statistics



PLS-II User Achievements (~2020)

Publications

nature





Science

Min et al., Science 366, 749-753 (2019) 8 November 2019

Efficient, stable solar cells by using inherent bandgap

of α-phase formamidinium lead iodide Hand Mir, Maongsuk Kim, Soung-Un Lee, Hycenneo Kim, Gaisu Kim, Keunou Chei,

general mixed colors and universe containing formansforming FAL methylammonian (BAL) methylam



Song et al., Science 367, 777-781 (2020) 14 February 2020

Dry reforming of methane by stable Ni-Mo nanocatalysts on single-crystalline MgO

Youngtong Song¹, Ersen Ozdemir^{2,3}, Sreerangappa Romesh², Attiar Adisber², Saravanan Subramanian², Aadesh Harole⁴, Nohammed Albash⁴, Bentar Abdellah Fachel^{4,5}, And Jamai^{4,6}, Debrum Moon², San Hee Chel⁴, Cofer T, Yanai^{25,5,5}

Lagranzia caranta finatima majana tepisebana devolucia productiva trans antaria da antaria finatima vagiana tepisebana descontrativa de la constructiva de la construcción de la constru



IRIC-+ 2021

nature

Article

Design and synthesis of multigrain nanocrystals via geometric misfit strain

| Nerri e este en en este este m | Verman I. David Margar | | Myoung Hwan Oh ^{1224,513} , Min Gee Cho ^{12,530} , Dong Young Chung ¹² , Inchul Park ¹⁶ , | | | |
|--|--|--|---|--|--|--|
| eived: 15 June 2018 | Youngwook Paul Kwon ⁷ , Colin Ophus ⁸ , Dokyoon Kim ^{12,9} , Min Gyu Kim ¹⁶ , Beomgyun Jeong ¹¹ , X. Wendy Gu ¹² , Jimwoung Jo ¹² , Ji Mun Yoo ¹³ , Jaeyoung Hong ¹² , Sara McMains ⁷ , Kisuk Kang ¹⁶ , Yung-Eun Sung ¹² , A. Paul Alivisatos ^{3,6,514} & Taeghwan Hyeon ¹³²⁴ | | | | | |
| epted: 30 October 2019 | | | | | | |
| lished online: 15 January 2020 | | | | | | |
| | The impact of topological defects associated with grain boundaries (GB defects) on | | | | | |
| | the electrical, optical, magnetic, mechanical and chemical properties of | | | | | |
| | nanocrystalline materiab ¹ 's wellkown. However, cluckdafing this influence coperimentally is difficult because grants possible wholh a langer range of stars, shapes and random relative onlinations ¹ . Here we demonstrate that precise control of the heterogenize of colloidal ophydration lancerystak enables ordered grant growth and can thereby produce materials samples with uniform GB defects. We fluxartae our approach with a multigrain nancerystak comprising 2.6.0, nancotbe core that carries hand, shellon oak there. The individual bits are symmetry- ore that carries that hereby and the stars of the stars of the second | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | related interconnect | ed grains", and the large geometric n | nisfit between adjacent | | | |
| | | | | | | |
| | | | | | | |
| | | | nature | | | |
| | | | mature | | | |
| ARTICLES | | | THATPHAN | | | |
| ARTICLES http://doi.org/10.1020/41563-079-0575 .tomic-level tun igh-performand roduction | ing of Co ce electro | -N-C catalyst ochemical H ₂ O | for | | | |
| ARTICLES hps://home.rostone.onv.org. tomic-level tun igh-performance roduction | ing of Co ce electro | o-N-C catalyst ochemical H₂O | for 2 | | | |
| tomic-level tun igh-performanc roduction | ing of Co ce electro | D-N-C catalyst ochemical H ₂ O | t for 2 | | | |
| ARTICLES http://doi.org/1002020.444643.049.0277.6 http://performand roduction lyacon Jung ^{12,4} , Heajong Shin ^{12,4} , son Sook Lea ¹² , Jiheon Kim ¹² , | ing of Co ce electro , Byoung-Hoon Lo Wytse Hooch Ant | -N-C catalyst ochemical H ₂ O | t for 2 hyeong Lee ³ , ng Lee ⁹ , | | | |
| Articles tomic-level tun igh-performand roduction lyeon Jung ^{12,4} , Heejong Shin ^{12,4} eon Seok Lee ^{3,} Jiheon Kim ^{13,4} ng-Pyo Cho ⁸ , Jong Suk Yoo ^{®14} | ing of Co ce electro , Byoung-Hoon Lo Wytse Hooch Ant , Yung-Eun Sung | -N-C catalyst ochemical H ₂ O e ¹³⁴ , Vladimir Efremov ³ , Sudi nk ¹³ , Subin Park ¹³ , Kug-Seu I ^{13*} and Taeghwan Hyeon | t for 2 hyeong Lee ³ , ng Lee ⁹ , | | | |
| An interest of the second seco | A goung-Hoon Le by Byoung-Hoon Le Wytse Hooch Ant , Yung-Eun Sung m peroduced electrocken lectrocatipyts is insue were structure samble the structu | D-N-C catalyst pchemical H ₂ O http://www.com/s.su http://www.com/s.su http://www.com/su and Taggiwan Hyson 4 restaived manufactured by the and Taggiwan Hyson 4 restaived manufactured by the intervent sector asygen fitteent to meet the demands for in the competing and the competing and the competing and the competing aby the competing and the competing and the competing and the competing aby the competing and the competing | tinaternats | | | |

Article | Published: 17 February 2020

Highly durable metal ensemble catalysts with full dispersion for automotive applications beyond single-atom catalysts

Hojin Jeang, Ohmin Kwan, Beam Sik Kim, Junemin Bae, Sangyang Shin, Hee Eun Kim, Jihan Kim & Hyunjao Lee \boxtimes

Nature Catalysis 3, 368-375(2020) Cite this article





Korean 4GSR Project

- ✤ 4GSR project was officially approved.
- ***** CDR was finished.
- ✤ Project will be started from 2022.



| Parameter | Units | PLS-II | Korean 4GSR |
|------------------------------|-------|---------|-----------------|
| Electron energy | GeV | 3 | 4 |
| Horiz. Emittance | рт | 5800 | 58 (RB: 39) |
| Vert. Emittance | рт | ~ 58 | ~ 5.8 (RB: 39) |
| Bunch length (rms) | ps | 20 | 13 (50 with HC) |
| Circumference | m | 280 | 800 |
| Harmonic # | | 470 | 1332 |
| RF frequency | MHz | 500 | 500 |
| Beam stability @ ID (x/y) | μт | < 4 / 2 | < 2.5 / 0.45 |
| Injection mode | | Тор-ир | Тор-ир |





PAL-XFEL



April 2011: PAL-XFEL project started (Total Budget: 400 M\$)

In 2017:

- User service started in June
- 120 days for user service

In 2018

- 140 days for user service - HX self-seeding commissioning

In 2019

- 160 days for user service - 60 Hz operation started

In 2020

- 170 days for user service
- HX self-seeding user service started

TOR LABORATORY



PAL-XFEL Parameters





FEL Pulse Energy of User Service (2020)







Hard X-ray Self-Seeding

Schematic of hard x-ray self-seeding with a diamond crystal





Self-Seeded FEL at 9.7 keV

- Photon Energy Ec = 9.7 keV
- Averaged FEL energy: ~850 μJ (~1.5 mJ for single shot)
- SASE bandwidth (FWHM) = 27 eV
- Measured bandwidth = 0.35 eV (Resolution = 0.26 eV)
- De-convoluted bandwidth (FWHM) = 0.22 eV
- FEL Pulse duration = ~ 20 fs
- Chicane time delay = 30 fs
- Bragg orientation = [115]
- Diamond thickness = $100 \ \mu m \ (c100)$
- Portion of SASE in seeded FEL: ~6 %
- Fraction of energy enclosed within \pm 1 eV : ~ 80%



Peak brightness (photons/s/ mm² /mrad²/0.1% BW): 5 x 10³⁵

PAL POHANG ACCELERATOR LABORATORY



Extending Photon Energy up to 20 keV

Pulse Energy



FEL pulse energy: ~0.48 mJ Undulator K = 1.409 Electron beam energy: 10.446 GeV

Spectrum



Bandwidth: ~ 21.2 eV (rms)





Two-Color FEL Generation

- 8 and 12 undulators were used before and after the self-seeding section.
- Two-color FEL pulses were obtained successfully.



Undulator Gap Setting for Two-Color FEL



Photon Energy Measurement of Two-Color FEL



Parallel Operation of Hard X-ray (30 Hz) and Soft X-ray (30 Hz)

IBIC+2021

- Kicker and septum magnets were installed in soft X-ray branch line
- Machine studies are ongoing for parallel operation





Thank you for your attention!

mine and the second for the second se

