



# Progress on the High Luminosity LHC

**Lucio Rossi – CERN**  
HL-LHC Project Leader  
**Oliver Brüning – CERN**  
deputy Project Leader

Plenary Talk # MOYPLM3  
IPAC'19 - Melbourne, 20 May 2019



# CONTENT

- LHC present performance and next Run
- HL-LHC
  - Why, scope and challenges
  - Beam Physics
  - LIU (LHC Injector Upgrade project)
- HL-LHC Status
  - Magnets
  - CCs
  - Collimators & other systems
  - Civil engineering
- Budget, time plan

*30 papers related to High Luminosity LHC @IPAC'19*


*Wednesday orals:*

- *B. Salvant et al. (impedance model)-invited*
- *J . Jowett et a. (heavy ion run)*
- *G. Sterbini et al. (Long Range beam-beam compensating wires test)*


*Thursday invited oral:*

- *M. Meddahi et al. (LHC Injector Upgrade)*

# LHC performance at a glance: Energy




# LHC performance at a glance: Energy




Energy depends on dipole field:

Design 7 TeV → 8.33 tesla, 86% of the max Ic


We will push LHC @ 2x7 TeV later on in Run3



# LHC Performance: Luminosity




Limited by the heat deposition in the IT Quadrupole in Nb-Ti: forecast 1.7- 2  $L_0$  ( $L_0 = 10^{34} \text{ cm}^{-2}\text{s}^{-1}$ , LHC nominal design lumi)




Typical figure for Run 2. this means 70% machine (including injectors) availability and about 60% efficiency!

# LHC Performance: Luminosity




Limited by the heat deposition in the IT Quadrupole in Nb-Ti: forecast 1.7- 2  $L_0$  ( $L_0 = 10^{34} \text{ cm}^{-2}\text{s}^{-1}$ , LHC nominal design lumi)



Typical figure for Run 2. this means 70% machine (including injectors) availability and about 60% efficiency!

# Performance: Integrated Luminosity

F. Bordry, Director of Accelerators & Technology, CERN



Period	Int. Luminosity [ $\text{fb}^{-1}$ ]
Run 1	29.2
Run 2: 2015	4.2
Run 2: 2016	39.7
Run 2: 2017	50.2
Run 2: 2018	66.0
<b>Total Run1 + Run 2</b>	<b>189.3</b>

Original goal of Run1+Run2 = 150  $\text{fb}^{-1}$ :  
 $\Delta = + 20\%$

# Outlook to LHC Run 3 (2021-2023)


Run3 WG,  
S. Fartoukh, chair  
N. Karastathis

## LIU beam intensity ramp up for HL-LHC: can be used in LHC Run3 ?


LHC Injectors Upgrade	2021	2022	2023*	Comment
# bunches	Up to 2748 (BCMS)			
$\epsilon_n [\mu m]$	1.3	1.3	1.3 → 1.55	Intensity Ramp Up
$N_b [10^{11} p]$	0 → 1.4	1.4 → 1.8	1.8 → 2.1	Max bunch population at the end of each year

Pushing present LHC at the limits (using HL-LHC studies and early installation of HiLumi equipment in LS2....: Levelling, collimator low-Z and DS, TDIS...)


Approaching cryogenic limitations different heat load emerged in Run2 is to be understood



### Swapping the vertical crossing polarity



r=30% decrease → 40% increase in integrated luminosity




**Goal Run3:  $L_{int}$  160 fb<sup>-1</sup> with margins**


F. Bordry, Director of Accelerators & Technology, CERN

L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.

# LHC / HL-LHC Plan




# LHC / HL-LHC Plan




L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.


# LHC / HL-LHC Plan




# LHC / HL-LHC Plan



# LHC / HL-LHC Plan




# LHC / HL-LHC Plan



Technical limitation on the instantaneous lumi:

- 1. Collider** (cryolimit in the triplet region) at  $2 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  twice the nominal design luminosity)
- 2. Experiments** (pile up in the detectors). Designed for PU 40 they are actually dealing with 60 (average)!

# LHC / HL-LHC Plan




Technical limitation on the instantaneous lumi:

1. **Collider** (cryolimit in the triplet region) at  $2 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  twice the nominal design luminosity)
2. **Experiments** (pile up in the detectors). Designed for PU 40 they are actually dealing with 60 (average)!


Technical limitation on integrated lumi:

1. **Collider** (radiation damage to the IT magnets – correctors and quadrupoles)
2. **Experiments** (radiation damage in the Inner Tracker)


# Why not just keep going with cons?



# Why not just keep going with cons?



# Why not just keep going with cons?



# Goal of HL-LHC

From EC-FP7 HiLumi LHC Design Study application of 2010

The main objective of HiLumi LHC Design Study is to determine a hardware configuration and a set of beam parameters that will allow the LHC to reach the following targets:

A peak luminosity of  $L_{\text{peak}} = 5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  with levelling, allowing:

An integrated luminosity of  $250 \text{ fb}^{-1}$  per year, enabling the goal of  $L_{\text{int}} = 3000 \text{ fb}^{-1}$  twelve years after the upgrade.

This luminosity is more than ten times the luminosity reach of the first 10 years of the LHC lifetime.

# Goal of HL-LHC

From EC-FP7 HiLumi LHC Design Study application of 2010

The main objective of HiLumi LHC Design Study is to determine a hardware configuration and a set of beam parameters that will allow the LHC to reach the following targets:

A peak luminosity of  $L_{\text{peak}} = 5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  with levelling, allowing:

An integrated luminosity of  $250 \text{ fb}^{-1}$  per year, enabling the goal of  $L_{\text{int}} = 3000 \text{ fb}^{-1}$  twelve years after the upgrade.

This luminosity is more than ten times the luminosity reach of the first 10 years of the LHC lifetime.

**Ultimate** performance established 2015-2016: with same hardware and same beam parameters: use of **engineering margins**:

$L_{\text{peak ult}} \cong 7.5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  and **Ultimate Integrated  $L_{\text{int ult}} \sim 4000 \text{ fb}^{-1}$**   
LHC should not be the limit, would Physics require more...

# Goal of HL-LHC

From EC-FP7 HiLumi LHC Design Study application of 2010

The main objective of HiLumi LHC Design Study is to determine a hardware configuration and a set of beam parameters that will allow the LHC to reach the following targets:

A peak luminosity of  $L_{\text{peak}} = 5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  with levelling, allowing:

An integrated luminosity of  $250 \text{ fb}^{-1}$  per year, enabling the goal of  $L_{\text{int}} = 3000 \text{ fb}^{-1}$  twelve years after the upgrade.

This luminosity is more than ten times the luminosity reach of the first 10 years of the LHC lifetime.

Ultimate performance established 2015-2016: with same hardware and same beam parameters: use of engineering margins:

$L_{\text{peak ult}} \cong 7.5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  and Ultimate Integrated  $L_{\text{int ult}} \sim 4000 \text{ fb}^{-1}$

LHC should not be the limit, would Physics require more...

# Goal of HL-LHC

From EC-FP7 HiLumi LHC Design Study application of 2010

The main objective of HiLumi LHC Design Study is to determine a hardware configuration and a set of beam parameters that will allow the LHC to reach the following targets:

A peak luminosity of  $L_{\text{peak}} = 5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  with levelling, allowing:

An integrated luminosity of  $250 \text{ fb}^{-1}$  per year, enabling the goal of  $L_{\text{int}} = 3000 \text{ fb}^{-1}$  twelve years after the upgrade.

This luminosity is more than ten times the luminosity reach of the first 10 years of the LHC lifetime.


Ultimate performance established 2015-2016: with same hardware and same beam parameters: use of engineering margins:

$L_{\text{peak ult}} \cong 7.5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$  and Ultimate Integrated  $L_{\text{int ult}} \sim 4000 \text{ fb}^{-1}$

LHC should not be the limit, would

Experiment are designing for this goal.  
We need to be compatible with it!

# HL-LHC performance (ultimate L<sub>lev</sub> from 2032)



## Luminosity: collision rate per unit cross section which parameters count for LHC?

$$L = \gamma \frac{f_{rev} n_b {N_b}^2}{4\pi \varepsilon_n \beta^*} R$$

## Luminosity: collision rate per unit cross section which parameters count for LHC?

$$L = \gamma \frac{f_{rev} n_b N_b^2}{4\pi\varepsilon_n \beta^*} R$$

energy

# Luminosity: collision rate per unit cross section which parameters count for LHC?

Beam current

$$L = \frac{\gamma f_{rev} n_b N_b^2}{4\pi\varepsilon_n \beta^*} R$$

energy

# Luminosity: collision rate per unit cross section which parameters count for LHC?

$$L = \frac{\gamma f_{rev} n_b N_b^2}{4\pi\varepsilon_n \beta^* R}$$

Beam current

energy

Beam size


# Luminosity: collision rate per unit cross section which parameters count for LHC?

Beam current

$$L = \frac{\gamma f_{rev} n_b N_b^2}{4\pi\varepsilon_n \beta^*} R$$

energy

Beam size



# Luminosity: collision rate per unit cross section which parameters count for LHC?


Beam current

$$L = \frac{\gamma f_{rev} n_b N_b^2}{4\pi\varepsilon_n \beta^*}$$

energy

Beam size

$$R = \frac{1}{\sqrt{1 + (\frac{\theta_c \sigma_s}{2\varepsilon_n \beta^*} \gamma)^2}}$$



# Luminosity: collision rate per unit cross section which parameters count for LHC?



**Beam current**

$$L = \gamma \frac{f_{rev} n_b N_b^2}{4\pi \varepsilon_n \beta^*}$$

**energy**

**Beam size**

$$R = \frac{1}{\sqrt{1 + (\frac{\theta_c \sigma_s}{2\varepsilon_n \beta^* \gamma})^2}}$$




# Luminosity: collision rate per unit cross section which parameters count for LHC?

**Beam current**



$$L = \frac{\gamma f_{rev} n_b N_b^2}{4\pi \varepsilon_n \beta^*}$$

**energy**

$$R = \frac{1}{\sqrt{1 + (\frac{\theta_c \sigma_s}{2\varepsilon_n \beta^* \gamma})^2}}$$



**Beam size**




# Luminosity: collision rate per unit cross section which parameters count for LHC?

**Beam current**




$$L = \gamma \frac{f_{rev} n_b N_b^2}{4\pi \varepsilon_n \beta^*}$$

**energy**

$$R = \frac{1}{\sqrt{1 + (\frac{\theta_c \sigma_s}{2\varepsilon_n \beta^* \gamma})^2}}$$



**Beam size**



# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters

Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)
Beam energy in collision [TeV]	7	7
$N_b$	1.15E+11	2.2E+11
$n_b^{12}$	2808	2760
Beam current [A]	0.58	1.1
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250
Minimum $\beta^*$ [m]	0.55	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50
Total loss factor R0 without crab-cavity	0.836	0.342
Total loss factor R1 with crab-cavity	-	0.716
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3

# HL-LHC parameters


Parameter	Nominal LHC (design report)	HL-LHC 25ns (standard)	HL-LHC 8b+4e <sup>10</sup>
Beam energy in collision [TeV]	7	7	7
$N_b$	1.15E+11	2.2E+11	2.2E+11
$n_b^{12}$	2808	2760	1972
Beam current [A]	0.58	1.1	0.79
Half Crossing angle [ $\mu\text{rad}$ ]	142.5	250	235 <sup>9</sup>
Minimum $\beta^*$ [m]	0.55	0.15	0.15
$\epsilon_n$ [ $\mu\text{m}$ ]	3.75	2.50	2.20
Total loss factor R0 without crab-cavity	0.836	0.342	0.342
Total loss factor R1 with crab-cavity	-	0.716	0.749
Virtual Luminosity with crab-cavity: $L_{\text{peak}} * R1/R0$ [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	1.70E+35	1.44E+35
Levelled Luminosity [ $\text{cm}^{-2} \text{s}^{-1}$ ]	-	5.0E+34 <sup>4</sup>	3.82E+34
Events / crossing (with leveling and crab-cavities for HL-LHC) <sup>7</sup>	27	131	140
Peak line density of pile up event [event/mm] (max over stable beams)	0.21	1.28	1.3
Leveling time [h] (assuming no emittance growth) <sup>7</sup>	-	7.3	7.1

Back-up  
for e-cloud

# Pile up


Pushing at the maximum the parameters of HL-LHC we would start the fill at  $L = 17 \times 10^{34}$  with 400 events/crossing.

# Pile up




Pushing at the maximum the parameters of HL-LHC we would start the fill at  $L = 17 \times 10^{34}$  with **400 events/crossing**.

# Pile up




Pushing at the maximum the parameters of HL-LHC we would start the fill at  $L = 17 \times 10^{34}$  with **400 events/crossing**.


# LIU (Intensity) and Levelling mode




Reducing heat load on the IT triplet  
(quench and cooling limits)  
Limiting pile up in the detectors



# LIU (Intensity) and Levelling mode



Reducing heat load on the IT triplet  
(quench and cooling limits)  
Limiting pile up in the detectors




# LIU installation under way:2019-2020



LHC Injectors Upgrade

Courtesy M. Meddahi and G. Rumolo, CERN




# LIU installation under way:2019-2020



LHC Injectors Upgrade

Courtesy M. Meddahi and G. Rumolo, CERN



**Linac 4**, has been built to take over.

- Higher energy **160 MeV**
- Acceleration of **H<sup>-</sup> ions** (charge exchange H<sup>-</sup>→p<sup>+</sup> in the PSB)

Construction **completed in 2017**

- Extensively tested in 2017-2018
- Ongoing **work in LS2 to connect it to the rest of the chain**



L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.

# LIU installation under way:2019-2020




LHC Injectors Upgrade

Courtesy M. Meddahi and G. Rumolo, CERN

## PSB upgrade

- **H<sup>-</sup> charge exchange injection** at 160 MeV → improved beam brightness (weaker space charge forces)
- **Energy : 1.4 GeV → 2 GeV**
  - New main power supply
  - New RF systems



**Linac 4**, has been built to take over.

- Higher energy **160 MeV**
- Acceleration of **H<sup>-</sup> ions** (charge exchange H<sup>-</sup>→p<sup>+</sup> in the PSB)

Construction **completed in 2017**

- Extensively tested in 2017-2018
- Ongoing **work in LS2 to connect it to the rest of the chain**



L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.

# LIU installation under way:2019-2020



LHC Injectors Upgrade

## SPS upgrade

- Main RF system upgrade (new solid state power plants – 2 x 1.6 MW)
- Impedance mitigation to improve beam stability
- More robust beam dump and protection devices



SPS  
6.9 km  
450 GeV

Courtesy M. Meddahi and G. Rumolo, CERN

## PSB upgrade

- H<sup>-</sup> charge exchange injection at 160 MeV → improved beam brightness (weaker space charge forces)
- Energy : 1.4 GeV → 2 GeV
  - New main power supply
  - New RF systems



PSB  
157 m  
1.4 GeV

Linac 4  
160 MeV

PS  
628 m  
26 GeV

Linac 2  
50 MeV




Linac 4, has been built to take over.

- Higher energy 160 MeV
- Acceleration of H<sup>-</sup> ions (charge exchange H<sup>-</sup>→p<sup>+</sup> in the PSB)

Construction completed in 2017

- Extensively tested in 2017-2018
- Ongoing work in LS2 to connect it to the rest of the chain

# LHC / HL-LHC Plan




## HL-LHC TECHNICAL EQUIPMENT:




### HL-LHC CIVIL ENGINEER:




# LHC / HL-LHC Plan



# ATS: new operation mode for hadron colliders Extending matching section to 13 km of arcs!



Pre-squeeze to  $\beta^* = 40$  cm






Tele-squeeze to  $\beta^* = 10$  cm

S. Fartoukh,  
et al. CERN

Overcoming LHC chromatic and matching limitations of  $\beta^* = 25\text{-}30$  cm.  
Around each P1 and P5 6.5 km machine become a giant matching  
section and beam size can be made as small as 5  $\mu\text{m}$ .

# Improving the data quality



Levelling helps to limit total pile up:

$\mu_{\text{ave}} = 140$  (ultimate:  $\mu_{\text{ave}} = 200$ ). Experiments ask to reduce the pile up linear density (number of events/length) and need to introduce time stamping

⇒ carefully control and variation of:

- $\beta^*$  (beam size at collision), main levelling knob
- Bunch tilt (Crab cavities)
- Crossing angle
- Longitudinal bunch length



Collision with  $\mu = 65$


# Performance

Due to many advances in beam dynamics understanding:

- ATS and beam optics controls
- Beam dynamics aperture
- Beam-beam (LR)
- Impedance model
- Noise model
- RF low level

HL WP2: G. Arduini, R. Tomas et al.






## Slide 56


---

LR2      Cecile can you add a New banner with the red circle of WP18?


Lucio Rossi, 22/03/2018



## Technology landmarks



## Technology landmarks




**CIVIL ENGINEERING**  
2 new caverns and two new 300-metre service galleries, two new large shafts; 10 new technical buildings on surface in P1 and P5 (ATLAS and CMS)



**"CRAB" CAVITIES**  
8 superconducting "crab" cavities for each of the ATLAS and CMS experiments to tilt the beams before collisions.


LHC TUNNEL



**FOCUSING MAGNETS**  
12 more powerful quadrupole magnets for each of the ATLAS and CMS experiments, designed to increase the concentration of the beams before collisions.



**BENDING MAGNETS**  
2 pairs of shorter and more powerful dipole bending magnets to free up space for the new collimators.




**CRYOGENICS**  
2 new large 1.9 K helium refrigerators for HL-LHC near ATLAS and CMS




Here, workers are seen carrying current to the magnets from the new service galleries to the LHC tunnel.




**COLLIMATORS**  
15 to 20 new collimators and 60 replacement collimators to reinforce machine protection.






**Complete 11.2 T cryo-assembly replacing a 15 m 8.3 T LHC dipole in 2020**




L. Bottura & A. Devred  
HiLumi WP11- F. Savary et al.

Hybrid (long proto): Excellent! But strong permanent degradation **after thermal cycle**. Absence of thermal gradient control in the procedure.

L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.





**Complete 11.2 T cryo-assembly replacing a 15 m 8.3 T LHC dipole in 2020**




Hybrid (long proto): Excellent! But strong permanent degradation **after thermal cycle**. Absence of thermal gradient control in the procedure.

# 11 T in full swing production: LS2 installation in 2020! great care given the stress sensitivity of $\text{Nb}_3\text{Sn}$




# IT quadrupole. Increase in field but also in size wrt LHC. Very relevant also for FCC magnets




# Test results IT QUAD

HiLumi WP3: G. Ambrosio (FNAL), P. Ferracin , E. Todesco (CERN) et al.




1st short (1 m long) model magnet: 2 coils  
CERN - 2 Coil US-LARP; test in Fermilab,  
excellent results and memory




1st long (4 m long) prototype magnet by  
US-LARP-AUP; test in Fermilab, very good  
start but short circuit developed. Now  
repaired and under **re-test next week**.

# Test results IT QUAD

HiLumi WP3: G. Ambrosio (FNAL), P. Ferracin , E. Todesco (CERN) et al.




1st short (1 m long) model magnet: 2 coils  
CERN - 2 Coil US-LARP; test in Fermilab,  
excellent results and memory




1st long (4 m long) prototype magnet by  
US-LARP-AUP; test in Fermilab, very good  
start but short circuit developed. Now  
repaired and under **re-test next week**.

## Further results IT quadrupoles on short models



## Further results IT quadrupoles on short models

Best HF magnet ever tested in terms of behaviour (not max field)  
Final conductor, final prestress procedure



HiLumi WP3:  
E. Todesco et al.

# Nb<sub>3</sub>Sn High Field Collider Magnets

- HiLumi needs by 2024 about 40 Nb<sub>3</sub>Sn large magnets:
  - **4+2** 11 T dipoles L=5.5m
  - **8+2** (7.2 m long) and **16+4** (4.2m long) IT quadrupole of 11.5 T
- We have learnt how to deal with this difficult technology (700 °C heat treatment, vac.impregnation, performance sensible to stress)
- However we found recently electrical and structural problems **on the first two long prototypes (partly seen also on 11 T)**.
  - Structural problems on IT Quads understood and solved: traced to too small margin (in shells) that could lead to failure for fatigue effect.
  - Electrical problem (QH insulation): 2 solutions identified, one under test on the 11 T dipole.
- Industrialization of long magnets is being more difficult than anticipated! Difference from LHC NbTi.




# Construction of the 1<sup>st</sup> and 2<sup>nd</sup> long (7.5 m!) IT Quad in CERN; in USA winding 4<sup>th</sup> long magnet




Hilal HL-LHC Melbourne.




# The HiLumi Magnets (~130)




Centro de Investigaciones  
Energéticas, Medioambientales  
y Tecnológicas



MCBXF



Skew quad




D2




Dodecapole



Decapole



Octupole






D2 orbit  
corrector

L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.




# Nb-Ti new technologies: CCT and SF magnets





Istituto Nazionale di Fisica Nucleare

L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.


# Crab Cavity




Rotational chemistry at



# Crab Cavity



Rotational chemistry at .



Hilumi  
HL-LHC PROJECT




CERN DQW prototype for SPS test  
Collaboration with UNILANC & STFC - C.I.  
Daresbury (UK)

CERN  
Lancaster University


Science & Technology Facilities Council  
The Cockcroft Institute of Accelerator Science and Technology

L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.


# The DQW CC in cryomodule for the SPS test



# The DQW CC in cryomodule for the SPS test





# The DQW CC in cryomodule for the SPS test



# Crab Cavities: progress in design, construction and test infrastructure





New SRF test stand  
with beam in SPS  
for HiLumi LHC  
Crab Cavities



RF phase scan w.r.t the beam phase  
with cavity 1: principle validated!  
Transparency of CC to beam  
demonstrated! MDs very successful  
(with voltage limitation).

# Crab Cavities: progress in design, construction and test infrastructure


New SRF test stand  
with beam in SPS  
for HiLumi LHC  
Crab Cavities



RF phase scan w.r.t the beam phase  
with cavity 1: principle validated!  
Transparency of CC to beam  
demonstrated! MDs very successful  
(with voltage limitation).

# Crab Cavities: progress in design, construction and test infrastructure

New SRF test stand  
with beam in SPS  
for HiLumi LHC  
Crab Cavities



New CC collaborations




Transparency of CC to beam demonstrated! MDs very successful (with voltage limitation).

Rossi - HL-LHC progress - IPAC'19 - Melbourne.


# Collimators low-Z : special MoGr Mo-coated upgrade partly in 2020 and then in 2025

Samples of MoGr (Molybdenum-Graphite) from producer (CERN EN/MME/STI)




HL WP5: S. Redaelli, R. Bruce, S. Gilardoni, M. Calviani, A. Bertrelli, R. Carra et al.

Cold-Warm-Cold bypass to host Collimators in the DS region



New injection protection absorber



HL WP14: C. Bracco et al.



In total some 40 new absorber and collimators devices in LS2 (2020) and LS3 (2025)

# Test on crystal collimation (for baseline)

Scope: further improvement of ion cleaning after 2016 re-baselining.


**Studying if, for ions, this can be an “adiabatic” upgrade of the IR7 system.**

**2017: improved by up to x60 collimation cleaning of Xe beams!**

Courtesy EN/SMM



Courtesy UA9 collaboration/PNPI




HL WP5: S. Redaelli, S.  
Gilardoni, M. Calviani al.


**4 mm = 50  $\mu$ rad,  
or 10 x 15m long LHC dipoles  
or 300 T at 7 TeV**

Two goniometers installed on B1 in LS2; two more on B2 in 2017, upgraded in 2018.

**4 operational crystals for collimation.**



# E-lens in HL-LHC for halo control - 30 MJ in the halo




*It would allow controlling actively the halo, through a hollow electron beam (overlapped over three meters to the proton/ion beams) that selectively excites halo particles.*

HL WP5: S. Redaelli, D. Perini, A. Rossi et al.



Cathode




Electron gun


*Design nearly complete.  
Surpassed target e-beam current of  
5A, now final cathode design (smaller)  
under test at FNAL.*

***Ready to built it, heading to integrated into the baseline.***


# High Luminosity LHC IT region



# High Luminosity LHC – Matching section



# Important upgrade of Technical infrastructure



HL-LHC Civil Enginner Point 5 (FR)  
The same in Point 1 (CH). In total:

- 10 new large buildings
- 1 km of galleries and caverns underground
- 2 shafts 65 m deep and 10 m wide

Hilumi Civil Engineer: 2 large shafts; 1 km  
of new underground; 20 new buildings;



Hilumi Civil Engineer: 2 large shafts; 1 km  
of new underground; 20 new buildings;

Contract T117 – JVMM (LHC-P1)




Hilumi Civil Engineer: 2 large shafts; 1 km  
of new underground; 20 new buildings;

Contract T117 – JVMM (LHC-P1)




**Hilumi Civil Engineer: 2 large shafts; 1 km  
of new underground; 20 new buildings;**

**Contract T117 – JVMM (LHC-P1)**




**Contract T118 – CIB (LHC-P5)**

# IN-KIND CONTRIBUTIONS



L.Rossi - HL-LHC progress - IPAC'19 - Melbourne.

# IN-KIND CONTRIBUTIONS



# IN-KIND CONTRIBUTIONS

**Personnel!**



CERN-  
KEK R&D

KEK D1  
design  
and  
construc-  
tion



DOE  
Nb3Sn  
R&D

LARP  
HiField  
quads

LARP  
Demo



FP6  
CARE  
Nb3Sn

FP7  
EuCARD-  
HiField  
Dip

FP7 DS

Hi-Lumi LHC

SLHC PP  
(INJ)  
SLHC INJ  
implem.

2000  
2005  
2010  
2015  
2024

**Project DS started**

**Project approval**

**Today**

Injector  
upgrade

HL-LHC  
Construction

HL-LHC  
install.& comm.

BINP+...  
Absorbers  
CC ampli.  
e-lens?...

TRIUMF  
CC  
cryostat




IHEP  
CCT  
corrector

**EU collaborations**



# Budget, expenditures & Time Plan

Total Completion	In kCHF
Material	925,345
M to P	25,697
Personnel	435,101
	<b>1,386,143</b>






# Budget, expenditures & Time Plan

Total Completion	In kCHF
Material	925,345
M to P	25,697
Personnel	435,101
	<b>1,386,143</b>

951 MCHF construction budget: no contingency (incl. 130 MCHF in-kind)

~ 2000 FTE-y (+collab.)

~ 80 MCHF of consolidation not incl.






# Budget, expenditures & Time Plan

Total Completion	In kCHF
Material	925,345
M to P	25,697
Personnel	435,101
	<b>1,386,143</b>

951 MCHF construction budget: no contingency (incl. 130 MCHF in-kind)

~ 2000 FTE-y (+collab.)

~ 80 MCHF of consolidation not incl.



W.r.t. schedule at project approval in 2016: **5 months of non-critical delays**  
**Extra cost? 3% now, projected → 5%?**

*Thanks*



High  
Luminosity  
LHC



# LHC energy exploitation (input from O. Bruning and task force)

- **14 TeV** operation (nominal design)
  - Tests before YETS 2016/2017 revealed problem with diode box that prevented termination of the proposed tests → LS2 consolidation of diode boxes.
  - The test in sector 1-2 for validating magnet performance **at 7TeV** prior to LS2 showed that we may need 1 quench/magnet:  $\geq 1000$  quenches, 2-3 months of intense quench campaign. Only question of time: foreseen in Run 3 (or Run 4)
- **15 TeV** (ultimate energy, dipoles at 93% of intrinsic limit):
  - Not impossible but very unlikely due to large time overhead (long quench campaign; and ~400 magnets never trained to ultimate ): trade-off between energy gain and luminosity
- Beyond ultimate energy sunstuting 1/3 of main dipole with a 11 T dipole
  - **~16 TeV**
  - Very unlikely: big change, big overheads of de and re-instalation (2-3 y?) and very difficult operation. The cost is in the 2-3 BCHF range.
  - The 11 T HiLumi dipole not optimized for cost and in series with LHC dipoles: big constraints