


Beam Line Design and Instrumentation for THz@PITZ -- the Proof-of-Principle Experiment on a THz SASE FEL at the PITZ Facility

T. Weilbach, P. Boonpornprasert, G. Georgiev, G. Koss, M. Krasilnikov, X.-K. Li, A. Lueangaramwong, F. Mueller, A. Oppelt, S. Philipp, F. Stephan and L. van Vu, DESY, Zeuthen, Germany, H. Shaker, CLS, Saskatoon, Canada

IPAC 2021
Campinas, SP, Brazil



Schematic Overview of PITZ




In order to allow THz pump--X-ray probe experiments at full bunch repetition rate for users at the European XFEL, the Photo Injector Test Facility at DESY in Zeuthen (PITZ) is building a prototype of an accelerator-based THz source. The goal is to generate THz SASE FEL radiation with a mJ energy level per bunch using an LCLS-I undulator driven by the electron beam from PITZ. Therefore, the existing PITZ beam line is extended into a tunnel annex downstream of the existing accelerator tunnel.


Core hole drilling



PITZ Tunnel




Tunnel Annex



Outlook

- Preparations of tunnel annex finished
- Last heavy construction work done in 06/2021
- Production / Ordering of components ongoing
- First beam in undulator planned for Q3/2021



Screen Station Design

- Design of all six screen stations finished
- Designed modularly to minimize the number of parts to produce
- In vacuum roller bearings for better stiffness at the THz screen
- Ellipsoidal mirror in vacuum to focus THz radiation, focus in diamond window to minimize window size (diameter: 20mm)

