

TUPLR011

Performance of the Novel Cornell ERL Main Linac Prototype Cryomodule

Fumio Furuta, John Dobbins, Ralf Eichhorn, Mingqi Ge, Daniel Gonnella, Georg Hoffstaetter,
Matthias Liepe, Tim O'Connell, Peter Quigley, Daniel Sabol, James Sears, Eric Smith, Vadim Veshcherevich
CLASSE, Cornell University, Ithaca, New York, U.S.A.



Introduction

The **main linac cryomodule (MLC)** for the future energy-recovery linac (ERL) based X-ray light source at Cornell has been designed, fabricated, and tested. It houses **six 7-cell SRF cavities** with individual higher order-modes (HOMs) absorbers, cavity frequency tuners, and one magnet/BPM section. **Cavities have achieved the specification values of 16.2MV/m with high-Q of 2.0e10 in 1.8K in continuous wave (CW) mode.** During initial MLC cavity testing, we encountered some field emission, reducing Q and lowering quench field. To overcome field emission and find optimal cool-down parameters, RF processing and thermal cycles with different cool-down conditions have been done. Here we report on these studies and present final results from the MLC cavity performance.




Image; moving MLC to Wilson lab, Mar2015.

Main Linac Cryomodule (MLC) prototype



Cavity preparation: bulk BCP, 650C outgassing, final BCP, 120C bake, HF rinse

RF test achievements in 1.8K




- Cavity #1, #2, and #3 achieved the target gradient of 16.2MV/m in the first power rise.
- Cavity #5 had severe field emission (FE), but processed out by RF processing. Cavity #4 was FE free, but limited by quench.
- 5 of 6 cavities achieved the design spec of 16.2MV/m.
- Cavity #1, #2, #3, and #5 achieved the target Q₀ of 2.0x10¹⁰ at 16.2MV/m, 1.8K after thermal cycles.
- Q₀ of cavity #4, #5, and #6 were impacted by early quench or field emission, and thus the impact of thermal cycles is less visible.
- 4 of 6 cavities had achieved design Q₀ of 2.0E+10 in 1.8K.

Summary

- The Cornell Main Linac Cryomodule has been cooled down from 300K to 1.8K successfully.
- The 7-cell cavities in the MLC have achieved the specification values of 16.2MV/m with Q₀ of 2.0x10¹⁰ in 1.8K.
- High-Q performance was maintained through cryomodule assembly to cool down and RF testing.
- Field emission caused mild Q₀ degradation in two cavities.
- Thermal cycle with small temperature gradient ("slow" cool down) gave the highest Q₀ for the cavities in the MLC prototype.

please see other posters for HOM and Microphonics.

Impact of thermal cycling with different dT_{vertical} on Q(E) in 1.8K



- Plot shows the temp. profiles on **top and bottom of Helium tank**. Not direct measurement of cavity surface temp.

