

# The muon linac project at J-PARC

---

**Y. Kondo**, R. Kitamura, Y. Fuwa, T. Morishita, K. Moriya **Japan Atomic Energy Agency**

M. Otani, E. Cicek, H. Ego, Y. Fukao, K. Futatsukawa, N. Kawamura, T. Mibe, Y. Miyake,

S. Mizobata, N. Saito, K. Shimomura, T. Yamazaki, M. Yoshida **KEK**

Y. Nakazawa, H. Inuma **Ibaraki Univ.** Y. Takeuchi, J. Tojo **Kyusyu Univ.**

K. Sumi, M. Yotsuzuka, T. Iijima, K. Inami **Nagoya Univ.** K. Ishida **RIKEN** N. Hayashizaki **TITEC**


Y. Iwashita Kyoto Univ. K. Hasegawa, Y. Iwata **QST** H. Yasuda **Univ. of Tokyo**

S. Bae, H. Choi, S. Choi, B. Kim, H. S. Ko **SNU** E. Won **Korea Univ.** G. P. Razuvaev **BINP**

- Physics motivation
- Experimental setup
- Accelerating structures
- Plan
- Summary


# Beyond the Standard Model?

## - muon g-2



$$\vec{\mu} = g \left( \frac{q}{2m} \right) \vec{S}$$

$$a_\mu = \frac{g - 2}{2}$$



# Muon g-2/EDM experiment J-PARC E34

Prog. Theor. Exp. Phys. **2019**, 053C02

proton  
(3 GeV) graphite target



$\mu^+$ (4 MeV) Surface muon  
 $\mu^+$ (25 meV) muon cooling

muon LINAC

$\mu^+$  (212 MeV)

injection



Storage magnet




Goals:  
 g-2 450 ppb (~ BNL/FNAL run 1)  
 EDM  $1.5 \times 10^{-21} \text{ e} \cdot \text{cm}$  (x70 better)

# J-PARC MLF

## Materials and Life science Facility









Particle	$\mu^+$
Energy	212 MeV (300 MeV/c)
Intensity	$1 \times 10^6$ /s
Rep rate	25 Hz
Pulse width	10 ns
Normalized rms emittance	$1.5 \pi$ mm mrad
Momentum spread	0.1 %

- 3-stage frequency, 4-structures.
- Comparable emittance to p linac, but very low intensity.

# Muon cooling for g-2/EDM experiment

USM production



- Thermal muonium production and laser dissociation produce ultra-slow muons (USM) [PTEP 091C01 (2014), PTEP 123C01 (2020)].





- J-PARC RFQ II (A spare of 30mA RFQ)




Structure	4-vane RFQ
$f_0$	<b>324 MHz</b>
$W_{in}$	<b>5.63 keV</b>
$W_{out}$	<b>0.337 MeV</b>
Vane length	3.172 m
# of cells	294
$r_0$	3.69 mm
$a_{min}$	2.11 mm
$m_{max}$	2.28
$\phi_{s,max}$	-44 ~ 48 deg
<b>V</b>	<b>9.32 kV</b>
Max. surface field	3.56 MV/m (0.2 $E_k$ )
<b>Nominal power</b>	<b>4.18 kW</b>



# The world's first RF accelerated muons!



- Epi-thermal  $\text{Mu}^-$  ( $\mu^+e^-e^-$ ) (not USM) is accelerated up to 89 keV.
- S. Bae et al., PRAB 21, 050101 (2018)



- TE110 mode (H mode) cavity
- $\pi$  mode operation ( $l_c = \frac{\beta\lambda}{2}$ )
- Alternative Phase Focusing (APF)



Structure	APF IH-DTL
$f_0$	324 MHz
<b>Operation mode</b>	<b><math>\pi</math></b>
$W_{in}$	0.337 MeV
$W_{out}$	4.26 MeV
Cavity length	1.32 m
# of cells	16
Bore radius	11.4 mm
$\phi_s$	<b>-44 ~ 48 deg</b>
Max. $E_0$	10 MV/m
ZTT	68 M $\Omega$ /m
Max. surface field	35.6 MV/m (2.0 $E_k$ )
Nominal power	310 kW

# IH-DTL fabrication



monolithic DT structure

Tuner

Fabrication of IH-DTL was completed.




# High power test of the IH-DTL prototype




Y. Nakazawa,  
MOPORI22

- Verify fabrication methodology with 6-cell IH-DTL.
- After 30 hour conditioning, 75 kW, 25 Hz, 40  $\mu$ s was achieved.
- No trip 88 kW (10% higher voltage )7 h operation,



$\beta = 0.27$

DAW 1<sup>st</sup> tank and bridge coupler model




DAW tank (11 cell)

Co-axial bridge coupler



Structure	DAW CCL
$f_0$	<b>1296 MHz</b>
Operation mode	$\pi/2$
$W_{in}$	4.26 MeV
$W_{out}$	<b>41.4 MeV</b>
Section length	16.15 m
# of tanks	<b>14</b>
# of modules	3
# of tanks / module	4, 5, 5
# of cells / tank	11
Bore radius	12 mm
$\phi_s$	-30 deg
$E_0$	<b>5.6 MV/m</b>
ZTT	18.6 ~ 62.7 M $\Omega$ /m
Max. surface field	28.9 MV/m (0.9 $E_k$ )
Max. power / tank	420 kW

$\beta = 0.7$



- Fabrication of DAW 1<sup>st</sup> tank is now underway.




Oxygen free copper




One 50 MW Klystron can drive 4 accelerating structures.



Structure	Disk loaded TW
$f_0$	<b>2592 MHz</b>
Operation mode	$2\pi/3$
$W_{in}$	41.4 MeV
$W_{out}$	212.4 MeV
Section length	9.8 m
# of acc. tunes	<b>4</b>
# of cells / tube	63, 63, 60, 60
Iris aperture diameter $2a$	<b>22.6 ~ 26.4 mm</b>
$\phi_s$	<b>-13 deg</b>
Max. $E_0$	<b>21 MV/m</b>
Z	32.2 ~ 57.0 M $\Omega$ /m
Max. power / tube	40 MW





## Proto-DL







• Fine tuning with detune rod

Note: distances are different (DLS1 downstream)  
 ①-②: 31.449 mm  
 Others: 31.436 mm









	Initial	RFQ	IH	DAW	DLS
transmission (%)	99	95	100	100	100
Decay loss (%)	22	19	1	4	1
$\epsilon_{n, rms, x}$ ( $\pi$ mm mrad)	0.51	0.25	0.27	0.27	0.28
$\epsilon_{n, rms, y}$ ( $\pi$ mm mrad)	0.12	0.18	0.19	0.21	0.22

Emittance evolution from the RFQ



Y. Takeuchi,  
TUPORI22

# Upcoming beam test plan



# Overall schedule of E34

**Construction budget assumed to be authorized**

FY	2021	2022	2023	2024	2025	2026	2027 and beyond
KEK Budget							
Surface muon		★ Beam at H1 area		★ Beam at H2 area			
Bldg. and facility			★ Final design			★ Completion	
Muon source		★ Ionization test @S2		★ Ionization test at H2			
<b>LINAC</b>			★ 80keV acceleration@S2	★ 4.3 MeV@ H2		★ fabrication complete	★ 210 MeV
Injection and storage			★ Completion of electron injection test				★ muon injection
Storage magnet				★ B-field probe ready		★ Install	★ Shimming done
Detector			★ Quater vane prototype	★ Mass production ready			★ Installation
DAQ and computing		★ grid service open	★ small DAQ system	★ common computing operation test	★ Ready		
Analysis				★ Tracking software ready	★ Analysis software ready		

**4y construction period**

**Commissioning**

**Data taking**

- We are now developing the world's first muon linac.
- Design work is almost finished.
- Among 4 accelerating structures, RFQ and IH-DTL are ready.
- Fabrication of DAW is started, and prototyping the DLS.
- Construction budget is expected to be authorized soon. We are moving from design phase to construction phase.

This work is supported by JSPS KAKENHI Grant Numbers JP15H03666, JP18H03707, JP16H03987, JP16J07784, JP20J21440, JP20H05625, JP21K18630, JP21H05088, JP22H00141; the JST FOREST Program (grant number JPMJFR2120); and the natural science grant of the Mitsubishi Foundation. This paper is based on results obtained from a project commissioned by the New Energy and Industrial Technology Development Organization (NEDO).