


Summary of the RHIC Performance during the FY07 Heavy Ion Run

- RHIC HI Operation
- Expectations and goals for Run 7
- Run-7 achievements
- Conclusions


Relativistic Heavy Ion Collider




Relativistic Heavy Ion Collider




Relativistic Heavy Ion Collider




Relativistic Heavy Ion Collider




Relativistic Heavy Ion Collider




Relativistic Heavy Ion Collider




Relativistic Heavy Ion Collider



Relativistic Heavy Ion Collider



Relativistic Heavy Ion Collider



Achieved beam parameters for Run7

- Avg. Luminosity gain: x2-3
- Int. Luminosity gain: x2
- Peak Luminosity gain: x2-2.5
- Reached maximum
 - Number of bunches
 - Transition crossing/bunch intensity
 - Luminosity lifetime? -> cooling
- **We reached the enhanced design goal**

run	year	β^* (m)	no. of bunches	ions/bunch 10^9	$\epsilon_{x,y}^{norm.}$ (π mm mrad)	\mathcal{L}_{peak} ($10^{26} \text{cm}^{-2} \text{s}^{-1}$)	$\mathcal{L}_{avg.}$	\mathcal{L}_{week} (μb^{-1})
design		2	55	1.0	15-40	9	2	50
enhanced design		1	111	1.0	15-40	30	8	300
Run-2	FY2001/02	1	55	0.5	15-40	3.7	1.5	24
Run-4	FY2004	1	45	1.1	15-40	15	5	160
Run-7	FY2007	0.8 (1.1?)	111	1.1	15-40	30	10-14	200-400





Expectations and Goals for Run-7

- Do better than Run-4
- Increase number of bunches to 111
- Reach 60% time at store on average
- Reach avg. luminosity/store
 - $> 8 \cdot 10^{26} \text{ cm}^{-2} \text{ s}^{-1}$ routinely
- Reach peak luminosity/store
 - $> 30 \cdot 10^{26} \text{ cm}^{-2} \text{ s}^{-1}$
- Increase bunch intensity





Expectations and Goals for Run-7

- Do better than Run-4 yes
- Increase number of bunches to 111 yes
- Reach 60% time at store on average no
- Reach avg. luminosity/store yes
 - $> 8 \cdot 10^{26} \text{ cm}^{-2} \text{ s}^{-1}$ routinely
- Reach peak luminosity/store yes
 - $> 30 \cdot 10^{26} \text{ cm}^{-2} \text{ s}^{-1}$
- Increase bunch intensity not really



Scrubbing at the beginning of the run


Pump failure





Before we could go for higher bunch numbers:

- Pressure bump moves from IR12 to IR4
- Pressure bump reduces after 4th high intensity injection
- Spend a total of 2 hours


Total Bunch Number 111->103



standard




Fancy Gap:
More crossings:
95->97




- beam losses along the bunch train (next slide)
- Rebucketing issues: debunching beam
- Higher bunch intensity?

Total Bunch Number 111->103





bluDCCTtotal (Y1) yelDCCTtotal (Y1) bluWCMbunched (Y1)
yelWCMbunched (Y1) ev-brebucket (Y1) PHENIX..ZDC. (Y2)


Total Bunch Number 111->103



standard




Fancy Gap:
More crossings:
95->97




- beam losses along the bunch train (next slide)
- Rebucketing issues: debunching beam
- Higher bunch intensity?

Losses along the bunch train

103
Std.





103
f.g.



- 103 std. ramp ($1.15e9$) shows beam blow up in all late bunches (ramp failed)
- Next 103 f.g. ramp with same bunch intensity ($1.17e9$) worked
- Gap pattern clearly visible in 8837
- 103 f.g. set to be default


Stochastic Cooling (Yellow only)

- Stochastic cooling was commissioned and made operational for the 2nd half of the run
- Yellow beam decay reduced to “burn-off” rate
- More beam in the center bucket
- Increased luminosity lifetime
- Net-effect on integrated luminosity 10%-20% (analysis not yet finished)
- Mechanical problems at the end of Run7



Stochastic Cooling (Yellow only)


- Stochastic cooling was commissioned and made operational for the 2nd half of the run
- Yellow beam decay reduced to “burn-off” rate
- More beam in the center bucket
- Increased luminosity lifetime
- Net-effect on integrated luminosity 10%-20% (analysis not yet finished)
- Mechanical problems at the end of Run7




Stochastic Cooling (Yellow only)

- Stochastic cooling was commissioned and made operational for the 2nd half of the run
- Yellow beam decay reduced to “burn-off” rate
- More beam in the center bucket
- Increased luminosity lifetime
- Net-effect on integrated luminosity 10%-20% (analysis not yet finished)
- Mechanical problems at the end of Run7

M. Blaskiewicz, “Stochastic Cooling of High Energy Bunched Beams”, WEYC02




Stochastic Cooling (contd.)



Blue beam
uncooled

- Uncooled beam has larger width of center bucket
- Cooled beam has significantly pronounced center and satellite buckets
- Exp. recorded luminosity (vertex cut) benefited from cooling as well


Stochastic Cooling (contd.)



Yellow beam
cooled


- Uncooled beam has larger width of center bucket
- Cooled beam has significantly pronounced center and satellite buckets
- Exp. recorded luminosity (vertex cut) benefited from cooling as well

Example of a good week (May 14-May 20)




Peak luminosity of $30 \cdot 10^{26} \text{ cm}^{-2} \text{ s}^{-1}$

Avg. store luminosity
of $8 \cdot 10^{26} \text{ cm}^{-2} \text{ s}^{-1}$




- 5 hours per store (nominal)
- This weeks integrated luminosity totaled $380 \mu\text{b}^{-1}$
- Stochastic cooling effect clearly visible
- Initial beam intensity routinely above $120 \cdot 10^9$

... and a not so good week ...



Bunch Intensity at Injection


Limited by transition crossing, e-cloud effects and exp. magnet polarity change




● blueBunchIntensity
1121.65

* yellowBunchIntensity
1090.16

Ramp Efficiency




Time between newfill and accramp (turn-around indicator)






• Time between Newfill and Accramp - - - - - 43 minutes

Run7 average luminosity/store highest with 103 bunches per ring






Low Energy Test @ 4.6 GeV

24 hour setup, collisions provided, vernier scan(s)




Low Energy Test @ 4.6 GeV

24 hour setup, collisions provided, vernier scan(s)




Failures in hours for Run-7 system by system

- Run-7 had
 - 13 weeks
 - late spring (temperature)
 - full magnetic field/current (Au@100 GeV)
 - Aging?
- Top 3: PS, cryo, RHIC RF
- Increase factors (from previous run to this run)
 - PS: x2.2
 - RF: x2.5
 - Cryo: x4.5




Run 7 Failures by system (to 6/12)




Failures in hours for Run-7 system by system

- Run-7 had
 - 13 weeks
 - late spring (temperature)
 - full magnetic field/current (Au@100 GeV)
 - Aging?
- Top 3: PS, cryo, RHIC RF
- Increase factors (from previous run to this run)
 - PS: x2.2
 - RF: x2.5
 - Cryo: x4.5




Week-by-week integrated luminosity Run 7



- 3 weeks above goal
- Contributing factors:
 - Temperature (late start of run), weather
 - Full field (Au @ 100 GeV)
 - Unprecedented intensity (beam loading)
 - Pushing the envelope (transition crossing, pressure rise, number of bunches etc.)
 - Aging?


Time at store over the years

- Data included until Jun 9th 2007
- Goal: 60%
- Reached 46%
- Failed to reach goal by about 15%
- Beam induced quenches not correlated with uptime but species => magnet current



Integrated Au-Au Luminosity Run-7

- Integrated luminosity well between min. and max. expectation
- Corrected for acc. collisions (due to high coll. rate)
- “bi-weekly” performance oscillation coinciding with maintenance days
- Slope change after experimental magnets polarity flip
- Integrated luminosity still in upper half even with only 45% time at store!



Conclusions

- Analysis of data not yet finished (Run-7 ended today)
- We met our goals (almost)
 - 111 (103) bunches
 - Exceeded $8 \cdot 10^{26} \text{ cm}^{-2} \text{ s}^{-1}$ avg. luminosity/store routinely
 - $30 \cdot 10^{26} \text{ cm}^{-1} \text{ s}^{-1}$ peak luminosity
 - Some weeks (3!) exceeded 300 ub^{-1} integrated luminosity
 - Achieved x2-3 more integrated luminosity than Run-4
- Bunch intensity limit ($\sim 1.2 \cdot 10^9$)
- Up-time or reliability needs significant changes:
 - Plans for next year
 - Long-term plans
- Stochastic Cooling concept worked very well





supplemental



Angelika Drees



Low Energy study: Challenges and Successes

○ Challenges

- h=366 invalid events stopped PHENIX, nearly stopped STAR, interfered with V125 abort trigger module
- 3-bucket cogging in h=366 prevented simultaneous expt cogging
- Unipolar defocusing sextupoles limited chromaticity to near zero
- Minor online model issues prevented full range of tune adjustment
- All challenges are addressible either offline or during test run setup

○ Successes

- LLRF worked like a charm, RF capture quick with phase detectors
- Instrumentation worked remarkably well with h=366 timing
- Orbit correction, coupling corrections worked well
- Longitudinal beam distribution shorter than expected (scraping?)
- Vernier scans still feasible even with 2-20 minute beam lifetimes
- Have data for luminosity measurement deliverable