



# 1.3 GHz Superconducting RF Cavity Program at Fermilab


C.M. Ginsburg, T. Arkan, S. Barbanotti, H. Carter, M. Champion, L. Cooley, C. Cooper, M. Foley, M. Ge, C. Grimm, E. Harms, A. Hocker, R. Kephart, T. Khabiboulline, J. Leibfritz, A. Lunin, J. Ozelis, Y. Pischalnikov, A. Rowe, W. Schappert, D. Sergatskov, A. Sukhanov, G. Wu

Fermilab




- ❑ 1.3 GHz SRF activity at FNAL supports Project X, ILC R&D, or other future SRF projects, and includes vendor development and associated cavity R&D for improved performance and reliability, and reduced cost
- ❑ Six 1.3 GHz cryomodules will be built at FNAL in the next few years
  - 1<sup>st</sup> cryomodule CM1 was built from a kit of parts supplied by DESY
  - Preparation of cavities and assembly infrastructure for CM2 is ongoing
- ❑ Facilities have been completed and some are being upgraded
  - FNAL/ANL cavity processing facility: surface processing and vertical/horizontal test prep
  - Vertical test system: bare cavity CW low-power acceptance test
  - Horizontal test system: dressed cavity pulsed high-power acceptance
  - Cryomodule assembly facility: dressed cavity ass'y into cryomodules
  - Cryomodule test facility at NML
- ❑ Overall goals of the 1.3 GHz SRF cavity program, supporting facilities, and accomplishments are described





cryomodule

- ❑ Located at ANL; designed, built, and operated jointly
- ❑ Electropolishing (EP) of 1-cell and 9-cell ILC-style cavities
- ❑ Ultrasonic rinse tank
- ❑ High-pressure water rinse (HPR) tool
- ❑ Clean rooms of class 10, 100, 1000
- ❑ Cavity vacuum system




1.Apr. 2011



Ginsburg (FNAL) PAC11 NYC




- ❑ One radiation shielded and magnetically shielded bare cavity test cryostat (VTS) in operation, typically operating at 2K
- ❑ Performance diagnostics include Cernox sensor “fast” thermometry, a new second sound system (adapted from Cornell), and routine, automated internal inspection of irises/equators (KEK/Kyoto system)
- ❑ One larger cryostat was delivered last week; another to be built in industry




VTS 1




VTS 2/3



KEK/Kyoto system optical inspection




Fast thermometry system



Second sound system

Suhane et al. TUP033  
 Maximenko and Sergatskov TUP082  
 Khabiboulline et al. TUP074

## ANL/FNAL SCSPF Cumulative Throughput




## CY2010: Surface process or test prep

- ☐ 44 electropolishing cycles
- ☐ 23 1-cell vertical test preps
- ☐ 32 9-cell vertical test preps


## CY2010: 81 vertical tests

- 38 9-cell, 39 1-cell, 4 R&D cavity tests

## Monthly VCTF Test Activity - FY08/09/10/11




## Americas 9-cell Cavities




- Many well performing cavities, including two cavities processed and tested at FNAL/ANL reaching ILC specification
- FNAL 9-cell tests done in strong collaboration with JLab and ANL, with important assistance from Cornell, KEK and DESY

- ❑ 17 cavities have been dressed for CM2 and subsequent CM's




- ❑ Weld (TIG) on helium vessel with helium two-phase pipe
- ❑ Magnetic shielding
- ❑ Blade type slow tuner (INFN Milano), piezo fast tuners
- ❑ High power coupler is TTF3 type (DESY)


- ❑ One dressed-cavity cryostat (HTS), operating@2K
- ❑ Tuner (fast and slow) tests, coupler conditioning, cavity performance
- ❑ New larger cryostat to cooldown two cavities simultaneously under devel.
- ❑ Have completed horizontal tests of ten 1.3 GHz 9-cell cavities
  - One cavity went to S1-Global CM
  - Three reached at least 35 MV/m
- ❑ Good agreement between vertical and horizontal test performance



HTS 1

Hocker et al. TUP071  
Pischalnikov et al. TUP082





- ❑ Fourteen cavities candidates for CM2; 13 pass ILC spec in vertical test
  - Three of these processed at FNAL/ANL, remainder at JLab
- ❑ Horizontal tests in progress
- ❑ Administrative gradient limit 35 MV/m imposed for horizontal tests after degradation of TB9ACC013 by arc event in input coupler
- ❑ TB9ACC013 and TB9ACC016 not tested with ILC pulse length due to FE
- ❑ Most instances of cavity degradation can be traced to FE
- ❑ Vacuum practices in all facilities under review; improvements expected

- ❑ Manufacturing/quality assurance optimization
  - Eddy current scanning investigation
  - X-ray tomography of welds
  - Cavity performance studies for cavity vendor fabrication qualification
- ❑ Cavity surface repair and surface processing optimization
  - Tumble polishing (repair or primary process), laser re-melting (repair)
    - Example of tumble-repaired 9-cell cavity: 19 -> 35 MV/m after tumble+EP sequence
    - Studies of performance as a function of surface finish
  - Dressed cavity electropolishing
- ❑ Basic SRF R&D
  - Understanding medium- and high-field Q-slope, associated with process type
  - Materials science of hot and cold spots using cut-outs
  - Optimization of RF surface properties: surface morphology, contamination, coatings, ...


Cooley THOCS2

CM1: a TESLA-style eight-cavity 1.3-GHz cryomodule


Receive dressed cavities and peripheral parts at CAF-MP9



Assemble dressed Cavities to form a String in the **Cavity String Assembly Area** (Clean Room)



Install String Assembly to Cold Mass in the **Cold Mass Assembly Area**



Transport the Cold Mass to **CAF-ICB**



Install the Cold Mass at CAF-ICB back to the Cold Mass Assembly Fixture in **Cold Mass Assembly Area**




Align Cavity String to the Cold Mass Support



Install the String assembly with the cold mass into the Vacuum vessel in the **Vacuum Vessel Assembly area**



Ship Completed Cryomodule to **NML** for testing



## ❑ Overall Goal

- Build a cryomodule test facility at the New Muon Lab building (NML) with ILC-like electron beam, using one, three and up to 6 CM's
  - Various Project-X parameters will also be tested with beam
- Provide a state-of-the-art facility for conducting advanced accelerator R&D [accelerator components, beam dynamics, instrumentation]


## ❑ Current Phase

- Infrastructure, RF power, cryogenics operational
- First cryomodule (CM1) and Capture Cavity-2 (CC2) installed and being tested without beam

## ❑ CM1 tests at NML (no beam)

- In 2010: final installation at NML, warm coupler conditioning, tuner tests, and cooldown to 2K
- Cold RF tests ongoing since Dec 2010
  - Cold coupler conditioning and cavity performance tests in progress
  - Of three tested so far, two cavities have retained their previous performance

Leibfritz et al. MOP009



- ❑ Processing/preparation/test facilities providing well performing cavities
  - Most processes are becoming routine after many 10's of cycles
  - Bare cavity processing throughput targets for CY2011 represent a 25-30% increase over CY2010
  - Incremental and R&D process development ongoing
- ❑ Aim to get 1.3 GHz SRF cavities qualified, dressed, and into cryomodules
  - Continue incremental improvements
  - Understand and eliminate cavity performance degradation among CM preparation stages - dressed cavity improvement is high priority
- ❑ Finish building 6 cryomodules in the next few years, starting with CM2
- ❑ Test them in the new NML facility, also with beam
- ❑ Have exercised nearly all steps in building a 1.3 GHz ILC-like cryomodule in preparation for next projects, e.g., Project X

Champion et al. THOCS6  
Nagaitsev et al. FROBN3