

HIE-ISOLDE cavity production & cryomodule commissioning: lessons learned

W. Venturini Delsolaro

K. Artoos, O. Capatina, Y. Kadi, Y. Leclercq, A. Miyazaki, E. Montesinos,
V. Parma, G. J. Rosaz, K. M. Schirm, A. R. M. Sublet,
S. Teixeira Lopez, M. Therasse, L.R. Williams,

CERN, Geneva, Switzerland




18th International Conference on
RF Superconductivity
Lanzhou China
July 17-21, 2017



Contents

- Status of HIE ISOLDE linac
- Notes on cavity series production
- Notes on cryomodule design and assembly
- Notes on cryomodule commissioning
- Summary


HIE ISOLDE linac in 2017




HIE-ISOLDE cryomodule







Cavity performance on line (3 CM)







Surface resistance fit parameters



1: performance improvements in linac




1: performance improvements in linac




Poster:THPB046


2: crack is evil



2: crack is evil




Cavity design evolution



Rolled sheets




Shrink fit




Seamless

See Silvia Teixeira Lopez's presentation tomorrow!


3: R (trapped flux) is higher for the best Nb/Cu cavities




4: R_s dependence on T gradient across T_c is cavity dependent




4: R_s dependence on T gradient across T_c is cavity dependent




6: $R(T) \neq R_{\text{BCS}}?$



6: $R(T) \neq R_{\text{BCS}}?$





5: $R_s(T)$ and $R_s(B)$ are positively correlated



7: Tuning system


- Carefully gather statistics on Δf (acceptance-operation) for pre-tuning
- Tuning plate: Trojan horse for vibrations.
Is plastic deformation taboo?





8: Endurance-test couplers in operational conditions!



8: Endurance-test couplers in operational conditions!



8: Endurance-test couplers in operational conditions!



9: Cryomodule design and assembly

Cryomodule design based on common vacuum and supporting system from the top plate:

- More compact and simpler mechanics, but
- Longer and more delicate assembly in clean room

- Procedures
- Logistics
- Blank assembly as much as possible
- Quality Assurance

Thermal shield nickel plated to reduce emissivity:

- May be overkilling
- Plating difficult to do with required quality

Thermal design and alignment concepts fully validated:

~ 10 W @ 4.5 K static; cavity/solenoid positioning < 0.1 mm


No cold leaks p ~ 10^{-11} mbar



Blank assembly of a seamless cavity, July 2017



10: cryomodule commissioning

- Horizontal test skipped: commissioning in the linac
- Controlled cool down
- Cryo-plant process → cavity detuning
- No venting without rinsing!
- He processing in situ works!



10: cryomodule commissioning

- Horizontal test skipped: commissioning in the linac
- Controlled cool down
- Cryo-plant process → cavity detuning
- No venting without rinsing!
- He processing in situ works!





Cavity measurement with beam

Comparison Energy Measurements:

We can compare the three independent methods to measure the energy of the beam:

- Calibration of the RF systems (W_{RF})
- First dipole of the XT01 HEBT line (W_B)
- TOF between silicon detectors in XT00 (W_{TOF})

#	E_{SRF08} [MV/m]	W_{RF} [MeV/u]	$\frac{W_{RF} - W_{TOF}}{W_{TOF}}$	W_B [MeV/u]	$\frac{W_B - W_{TOF}}{W_{TOF}}$	W_{TOF} [MeV/u]
E1	5.455	4.908	0.9 %	4.866	0.0 %	4.866
E2	4.455	4.846	1.0 %	4.810	0.3 %	4.797
E3	3.455	4.784	0.9 %	4.745	0.1 %	4.740
E4	2.455	4.722	0.9 %	4.677	-0.0 %	4.679
E5	1.455	4.659	0.8 %	4.631	0.2 %	4.621
E6	0.455	4.597	0.5 %	4.572	-0.0 %	4.574
E7	0.000	4.569	0.2 %	--	--	4.560



Summary

- **Nb/Cu technology was successfully used to build HIE-ISOLDE RIB linac serving a large physics community at CERN**
- 15 cavities are running at 4.5 K requiring ~ 100 W RF power for ~ 1.8 MV V_{acc}
- Cavity dissipation in the linac < 10 W at 6 MV/m
- Without magnetic shielding
- No interference from neighbouring superconducting solenoids
- >> 20 cavities coated with same method and cold tested
 - Importance of substrate quality for Nb/Cu
 - Importance of homogeneous ($\Delta T \rightarrow 0$) cool down across T_c
 - Surface resistance displaying intriguing behaviour and correlations
 - Cavity design and sputtering protocol further perfectible
- 3 cryomodules assembled, installed and commissioned in the linac (4th is coming)
 - Design choices validated
 - Importance of stress testing coupler and tuning systems in V tests
 - Nb/Cu QWR could be made insensitive to vibrations by a stiffer tuning plate
 - FE can be processed on line
 - RF measurements cross checked with TOF