



LCLS-II



LCLS-II-HE

# Industrial Cavity Production:

## Lessons Learned to Push the Boundaries of Nitrogen-Doping

Dan Gonnella *for the LCLS-II and LCLS-II HE Collaboration*


*SLAC National Accelerator Laboratory*

July 5, 2019



U.S. DEPARTMENT OF  
**ENERGY**

Stanford  
University



**SLAC**

NATIONAL  
ACCELERATOR  
LABORATORY



**Fermilab**

**Jefferson Lab**

- Introduction – the Need for High  $Q_0$
- LCLS-II Cavity Production Overview
- Lessons Learned from Cavity Production
- Nitrogen-Doping in the Future: LCLS-II HE
- Conclusions

- Introduction – the Need for High  $Q_0$
- LCLS-II Cavity Production Overview
- Lessons Learned from Cavity Production
- Nitrogen-Doping in the Future: LCLS-II HE
- Conclusions

# LCLS-II and LCLS-II HE Requirements

Parameter	LCLS-II	LCLS-II HE
# 1.3 GHz CMs	35	
Operating Gradient	16 MV/m	
Required $Q_0$ at Operating Gradient	$2.7 \times 10^{10}$	

**LCLS-II is constructing two 4 kW cryoplants @ 2 K**

- Operation at 4 GeV for LCLS-II can be achieved with a  $Q_0$  of  $1.2 \times 10^{10}$
- Single-cryoplant operation of LCLS-II is a necessary condition for the success of HE



# LCLS-II and LCLS-II HE Requirements

Parameter	LCLS-II	LCLS-II HE
# 1.3 GHz CMs	35	20
Operating Gradient	16 MV/m	20.8 MV/m for new CMs 18 MV/m for old CMs
Required $Q_0$ at Operating Gradient	$2.7 \times 10^{10}$	$2.7 \times 10^{10}$

## LCLS-II is constructing **two 4 kW** cryoplants @ 2 K

- Operation at **4 GeV** for LCLS-II can be achieved with a  $Q_0$  of  $1.2 \times 10^{10}$
- Single-cryoplant operation of LCLS-II is a necessary condition for the success of HE
- Operating at **8 GeV** for LCLS-II HE requires an average  $Q_0$  of  $2.7 \times 10^{10}$

Parameter	LCLS-II	LCLS-II HE
# 1.3 GHz CMs	35	20


**Achieving  $Q_0$ 's of at least  $2.7 \times 10^{10}$  required significant improvement and great care in previous industrial cavity performance**

LCLS-II is constructing **two 4 kW** cryoplants

- Operation at **4 GeV** for LCLS-II can be achieved with a  **$Q_0$  of  $1.2 \times 10^{10}$**
- Single-cryoplant operation of LCLS-II is a necessary condition for the success of HE
- Operating at **8 GeV** for LCLS-II HE requires an average  **$Q_0$  of  $2.7 \times 10^{10}$**

- Introduction – the Need for High  $Q_0$
- **LCLS-II Cavity Production Overview**
- Lessons Learned from Cavity Production
- Nitrogen-Doping in the Future: LCLS-II HE
- Conclusions

## 2/6 Nitrogen-Doping



- Cavities prepared with EP typically show  $Q_0 \sim 1.5 \times 10^{10}$  at medium fields with quench fields  $\sim 25$ -30 MV/m
- 2/6 Nitrogen-doping on average:
  - increases the  $Q_0$  by 100-200%
  - Lowers the quench field by  $\sim 20$ -30%

- To facilitate the construction of **36 Cryomodules** (34 production + 2 prototypes), **264 9-cell cavities** were ordered
  - This order was split 50/50 between RI and Zanon – previous success with XFEL
  - Material was split ~50/50 between Tokyo Denkai (TD) and Ningxia (NX)
  - Additionally **16 prototype cavities** were used (produced by AES with Wah-Chang material during ILC R&D studies)
- Midway through production additional cavities were ordered to allow for a total of **40 CMs** to be built and to account for cavity yield losses
  - This brings the total cavities purchased to **373**
  - These cavities were prepared with the 2/6 nitrogen-doping and were required to reach the LCLS-II specifications of:

$$Q_0 \geq 2.7 \times 10^{10} \text{ at } 16 \text{ MV/m}$$

$$E_{\text{max}} \geq 19 \text{ MV/m}$$

- To facilitate the construction of **36 Cryomodules** (34 production + 2 prototypes), **264 9-cell cavities** were ordered
  - This order was split 50/50 between RI and Zanon – previous success with XFEL
  - Material was split ~50/50 between Tokyo Denkai (TD) and Ningxia (NX)
  - Additionally **16 prototype cavities** were used (produced by AES with Wah-Chang material during ILC R&D studies)
- Midway through production additional cavities were ordered to allow for a total of **40 CMs** to be built and to account for cavity yield losses
  - This brings the total cavities purchased to **373**
  - These cavities were prepared with the 2/6 nitrogen-doping and were required to reach the LCLS-II specifications of:

$$Q_0 \geq 2.5 \times 10^{10} \text{ at } 16 \text{ MV/m}$$

$$E_{\max} \geq 19 \text{ MV/m}$$

- To facilitate the construction of **36 Cryomodules** (34 production + 2 prototypes), **264 9-cell cavities** were ordered
  - This order was split 50/50 between RI and Zanon – previous success with XFEL


**LCLS-II cavity requirements push the state-of-the-art considerably compared with XFEL and previous projects using similar SRF technology**

- This brings the total cavities purchased to **373**
- These cavities were prepared with the 2/6 nitrogen-doping and were required to reach the LCLS-II specifications of:

$$Q_0 \geq 2.5 \times 10^{10} \text{ at } 16 \text{ MV/m}$$

$$E_{\text{max}} \geq 19 \text{ MV/m}$$

# Baseline LCLS-II Cavity Preparation







- Introduction – the Need for High  $Q_0$
- LCLS-II Cavity Production Overview
- **Lessons Learned from Cavity Production**
- Nitrogen-Doping in the Future: LCLS-II HE
- Conclusions

# Overall Cavity Performance

## Gradient Reach




## $Q_0$



**Overall performance has been very good –  
cavities typically exceed requirements**


# Overall Cavity Performance

## Gradient Reach




- Poor fabrication techniques at EZ
- Furnace contamination at high temperatures
- Good procedures

## $Q_0$




- Poor fabrication techniques at EZ
- Insufficient heat treatment to improve flux expulsion
- Good procedures

# Lesson Learned: $Q_0$ and Flux Expulsion




# Lesson Learned: $Q_0$ and Flux Expulsion

$Q_0$




- First article cavities were made with TD material and heat treated at 800°C




# Lesson Learned: $Q_0$ and Flux Expulsion

- First article cavities were made with TD material and heat treated at 800°C
- Low  $Q_0$  was attributed to flux trapping causing high residual resistance




# Lesson Learned: $Q_0$ and Flux Expulsion

- First article cavities were made with TD material and heat treated at 800°C
- Low  $Q_0$  was attributed to flux trapping causing high residual resistance
- Increase of the heat treatment temperature to 900°C improved flux expulsion



# Lesson Learned: $Q_0$ and Flux Expulsion

- First article cavities were made with TD material and heat treated at 800°C
- Low  $Q_0$  was attributed to flux trapping causing high residual resistance
- Increase of the heat treatment temperature to 900°C improved flux expulsion
- It was later found that material from different vendors did not respond to the same heat treatment temperatures
  - NX material typically required higher temperatures for the same flux expulsion
  - Some TD material required higher temperatures




**Midway through production: single-cell cavities were built for remaining material batches and material was sorted prior to cavity construction**



# Lesson Learned: $Q_0$ and Flux Expulsion

- First article cavities were made with TD material and heat treated at 800°C
- Low  $Q_0$  was attributed to flux trapping




**Lesson Learned: Flux expulsion for all material batches must be verified on single-cell cavities to determine correct heat treatment temperature**

- NX material typically required higher temperatures for the same flux expulsion
- Some TD material required higher temperatures

Midway through production: single-cell cavities were built for remaining material batches and material was sorted prior to cavity construction


# Overall Cavity Performance

## Gradient Reach



- Poor fabrication techniques at EZ
- Furnace contamination at high temperatures
- Good procedures


## $Q_0$



- Poor fabrication techniques at EZ
- Insufficient heat treatment to improve flux expulsion
- Good procedures


# Overall Cavity Performance

## Gradient Reach



- **Poor fabrication techniques at EZ**
- Furnace contamination at high temperatures
- Good procedures


## $Q_0$



- **Poor fabrication techniques at EZ**
- Insufficient heat treatment to improve flux expulsion
- Procedures Improved


# Lesson Learned: Fabrication Techniques at EZ

## First EZ Production



- First nitrogen-doped cavities produced by EZ for LCLS-II showed low quench fields and a strong Q-slope above 13 MV/m
- Production was placed on hold at EZ and a full audit of fabrication procedures was undertaken


# Lesson Learned: Fabrication Techniques at EZ



Very rough EP'ed surface  
Zanon initial production


- Incomplete transfer of new EP technology to EZ resulted in etching, which in turn caused rough surfaces for the first ~25 cavities
- EP procedures improved via on-site presence by JLab staff

- Incorrect cell polishing prior to welding
- Whole-cell grinding with aggressive tooling resulted in the burial of normal conducting media
- Corrected through thorough vetting of procedures and retraining by JLab and SLAC staff




# Lesson Learned: Fabrication Techniques at EZ

- LCLS-II contract did not forbid weld splatter
- Many of the first ~70 cavities had internal and external weld splatter
- **This is not acceptable for high performing cavities as the splatter is highly correlated to cat eye defects**
- Improved through multi-week, hands-on training and review during weld stack-up, and weld prep machining




- ~70 cavities produced by EZ for LCLS-II required rework
- These cavities were in various states of production and required different rework paths
- Typically involved BCP to attack normal conducting media

# Lesson Learned: Fabrication Techniques at EZ




# Lesson Learned: Fabrication Techniques at EZ



- Repair of EP and grinding procedures improved gradient performance moderately




# Lesson Learned: Fabrication Techniques at EZ




- Repair of EP and grinding procedures improved gradient performance moderately
- Improvement of weld stackup procedures resulted in cavities with performance in line with RI

# Lesson Learned: Fabrication Techniques at EZ



- Repair of EP and grinding procedures improved gradient performance moderately
- Improvement of weld stackup procedures resulted in cavities with performance in line with RI
- Rework had ~50% success


# Lesson Learned: Fabrication Techniques at EZ



- Repair of EP and grinding procedures improved gradient performance moderately
- Improvement of weld stackup procedures resulted in cavities with performance in line with RI
- Rework had ~50% success
  - Cavities which were already fabricated had lower chance of rework success compared with dumbbells

- Repair of EP and grinding procedures improved gradient


**Lesson Learned: Thorough vetting of fabrication procedures and on-site presence at vendors is crucial to maintain excellent performance**



- Cavities which were already fabricated had lower chance of rework success compared with dumbbells


# Lesson Learned: Furnace Contamination

## Gradient Reach




# Lesson Learned: Furnace Contamination

## Gradient Reach




# Lesson Learned: Furnace Contamination



- **NO CORRELATION** between niobium manufacturer and quench field
- Typically no correlation between heat treatment temperature and quench field has been observed


# Lesson Learned: Furnace Contamination



- **NO CORRELATION** between niobium manufacturer and quench field
- Typically no correlation between heat treatment temperature and quench field has been observed
- However, cavities treated **ABOVE 950°C** in RI's furnace showed a statistically significant **drop in quench field**
  - Suggests presence of contamination that outgasses above 950°C



# Lesson Learned: Furnace Contamination




- **NO CORRELATION** between niobium manufacturer and quench field
- Typically no correlation between heat treatment temperature and quench field has been observed
- However, cavities treated **ABOVE 950°C** in RI's furnace showed a statistically significant **drop in quench field**
  - Suggests presence of contamination that outgasses above 950°C
- Likewise, EZ's furnace was found to be contaminated near the end of production and is in the process of being rehabilitated

# Lesson Learned: Furnace Contamination

- NO CORRELATION between niobium manufacturer and quench field


**Lesson Learned: Great care must be taken to maintain furnace cleanliness – when high  $Q_0$  requires high temperature treatment consider a two-stage furnace treatment cycle with EP between**



- contamination that outgasses above 950°C
- Likewise, EZ's furnace was found to be contaminated near the end of production and has since been rehabilitated


# Overall Cavity Performance

## Gradient Reach



- Poor fabrication techniques at EZ
- Furnace contamination at high temperatures
- Good procedures


## $Q_0$



- Poor fabrication techniques at EZ
- Insufficient heat treatment to improve flux expulsion
- Good procedures


# Overall Cavity Performance

## Gradient Reach





- Poor fabrication techniques at EZ
- Furnace contamination at high temperatures
- **Good procedures**

## $Q_0$



- Poor fabrication techniques at EZ
- Insufficient heat treatment to improve flux expulsion
- **Good procedures**


# Improved Cavity Performance



**Both vendors now produce excellent nitrogen-doped cavities**

Parameter	Value
$\langle E_{acc} \rangle$	23.1 MV/m
$\langle Q_0 \rangle$	$3.3 \times 10^{10}$


# LCLS-II Cavity Qualification




Qualification:

$E_{\text{quench}} \geq 19 \text{ MV/m},$   
 $Q_0(16 \text{ MV/m}, 2 \text{ K}) \geq 2.5 \times 10^{10}$

# LCLS-II Cavity Qualification



# LCLS-II Cavity Qualification







- Introduction – the Need for High  $Q_0$
- LCLS-II Cavity Production Overview
- Lessons Learned from Cavity Production
- **Nitrogen-Doping in the Future: LCLS-II HE**
- Conclusions

- LCLS-II asked: “can we operate at medium fields with high  $Q_0$ ?”
- XFEL asked: “can we operate at high fields (low to mid 20s)?”

### WHY NOT BOTH?

- LCLS-II HE will operate at high fields **WITH** high  $Q_0$
- Cavities in the linac will operate at 20.8 MV/m
- In VT, these cavities are required to achieve 23 MV/m with a  **$Q_0$  of  $2.7 \times 10^{10}$  at 21 MV/m**


## 2/6 Doping and LCLS-II HE



**~42% of LCLS-II cavities do not meet the  
LCLS-II HE vertical test specification**  
**A change to the doping is required**

# Pushing the Boundaries of Nitrogen-Doping


## 3/60 Doping



- Two new doping recipes have been explored: 3/60 and 2/0

- Both recipes have shown excellent progress on single-cells
  - Nearly all single-cell cavities tested exceed the HE requirements

## 2/0 Doping





# Pushing the Boundaries of Nitrogen-Doping

SLAC

## 2/0 Recipe on 9-Cell


3/60



- Both recipes progress on
- Nearly a
- exceed the HE requirements


been

ng





## 2/0 Recipe on 9-Cell

e been



**For more details see *D. Bafia's presentation* TUFUA4 and MOP044**



- Both recipes progress on
- Nearly all
- exceed the HE requirements

- Introduction – the Need for High  $Q_0$
- LCLS-II Cavity Production Overview
- Lessons Learned from Cavity Production
- Nitrogen-Doping in the Future: LCLS-II HE
- **Conclusions**

# Conclusions

- LCLS-II cavity production has resulted in nearly 400 nitrogen-doped cavities produced by industry and performance has been excellent but there have been important lessons learned:
  - **Flux expulsion for all material batches must be verified on single-cell cavities to determine correct heat treatment temperature**
  - **Thorough vetting of fabrication procedures and on-site presence at vendors is crucial to maintain excellent performance**
  - **Great care must be taken to maintain furnace cleanliness**
- The strict requirements of nitrogen-doping laid bare issues that had not manifested in earlier projects
- **With project oversight, cavity vendors can produce cavities that achieve  $Q_0 > 3 \times 10^{10}$  at 2 K with good gradient reach**
  - **High  $Q_0$  SRF Cavity production is moving towards industrialization**
- LCLS-II HE will continue to push the boundaries of nitrogen-doping and pursue a cavity recipe which produces high  $Q_0$  with higher gradient reach
  - Early results have been exceptional



# Acknowledgments

SLAC

Special thanks to the LCLS-II and LCLS-II HE collaboration at multiple labs around the US and to our cavity vendors in Europe!

**Thanks for your attention!**

